

## SAFETY DATA SHEET

### 1. Identification

**Material name:** POLYROOF LV 5 GL  
**Material:** 361591 805

**Recommended use and restriction on use**

**Recommended use:** Sealant  
**Restrictions on use:** Not known.

**Manufacturer/Importer/Supplier/Distributor Information**

WATERPROOFING TECHNOLOGIES INC.  
3735 Green road  
Beachwood OH 44122  
US

**Contact person:** EH&S Department  
**Telephone:**  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

### 2. Hazard(s) identification

**Hazard Classification**

**Health Hazards**

|   |             |
|---|-------------|
| Acute toxicity (Inhalation - dust and mist) | Category 4  |
| Serious Eye Damage/Eye Irritation           | Category 2B |
| Germ Cell Mutagenicity                      | Category 1B |
| Carcinogenicity                             | Category 1A |
| Toxic to reproduction                       | Category 1B |

**Unknown toxicity - Health**

|  |         |
|--|---------|
| Acute toxicity, oral                     | 0.93 %  |
| Acute toxicity, dermal                   | 1.61 %  |
| Acute toxicity, inhalation, vapor        | 99.76 % |
| Acute toxicity, inhalation, dust or mist | 94.79 % |

**Environmental Hazards**

|  |            |
|--|------------|
| Acute hazards to the aquatic environment | Category 2 |
|--|------------|

**Unknown toxicity - Environment**

|  |         |
|--|---------|
| Acute hazards to the aquatic environment   | 74.01 % |
| Chronic hazards to the aquatic environment | 99.33 % |

## Label Elements

### Hazard Symbol:



**Signal Word:** Danger

**Hazard Statement:** Harmful if inhaled.  
Causes eye irritation.  
May cause genetic defects.  
May cause cancer.  
May damage fertility or the unborn child.  
Toxic to aquatic life.

### Precautionary Statements

**Prevention:** Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a POISON CENTER/doctor/ if you feel unwell.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations; and product characteristics at time of disposal.

**Hazard(s) not otherwise classified (HNOC):** None.

## 3. Composition/information on ingredients

### Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|-------------------|------------|-------------------------|
|-------------------|------------|-------------------------|

|                                       |            |            |
|---------------------------------------|------------|------------|
| Asphalt                               | 8052-42-4  | 20 - <50%  |
| Xylene                                | 1330-20-7  | 10 - <20%  |
| Amorphous silica                      | 7631-86-9  | 5 - <10%   |
| Coal tar pitch                        | 65996-93-2 | 1 - <5%    |
| Ethylbenzene                          | 100-41-4   | 1 - <5%    |
| Petroleum distillates                 | 64741-81-7 | 1 - <5%    |
| Residues (petroleum), thermal cracked | 64741-80-6 | 1 - <5%    |
| Polyethylene                          | 9002-88-4  | 0.1 - <1%  |
| Carbon Black                          | 1333-86-4  | 0.1 - <1%  |
| Toluene                               | 108-88-3   | 0.1 - <1%  |
| Fluorathene                           | 206-44-0   | 0.01 - <1% |

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor/ if you feel unwell. Rinse mouth.
- Inhalation:** Move to fresh air.
- Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

#### Most important symptoms/effects, acute and delayed

**Symptoms:** May cause skin and eye irritation.

#### Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

#### 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

#### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

#### Special protective equipment and precautions for firefighters

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** No data available.

**Methods and material for containment and cleaning up:** Stop the flow of material, if this is without risk. Absorb with sand or other inert absorbent.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

## 7. Handling and storage

**Precautions for safe handling:** Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities:** Store locked up.

## 8. Exposure controls/personal protection

### Control Parameters

#### Occupational Exposure Limits

| Chemical Identity                                   | Type | Exposure Limit Values | Source   |
|---|------|-----------------------|--|
| Asphalt - Inhalable fraction. - as benzene solubles | TWA  | 0.5 mg/m3             | US. ACGIH Threshold Limit Values (2011)                                |
| Xylene  | STEL | 150 ppm 655 mg/m3     | US. NIOSH: Pocket Guide to Chemical Hazards (2010)                     |
|   | REL  | 100 ppm 435 mg/m3     | US. NIOSH: Pocket Guide to Chemical Hazards (2010)                     |
|   | STEL | 150 ppm 655 mg/m3     | US. NIOSH: Pocket Guide to Chemical Hazards (2010)                     |
|   | REL  | 100 ppm 435 mg/m3     | US. NIOSH: Pocket Guide to Chemical Hazards (2010)                     |
|   | STEL | 150 ppm 655 mg/m3     | US. NIOSH: Pocket Guide to Chemical Hazards (2010)                     |
|   | REL  | 100 ppm 435 mg/m3     | US. NIOSH: Pocket Guide to Chemical Hazards (2010)                     |
|   | STEL | 150 ppm 655 mg/m3     | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)                         |
|   | TWA  | 100 ppm 435 mg/m3     | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)                         |
|   | TWA  | 100 ppm 435 mg/m3     | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008) |
|   | STEL | 150 ppm 655 mg/m3     | US. Tennessee. OELs. Occupational Exposure                             |

|   |         |  | Limits, Table Z1A (06 2008)  |
|---|---------|--|--|
|   | ST ESL  | 350 µg/m3                                      | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)  |
|   | ST ESL  | 80 ppb   | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)  |
|   | AN ESL  | 42 ppb   | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)  |
|   | AN ESL  | 180 µg/m3                                      | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)  |
|   | STEL    | 150 ppm 655 mg/m3                              | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
|   | Ceiling | 300 ppm  | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
|   | TWA PEL | 100 ppm 435 mg/m3                              | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
|   | TWA     | 100 ppm  | US. ACGIH Threshold Limit Values (2011)  |
|   | STEL    | 150 ppm  | US. ACGIH Threshold Limit Values (2011)  |
|   | PEL     | 100 ppm 435 mg/m3                              | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)                |
| Amorphous silica                                | TWA     | 20 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)   |
|   | TWA     | 0.8 mg/m3                                      | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)   |
| Coal tar pitch - Aerosol. - as benzene solubles | TWA     | 0.2 mg/m3                                      | US. ACGIH Threshold Limit Values (2011)  |
| Coal tar pitch                                  | PEL     | 0.2 mg/m3                                      | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)                |
| Ethylbenzene                                    | TWA     | 20 ppm   | US. ACGIH Threshold Limit Values (2011)  |
|   | PEL     | 100 ppm 435 mg/m3                              | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)                |
| Polyethylene - Inhalable particles.             | TWA     | 10 mg/m3                                       | US. ACGIH Threshold Limit Values (03 2015)   |
| Polyethylene - Respirable particles.            | TWA     | 3 mg/m3  | US. ACGIH Threshold Limit Values (03 2015)   |
| Polyethylene - Respirable fraction.             | PEL     | 5 mg/m3  | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)                |
| Polyethylene - Total dust.                      | PEL     | 15 mg/m3                                       | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)                |
|   | TWA     | 15 mg/m3                                       | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)   |
|   | TWA     | 50 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)   |
| Polyethylene - Respirable fraction.             | TWA     | 5 mg/m3  | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)   |
|   | TWA     | 15 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)   |
| Carbon Black - Inhalable fraction.              | TWA     | 3 mg/m3  | US. ACGIH Threshold Limit Values (2011)  |
| Carbon Black                                    | PEL     | 3.5 mg/m3                                      | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)                |
| Toluene   | TWA     | 20 ppm   | US. ACGIH Threshold Limit Values (2011)  |
|   | TWA     | 200 ppm  | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)  |
|   | Ceiling | 300 ppm  | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)  |

|  |           |         |   |
|--|-----------|---------|---|
|  | MAX. CONC | 500 ppm | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
|--|-----------|---------|---|

| Chemical name                                       | Type | Exposure Limit Values | Source  |
|---|------|-----------------------|---|
| Asphalt - Aerosol, inhalable. - as benzene solubles | TWA  | 0.5 mg/m3             | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Asphalt - Inhalable fraction. - as benzene solubles | TWA  | 0.5 mg/m3             | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
| Asphalt - Fume.                                     | TWA  | 5 mg/m3               | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
| Xylene  | TWA  | 100 ppm 434 mg/m3     | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)   |
|   | STEL | 150 ppm 651 mg/m3     | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)   |
| Xylene  | TWA  | 100 ppm               | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
|   | STEL | 150 ppm               | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Xylene  | TWA  | 100 ppm               | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
|   | STEL | 150 ppm               | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
| Xylene  | TWA  | 100 ppm 434 mg/m3     | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
|   | STEL | 150 ppm 651 mg/m3     | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
| Amorphous silica - Total                            | TWA  | 4 mg/m3               | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Amorphous silica - Respirable.                      | TWA  | 1.5 mg/m3             | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Amorphous silica - Respirable dust.                 | TWA  | 6 mg/m3               | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
| Coal tar pitch - Aerosol. - as benzene solubles     | TWA  | 0.2 mg/m3             | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Coal tar pitch - Aerosol. - as benzene solubles     | TWA  | 0.2 mg/m3             | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
| Coal tar pitch - as benzene solubles                | TWA  | 0.2 mg/m3             | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
| Ethylbenzene  | TWA  | 20 ppm                | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011) |
| Ethylbenzene  | TWA  | 20 ppm                | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)  |
| Ethylbenzene  | TWA  | 100 ppm 434 mg/m3     | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
|   | STEL | 125 ppm 543 mg/m3     | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |

|                                    |     |                  |   |
|------------------------------------|-----|------------------|---|
| Carbon Black - Inhalable           | TWA | 3 mg/m3          | Environment) (12 2008)<br>Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011) |
| Carbon Black - Inhalable fraction. | TWA | 3 mg/m3          | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)  |
| Carbon Black                       | TWA | 3.5 mg/m3        | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
| Toluene                            | TWA | 20 ppm           | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)                           |
| Toluene                            | TWA | 20 ppm           | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
| Toluene                            | TWA | 50 ppm 188 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |

### Biological Limit Values

| Chemical Identity  | Exposure Limit Values          | Source              |
|--|--------------------------------|---------------------|
| Xylene (Methylhippuric acids: Sampling time: End of shift.)                                | 1.5 g/g (Creatinine in urine)  | ACGIH BEI (03 2013) |
| Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.) | 0.15 g/g (Creatinine in urine) | ACGIH BEI (02 2014) |
| Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.)                          | 0.3 mg/g (Creatinine in urine) | ACGIH BEI (03 2013) |
| Toluene (toluene: Sampling time: Prior to last shift of work week.)                        | 0.02 mg/l (Blood)              | ACGIH BEI (03 2013) |
| Toluene (toluene: Sampling time: End of shift.)  | 0.03 mg/l (Urine)              | ACGIH BEI (03 2013) |

### Appropriate Engineering Controls

No data available.

### Individual protection measures, such as personal protective equipment

|                                |   |
|--------------------------------|---|
| <b>General information:</b>    | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc. |
| <b>Eye/face protection:</b>    | Wear safety glasses with side shields (or goggles).   |
| <b>Skin Protection</b>         |   |
| <b>Hand Protection:</b>        | No data available.  |
| <b>Other:</b>                  | Wear suitable protective clothing.  |
| <b>Respiratory Protection:</b> | In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.   |

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use.

## 9. Physical and chemical properties

### Appearance

|  |   |
|--|---|
| <b>Physical state:</b>                                       | solid   |
| <b>Form:</b>   | Paste   |
| <b>Color:</b>  | Black   |
| <b>Odor:</b>   | Slight odor   |
| <b>Odor threshold:</b>                                       | No data available.  |
| <b>pH:</b>   | No data available.  |
| <b>Melting point/freezing point:</b>                         | No data available.  |
| <b>Initial boiling point and boiling range:</b>              | No data available.  |
| <b>Flash Point:</b>  | No data available.  |
| <b>Evaporation rate:</b>                                     | Slower than Ether   |
| <b>Flammability (solid, gas):</b>                            | No  |
| <b>Upper/lower limit on flammability or explosive limits</b> |   |
| <b>Flammability limit - upper (%):</b>                       | No data available.  |
| <b>Flammability limit - lower (%):</b>                       | No data available.  |
| <b>Explosive limit - upper (%):</b>                          | No data available.  |
| <b>Explosive limit - lower (%):</b>                          | No data available.  |
| <b>Vapor pressure:</b>                                       | No data available.  |
| <b>Vapor density:</b>  | Vapors are heavier than air and may travel along the floor and in the bottom of containers. |
| <b>Relative density:</b>                                     | 1.02  |
| <b>Solubility(ies)</b>                                       |   |
| <b>Solubility in water:</b>                                  | Practically Insoluble   |
| <b>Solubility (other):</b>                                   | No data available.  |
| <b>Partition coefficient (n-octanol/water):</b>              | No data available.  |
| <b>Auto-ignition temperature:</b>                            | No data available.  |
| <b>Decomposition temperature:</b>                            | No data available.  |
| <b>Viscosity:</b>  | No data available.  |

## 10. Stability and reactivity

|  |   |
|--|---|
| <b>Reactivity:</b>                         | No data available.                          |
| <b>Chemical Stability:</b>                 | Material is stable under normal conditions. |
| <b>Possibility of hazardous reactions:</b> | No data available.                          |
| <b>Conditions to avoid:</b>                | Avoid heat or contamination.                |



**Incompatible Materials:** Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).

**Hazardous Decomposition Products:** Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation:** In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

**Skin Contact:** May be harmful in contact with skin. Causes mild skin irritation.

**Eye contact:** Causes eye irritation.

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

**Oral Product:** ATEmix: 12,414.2 mg/kg

**Dermal Product:** ATEmix: 3,418.07 mg/kg

**Inhalation Product:** ATEmix: 4.1 mg/l

**Repeated dose toxicity Product:** No data available.

**Skin Corrosion/Irritation Product:** No data available.

**Specified substance(s):**

|                  |   |
|------------------|---|
| Asphalt          | in vivo (Rabbit): Not irritant Experimental result, Key study                     |
| Xylene           | in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study |
| Amorphous silica | in vivo (Rabbit): Not irritant Experimental result, Key study                     |
| Coal tar pitch   | in vivo (Rabbit): Not irritant Experimental result, Key study                     |
| Carbon Black     | in vivo (Rabbit): Not irritant Experimental result, Key study                     |
| Toluene          | in vivo (Rabbit): Irritating Experimental result, Key study                       |

### Serious Eye Damage/Eye Irritation

**Product:** No data available.

**Specified substance(s):**

|                  |                                       |
|------------------|---------------------------------------|
| Asphalt          | Rabbit, 24 hrs: Not irritating        |
| Xylene           | Rabbit, 24 hrs: Moderately irritating |
| Amorphous silica | Rabbit, 24 hrs: Not irritating        |
| Coal tar pitch   | Rabbit, 1 hrs: Not irritating         |
| Ethylbenzene     | Rabbit, 7 d: Slightly irritating      |
| Carbon Black     | Rabbit, 24 - 72 hrs: Not irritating   |
| Toluene          | Rabbit, 24 - 72 hrs: Not irritating   |

### Respiratory or Skin Sensitization

**Product:** No data available.

### Carcinogenicity

**Product:** No data available.

## IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

|                       |  |
|-----------------------|--|
| Asphalt               | Overall evaluation: Possibly carcinogenic to humans. |
| Coal tar pitch        | Overall evaluation: Carcinogenic to humans.          |
| Ethylbenzene          | Overall evaluation: Possibly carcinogenic to humans. |
| Petroleum distillates | Overall evaluation: Possibly carcinogenic to humans. |
| Carbon Black          | Overall evaluation: Possibly carcinogenic to humans. |

## US. National Toxicology Program (NTP) Report on Carcinogens:

Coal tar pitch Known To Be Human Carcinogen.

## US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

## Germ Cell Mutagenicity

**In vitro**  
Product: No data available.

**In vivo**  
Product: No data available.

**Reproductive toxicity**  
Product: May damage fertility or the unborn child.

**Specific Target Organ Toxicity - Single Exposure**  
Product: No data available.

**Specific Target Organ Toxicity - Repeated Exposure**  
Product: No data available.

**Aspiration Hazard**  
Product: No data available.

**Other effects:** No data available.

RECEIVED KQD/  
16 MAR 13 AM 8:29

## 12. Ecological information

### Ecotoxicity:

#### Acute hazards to the aquatic environment:

##### Fish

**Product:** No data available.

##### Specified substance(s):

|              |   |
|--------------|---|
| Xylene       | LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality              |
| Ethylbenzene | LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality |
| Toluene      | LC 50 (Fathead minnow (Pimephales promelas), 96 h): 20.5 - 23.8 mg/l Mortality        |
| Fluorathene  | LC 50 (Fathead minnow (Pimephales promelas), 96 h): 0.074 - 0.113 mg/l Mortality      |

##### Aquatic Invertebrates

**Product:** No data available.

##### Specified substance(s):

|              |  |
|--------------|--|
| Ethylbenzene | EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication   |
| Toluene      | LC 50 (Water flea (Daphnia magna), 24 h): 240 - 420 mg/l Mortality   |
| Fluorathene  | LC 50 (Water flea (Daphnia magna), 24 h): 1,000 - 1,600 mg/l Mortality<br>EC 50 (Water flea (Daphnia magna), 7 d): > 0.01 - 0.012 mg/l Intoxication<br>LC 50 (Purple-spined sea urchin (Arbacia punctulata), 48 h): > 0.127 mg/l Mortality<br>EC 50 (Water flea (Daphnia magna), 7 d): > 0.01 - 0.015 mg/l Intoxication<br>LC 50 (Purple-spined sea urchin (Arbacia punctulata), 96 h): > 0.033 mg/l Mortality |

#### Chronic hazards to the aquatic environment:

##### Fish

**Product:** No data available.

##### Specified substance(s):

|                       |   |
|-----------------------|---|
| Asphalt               | NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study<br>LL 50 (Oncorhynchus mykiss, 28 d): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study |
| Coal tar pitch        | LC 50 (Danio rerio, 42 d): > 4 µg/l Read-across from supporting substance (structural analogue or surrogate), Key study<br>NOAEL (Danio rerio, 42 d): 4 µg/l Read-across from supporting substance (structural analogue or surrogate), Key study                            |
| Petroleum distillates | NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study  |
| Residues (petroleum), | NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study  |

thermal cracked

**Toluene**  
 LOAEL (Oncorhynchus kisutch, 40 d): 2.77 mg/l Experimental result, Key study  
 NOAEL (Pimephales promelas, 32 d): 4 mg/l Experimental result, Supporting study  
 LOAEL (Pimephales promelas, 32 d): 6 mg/l Experimental result, Supporting study  
 NOAEL (Oncorhynchus kisutch, 40 d): 1.39 mg/l Experimental result, Key study

**Aquatic Invertebrates**

**Product:** No data available.

**Toxicity to Aquatic Plants**

**Product:** No data available.

**Persistence and Degradability**

**Biodegradation**

**Product:** No data available.

**BOD/COD Ratio**

**Product:** No data available.

**Bioaccumulative potential**

**Bioconcentration Factor (BCF)**

**Product:** No data available.

**Specified substance(s):**

Toluene Green algae (Selenastrum capricornutum), Bioconcentration Factor (BCF): 3,016 (Static)

Fluorathene Water flea (Daphnia magna), Bioconcentration Factor (BCF): 1,741.8 (Static)

**Partition Coefficient n-octanol / water (log Kow)**

**Product:** No data available.

**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Toluene Log Kow: 2.73

Fluorathene Log Kow: 5.16

**Mobility in soil:**

No data available.

**Other adverse effects:**

Toxic to aquatic organisms.

RECEIVED ICCDA  
18 MAR 13 AM 8:29

## 13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

## 14. Transport information

**TDG:**

Not Regulated

**CFR / DOT:**

Not Regulated

**IMDG:**

Not Regulated

## 15. Regulatory information

**US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**  
None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

| <u>Chemical Identity</u> | <u>OSHA hazard(s)</u>  |
|--------------------------|--|
| Benzene                  | Blood<br>respiratory tract irritation<br>Central nervous system<br>Flammability<br>Cancer<br>Skin<br>Aspiration<br>Eye |

**CERCLA Hazardous Substance List (40 CFR 302.4):**

| <u>Chemical Identity</u>                     | <u>Reportable quantity</u> |
|--|----------------------------|
| Asphalt                                      | 100 lbs.                   |
| Xylene                                       | 100 lbs.                   |
| Ethylbenzene                                 | 1000 lbs.                  |
| Toluene                                      | 1000 lbs.                  |
| Fluorathene                                  | 100 lbs.                   |
| Phenanthrene                                 | 5000 lbs.                  |
| Naphthalene                                  | 100 lbs.                   |
| Anthracene                                   | 5000 lbs.                  |
| Indeno[1,2,3-cd]pyrene                       | 100 lbs.                   |
| Benzo(a)anthracene                           | 10 lbs.                    |
| Chrysene                                     | 100 lbs.                   |
| Benzo(a)pyrene                               | 1 lbs.                     |
| Acenaphthene                                 | 100 lbs.                   |
| Dibenzofuran                                 | 100 lbs.                   |
| Benzo(b)fluoranthene/benzo[e]acefenantrileno | 1 lbs.                     |
| Biphenyl                                     | 100 lbs.                   |
| Dibenz(a,h)anthracene                        | 1 lbs.                     |
| Benzene                                      | 10 lbs.                    |

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard

**SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

**SARA 304 Emergency Release Notification**

| <u>Chemical Identity</u>                     | <u>Reportable quantity</u> |
|--|----------------------------|
| Asphalt                                      | 100 lbs.                   |
| Xylene                                       | 100 lbs.                   |
| Ethylbenzene                                 | 1000 lbs.                  |
| Toluene                                      | 1000 lbs.                  |
| Fluorathene                                  | 100 lbs.                   |
| Phenanthrene                                 | 5000 lbs.                  |
| Naphthalene                                  | 100 lbs.                   |
| 2-(2-(2-Butoxyethoxy)ethoxy)ethanol          |                            |
| Anthracene                                   | 5000 lbs.                  |
| Indeno[1,2,3-cd]pyrene                       | 100 lbs.                   |
| Benzo(a)anthracene                           | 10 lbs.                    |
| Chrysene                                     | 100 lbs.                   |
| Benzo(a)pyrene                               | 1 lbs.                     |
| Acenaphthene                                 | 100 lbs.                   |
| Dibenzofuran                                 | 100 lbs.                   |
| Benzo(b)fluoranthene/benzo[e]acefenantrileno | 1 lbs.                     |
| Biphenyl                                     | 100 lbs.                   |
| Dibenz(a,h)anthracene                        | 1 lbs.                     |
| Benzene                                      | 10 lbs.                    |

RECEIVED  
 18 MAR 13 AM 8:29

### SARA 311/312 Hazardous Chemical

| <u>Chemical Identity</u>                 | <u>Threshold Planning Quantity</u> |
|--|------------------------------------|
| Asphalt                                  | 10000 lbs                          |
| Xylene                                   | 10000 lbs                          |
| Amorphous silica                         | 10000 lbs                          |
| Coal tar pitch                           | 10000 lbs                          |
| Ethylbenzene                             | 10000 lbs                          |
| Petroleum distillates                    | 10000 lbs                          |
| Residues (petroleum),<br>thermal cracked | 10000 lbs                          |
| Polyethylene                             | 10000 lbs                          |
| Carbon Black                             | 10000 lbs                          |
| Toluene                                  | 10000 lbs                          |
| Fluorathene                              | 10000 lbs                          |

### SARA 313 (TRI Reporting)

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene                   |
| Ethylbenzene             |

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene                   | Reportable quantity: lbs.  |

### US State Regulations

#### US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

|  |                                  |
|--|----------------------------------|
| Asphalt                                      | Carcinogenic. 09 2011            |
| Petroleum distillates                        | Carcinogenic. 09 2011            |
| Carbon Black                                 | Carcinogenic. 09 2011            |
| Toluene                                      | Developmental toxin. 09 2011     |
| Naphthalene                                  | Carcinogenic. 09 2011            |
| Indeno[1,2,3-cd]pyrene                       | Carcinogenic. 09 2011            |
| Benzo(a)anthracene                           | Carcinogenic. 09 2011            |
| Chrysene                                     | Carcinogenic. 09 2011            |
| Benzo(a)pyrene                               | Carcinogenic. 09 2011            |
| Benzo(b)fluoranthene/benzo[e]acefenantrileno | Carcinogenic. 09 2011            |
| Dibenz(a,h)anthracene                        | Carcinogenic. 09 2011            |
| Benzene                                      | Carcinogenic. 09 2011            |
| Benzene                                      | Developmental toxin. 09 2011     |
| Benzene                                      | Male reproductive toxin. 09 2011 |

#### US. New Jersey Worker and Community Right-to-Know Act

| <u>Chemical Identity</u> |
|--------------------------|
| Asphalt                  |
| Xylene                   |
| Amorphous silica         |
| Coal tar pitch           |
| Ethylbenzene             |
| Carbon Black             |



## US. Massachusetts RTK - Substance List

### Chemical Identity

Asphalt  
Xylene  
Amorphous silica  
Coal tar pitch  
Ethylbenzene  
Indeno[1,2,3-cd]pyrene  
Benzo(a)anthracene  
Chrysene  
Benzo(a)pyrene  
Benzo(b)fluoranthene/benzo[e]acefenantrileno  
Dibenz(a,h)anthracene

## US. Pennsylvania RTK - Hazardous Substances

### Chemical Identity

Asphalt  
Xylene  
Amorphous silica  
Coal tar pitch  
Ethylbenzene

## US. Rhode Island RTK

### Chemical Identity

Asphalt  
Xylene  
Ethylbenzene

## International regulations

### Montreal protocol

not applicable

### Stockholm convention

not applicable

### Rotterdam convention

not applicable

### Kyoto protocol

not applicable

### VOC:

Regulatory VOC (less water and  
exempt solvent) : 253 g/l  
VOC Method 310 : 24.79 %

RECEIVED KODM  
18 MAR 13 AM 8:29

**Inventory Status:**

Australia AICS:

One or more components in this product are not listed on or exempt from the Inventory.

Canada DSL Inventory List:

One or more components in this product are not listed on or exempt from the Inventory.

EINECS, ELINCS or NLP:

One or more components in this product are not listed on or exempt from the Inventory.

Japan (ENCS) List:

One or more components in this product are not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI):

One or more components in this product are not listed on or exempt from the Inventory.

Canada NDSL Inventory:

One or more components in this product are not listed on or exempt from the Inventory.

Philippines PICCS:

One or more components in this product are not listed on or exempt from the Inventory.

US TSCA Inventory:

All components in this product are listed on or exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are not listed on or exempt from the Inventory.

Japan ISHL Listing:

One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are not listed on or exempt from the Inventory.

Mexico INSQ:

One or more components in this product are not listed on or exempt from the Inventory.

Ontario Inventory:

One or more components in this product are not listed on or exempt from the Inventory.

Taiwan Chemical Substance Inventory:

One or more components in this product are not listed on or exempt from the Inventory.

**16. Other information, including date of preparation or last revision**

**Revision Date:** 10/17/2017

**Version #:** 1.1

**Further Information:** No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

RECEIVED  
18 MAR 13 AM 8:29

