

# SAFETY DATA SHEET

## 1. Identification

**Material name:** ONESEAL CLEAN & PRIME 6/CASE  
**Material:** 6637837 213

**Recommended use and restriction on use**

**Recommended use:** Cleaning agent  
**Restrictions on use:** Not known.

**Manufacturer/Importer/Supplier/Distributor Information**

WATERPROOFING TECHNOLOGIES INC.  
3735 Green road  
Beachwood OH 44122  
US

**Contact person:** EH&S Department  
**Telephone:**  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

### Hazard Classification

#### Physical Hazards

Flammable aerosol Category 1

#### Health Hazards

Serious Eye Damage/Eye Irritation Category 2A  
Germ Cell Mutagenicity Category 1B  
Carcinogenicity Category 1A

#### Unknown toxicity - Health

Acute toxicity, oral 24.49 %  
Acute toxicity, dermal 25 %  
Acute toxicity, inhalation, vapor 89.5 %  
Acute toxicity, inhalation, dust or mist 100 %

### Environmental Hazards

Acute hazards to the aquatic environment Category 3

#### Unknown toxicity - Environment

Acute hazards to the aquatic environment 26.49 %  
Chronic hazards to the aquatic environment 100 %

### Label Elements

**Hazard Symbol:**



<b>Signal Word:</b>	Danger
<b>Hazard Statement:</b>	Extremely flammable aerosol. Causes serious eye irritation. May cause genetic defects. May cause cancer. Harmful to aquatic life. Pressurized container: May burst if heated.
<b>Precautionary Statement:</b>	
<b>Prevention:</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
<b>Response:</b>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.
<b>Storage:</b>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up.
<b>Disposal:</b>	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
<b>Other hazards which do not result in GHS classification:</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl acetate	79-20-9	40 - 70%
Liquefied petroleum gases	68476-86-8	15 - 40%
Methyl ethyl ketone	78-93-3	10 - 30%
Butyl acetate	123-86-4	10 - 30%
Aromatic petroleum distillates	64742-95-6	1 - 5%
Cumene	98-82-8	0.5 - 1.5%
Ethylbenzene	100-41-4	0.5 - 1.5%
1,2,4-Trimethylbenzene	95-63-6	0.5 - 1.5%

Methanol	67-56-1	0.5 - 1.5%
Chlorobenzene	108-90-7	0.5 - 1.5%
m-Xylene	108-38-3	0.5 - 1.5%
ortho-Xylene	95-47-6	0.5 - 1.5%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor/...if you feel unwell. Rinse mouth.
- Inhalation:** Move to fresh air.
- Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

### Most important symptoms/effects, acute and delayed

**Symptoms:** Respiratory tract irritation.

### Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

## 5. Fire-fighting measures

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** Vapors may travel considerable distance to a source of ignition and flash back.

### Special protective equipment and precautions for firefighters

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

**Methods and material for containment and cleaning up:** Stop the flow of material, if this is without risk. Absorb with sand or other inert absorbent.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

## 7. Handling and storage

**Precautions for safe handling:** Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities:** Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

## 8. Exposure controls/personal protection

### Control Parameters

#### Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Methyl acetate	TWA	200 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	250 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	200 ppm      610 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Methyl ethyl ketone	TWA	200 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	300 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	200 ppm      590 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Butyl acetate	TWA	150 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	200 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	150 ppm      710 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

1,2,4-Trimethylbenzene	TWA	25 ppm		US. ACGIH Threshold Limit Values (2011)
Methanol	TWA	200 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	250 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	200 ppm	260 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cumene	TWA	50 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Chlorobenzene	TWA	10 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	75 ppm	350 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
m-Xylene	TWA	100 ppm		US. ACGIH Threshold Limit Values (02 2012)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (02 2012)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
ortho-Xylene	STEL	150 ppm		US. ACGIH Threshold Limit Values (03 2014)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (03 2014)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Methyl acetate	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl acetate	TWAEV	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	250 ppm	Canada. Ontario OELs. (Control of

				Exposure to Biological or Chemical Agents) (11 2010)
Methyl acetate	TWA	200 ppm	606 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	250 ppm	757 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Methyl ethyl ketone	TWA	50 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl ethyl ketone	TWAEV	200 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	300 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl ethyl ketone	TWA	50 ppm	150 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	100 ppm	300 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Butyl acetate	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Butyl acetate	STEL	200 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Butyl acetate	STEL	200 ppm	950 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	TWA	150 ppm	713 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWAEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWAEV	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

### Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Methyl ethyl ketone (MEK: Sampling time: End of shift.)	2 mg/l (Urine)	ACGIH BEI (03 2013)
Methanol (methanol: Sampling time: End of shift.)	15 mg/l (Urine)	ACGIH BEI (03 2013)
Chlorobenzene (4-Chlorocatechol, with hydrolysis: Sampling time: End of shift at end of work week.)	100 mg/g (Creatinine in urine)	ACGIH BEI (03 2013)
Chlorobenzene (p-Chlorophenol, with hydrolysis: Sampling time: End of shift at end of work week.)	20 mg/g (Creatinine in urine)	ACGIH BEI (03 2013)
m-Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
ortho-Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

**Appropriate Engineering Controls**                      No data available.

### Individual protection measures, such as personal protective equipment

**General information:**                      Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Eye/face protection:**                      Wear safety glasses with side shields (or goggles).

**Skin Protection**

**Hand Protection:**                      No data available.

**Other:**                      Wear suitable protective clothing.



<b>Respiratory Protection:</b>	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
<b>Hygiene measures:</b>	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke.

**9. Physical and chemical properties****Appearance**

<b>Physical state:</b>	Aerosols
<b>Form:</b>	Aerosols
<b>Color:</b>	No data available.
<b>Odor:</b>	Strong petroleum/solvent
<b>Odor threshold:</b>	No data available.
<b>pH:</b>	No data available.
<b>Melting point/freezing point:</b>	No data available.
<b>Initial boiling point and boiling range:</b>	No data available.
<b>Flash Point:</b>	-56 °C -69 °F
<b>Evaporation rate:</b>	Slower than Ether
<b>Flammability (solid, gas):</b>	Yes
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	No data available.
<b>Flammability limit - lower (%):</b>	No data available.
<b>Explosive limit - upper (%):</b>	No data available.
<b>Explosive limit - lower (%):</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
<b>Relative density:</b>	0.787
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Practically Insoluble
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

**10. Stability and reactivity**

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions:</b>	No data available.

<b>Conditions to avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

**11. Toxicological information****Information on likely routes of exposure**

<b>Ingestion:</b>	May be ingested by accident. Ingestion may cause irritation and malaise.
<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	May be harmful in contact with skin. Causes mild skin irritation.
<b>Eye contact:</b>	Causes serious eye irritation.

**Information on toxicological effects****Acute toxicity (list all possible routes of exposure)**

<b>Oral Product:</b>	ATEmix: 15,509.75 mg/kg
<b>Dermal Product:</b>	ATEmix: 2,884.62 mg/kg
<b>Inhalation Product:</b>	No data available.

<b>Repeated dose toxicity Product:</b>	No data available.
--	--------------------

<b>Skin Corrosion/Irritation Product:</b>	No data available.
---	--------------------

<b>Specified substance(s):</b>	
Methyl acetate	in vivo (Rabbit): Experimental result, Key study
Methyl ethyl ketone	in vivo (Rabbit): Read-across from supporting substance (structural analogue or surrogate), Key study
Butyl acetate	in vivo (Rabbit): Experimental result, Key study

---

Aromatic petroleum distillates	in vivo (Rabbit): Experimental result, Key study
Cumene	in vivo (Rabbit): Experimental result, Key study
1,2,4-Trimethylbenzene	in vivo (Rabbit): Read-across from supporting substance (structural analogue or surrogate), Key study
Methanol	in vivo (Rabbit): Experimental result, Key study
m-Xylene	in vivo (Rabbit): Experimental result, Weight of Evidence study
ortho-Xylene	in vivo (Rabbit): Experimental result, Supporting study

**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Methyl acetate	Irritating in vivo (Rabbit): Irritating
Methyl ethyl ketone	Irritating in vivo (Rabbit, 24 hrs): Category 2
Butyl acetate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Aromatic petroleum distillates	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Cumene	in vivo (Rabbit, 24 hrs): Not irritating
Ethylbenzene	in vivo (Rabbit, 7 d): Slightly irritating
1,2,4-Trimethylbenzene	in vivo (Rabbit, 30 min): Not irritating
Methanol	in vivo (Rabbit, 24 hrs): Not irritating
Chlorobenzene	in vivo (Rabbit, 24 - 72 hrs): Not irritating
m-Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating
ortho-Xylene	in vivo (Rabbit, 24 hrs): Moderately irritating

**Respiratory or Skin Sensitization****Product:** No data available.**Carcinogenicity****Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Cumene	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

Cumene	Reasonably Anticipated to be a Human Carcinogen.
--------	--

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity**

<b>In vitro</b>	
Product:	No data available.

<b>In vivo</b>	
Product:	No data available.

<b>Reproductive toxicity</b>	
Product:	No data available.

<b>Specific Target Organ Toxicity - Single Exposure</b>	
Product:	No data available.

<b>Specific Target Organ Toxicity - Repeated Exposure</b>	
Product:	No data available.

<b>Aspiration Hazard</b>	
Product:	No data available.

<b>Other effects:</b>	No data available.
-----------------------	--------------------

**12. Ecological information****Ecotoxicity:****Acute hazards to the aquatic environment:**

<b>Fish</b>	
Product:	No data available.

<b>Specified substance(s):</b>	
Methyl acetate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 295 - 348 mg/l Mortality

Methyl ethyl ketone	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 3,130 - 3,320 mg/l Mortality
Butyl acetate	LC 50 (Zebra danio (Danio rerio), 96 h): 62 mg/l Mortality
Cumene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 6.04 - 6.61 mg/l Mortality
Ethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 9.1 - 15.6 mg/l Mortality
1,2,4-Trimethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality
Methanol	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 28,200 mg/l Mortality
Chlorobenzene	LC 50 (Bluegill (Lepomis macrochirus), 8 h): 6 mg/l Mortality LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 16 d): < 0.09 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 16 h): 6 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 24 h): 17 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 24 h): 18.88 - 30.51 mg/l Mortality
m-Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 14.31 - 18.01 mg/l Mortality
ortho-Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 11.6 - 22.4 mg/l Mortality

**Aquatic Invertebrates  
Product:**

No data available.

**Specified substance(s):  
Methyl ethyl ketone**

Methyl ethyl ketone	LC 50 (Water flea (Daphnia magna), 24 h): 8,890 mg/l Mortality LC 50 (Water flea (Daphnia magna), 48 h): > 520 mg/l Mortality LC 50 (Opossum shrimp (Americamysis bahia), 96 h): > 402 mg/l Mortality LC 50 (Water flea (Daphnia magna), 24 h): > 520 mg/l Mortality
Butyl acetate	LC 50 (Water flea (Daphnia magna), 24 h): 205 mg/l Mortality
Cumene	LC 50 (Water flea (Daphnia magna), 24 h): 95 mg/l Mortality
Ethylbenzene	LC 50 (Water flea (Daphnia magna), 24 h): 190 mg/l Mortality
1,2,4-Trimethylbenzene	LC 50 (Scud (Elasmopus pectinicus), 24 h): 4.89 - 5.62 mg/l Mortality
Methanol	LC 50 (Water flea (Daphnia magna), 24 h): 3,616 - 6,414 mg/l Mortality EC 50 (Water flea (Daphnia magna), 48 h): > 10,000 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): > 10,000 mg/l Intoxication LC 50 (Water flea (Daphnia magna), 96 h): > 100 mg/l Mortality LC 50 (Oligochaete, worm (Lumbriculus variegatus), 96 h): > 100 mg/l Mortality
Chlorobenzene	LC 50 (Water flea (Daphnia magna), 24 h): 310 mg/l Mortality
m-Xylene	EC 50 (Water flea (Daphnia magna), 24 h): 4.7 mg/l Intoxication

ortho-Xylene LC 50 (Water flea (Daphnia magna), 48 h): 11.2 - 20.3 mg/l Mortality  
EC 50 (Water flea (Daphnia magna), 48 h): < 1.39 mg/l Intoxication  
LC 50 (Snail (Aplexa hypnorum), 96 h): > 22.4 mg/l Mortality

**Chronic hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Aromatic petroleum distillates EC 50 (Daphnia magna, 21 d): 10 mg/l Other, Key study

Cumene NOAEL (Danio rerio; Pimephales promelas, 28 d): 0.38 mg/l QSAR QSAR, Key study

Methanol NOAEL (Oryzias latipes, 200 h): 15,800 mg/l Experimental result, Supporting study  
NOAEL (Oryzias latipes, 200 h): 158,000 mg/l Experimental result, Supporting study  
EC 50 (Oryzias latipes, 200 h): 9,164 mg/l Experimental result, Supporting study  
EC 50 (Oryzias latipes, 200 h): 10,270 mg/l Experimental result, Supporting study  
LOAEL (Oryzias latipes, 200 h): 7,900 mg/l Experimental result, Supporting study

Chlorobenzene LC 50 (Various, 4 d): 0.11 mg/l Experimental result, Not specified  
LC 50 (Various, 4 d): 0.88 mg/l Experimental result, Not specified  
LOAEL (21 d): 0.63 mg/l Experimental result, Key study  
LC 50 (Poecilia reticulata, 14 d): 19.1 mg/l Experimental result, Supporting study  
LC 50 (Various, 4 d): 0.05 mg/l Experimental result, Not specified

m-Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l Read-across based on grouping of substances (category approach), Key study

ortho-Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l Read-across based on grouping of substances (category approach), Key study

**Aquatic Invertebrates**

**Product:** No data available.

**Toxicity to Aquatic Plants**

**Product:** No data available.

**Persistence and Degradability**

**Biodegradation**

**Product:** No data available.

**BOD/COD Ratio**

**Product:** No data available.

## Bioaccumulative Potential Bioconcentration Factor (BCF)

**Product:** No data available.

### Specified substance(s):

Methanol Green algae (*Chlorella fusca vacuolata*), Bioconcentration Factor (BCF): 28,400 (Static)

Chlorobenzene Green algae (*Selenastrum capricornutum*), Bioconcentration Factor (BCF): 2,172 (Static)  
Western mosquitofish (*Gambusia affinis*), Bioconcentration Factor (BCF): 645 (Static)  
Water flea (*Daphnia magna*), Bioconcentration Factor (BCF): 2,789 (Static)  
Southern house mosquito (*Culex quinquefasciatus*), Bioconcentration Factor (BCF): 1,292 (Static)  
Ide, silver or golden orfe (*Leuciscus idus*), Bioconcentration Factor (BCF): 75 (Not reported)

## Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

### Specified substance(s):

Methyl acetate Log Kow: 0.18

Methyl ethyl ketone Log Kow: 0.29

Butyl acetate Log Kow: 1.78

Cumene Log Kow: 3.66

Ethylbenzene Log Kow: 3.15

Methanol Log Kow: -0.77

Chlorobenzene Log Kow: 2.89

m-Xylene Log Kow: 3.20

ortho-Xylene Log Kow: 3.12

**Mobility in Soil:** No data available.

**Other Adverse Effects:** Harmful to aquatic organisms.

## 13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

## 14. Transport information

**TDG:**

UN1950, AEROSOLS, 2.1

**CFR / DOT:**

UN1950, Aerosols, 2.1

**IMDG:**

UN1950, AEROSOLS, 2.1

**Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

## 15. Regulatory information

### US Federal Regulations

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

None present or none present in regulated quantities.

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Methyl acetate	100 lbs.
Methyl ethyl ketone	5000 lbs.
Butyl acetate	5000 lbs.
Methanol	5000 lbs.
Cumene	5000 lbs.
Chlorobenzene	100 lbs.
m-Xylene	1000 lbs.
ortho-Xylene	1000 lbs.
Ethylbenzene	1000 lbs.
p-Xylene	100 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

Fire Hazard  
Immediate (Acute) Health Hazards  
Delayed (Chronic) Health Hazard

**SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.



**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Methyl acetate	100 lbs.
Methyl ethyl ketone	5000 lbs.
Butyl acetate	5000 lbs.
Methanol	5000 lbs.
Cumene	5000 lbs.
Chlorobenzene	100 lbs.
m-Xylene	1000 lbs.
ortho-Xylene	1000 lbs.
Ethylbenzene	1000 lbs.
p-Xylene	100 lbs.

**SARA 311/312 Hazardous Chemical**

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Methyl acetate	500 lbs
Liquefied petroleum gases	500 lbs
Methyl ethyl ketone	500 lbs
Butyl acetate	500 lbs
Aromatic petroleum distillates	500 lbs
Cumene	500 lbs
Ethylbenzene	500 lbs
1,2,4-Trimethylbenzene	500 lbs
Methanol	500 lbs
Chlorobenzene	500 lbs
m-Xylene	500 lbs
ortho-Xylene	500 lbs

**SARA 313 (TRI Reporting)**

<u>Chemical Identity</u>
Ethylbenzene

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

None present or none present in regulated quantities.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

None present or none present in regulated quantities.

**US State Regulations****US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

**US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity

Methyl acetate  
Methyl ethyl ketone  
Butyl acetate  
Ethylbenzene

## US. Massachusetts RTK - Substance List

### Chemical Identity

Methyl acetate  
Methyl ethyl ketone  
Butyl acetate

## US. Pennsylvania RTK - Hazardous Substances

### Chemical Identity

Methyl acetate  
Methyl ethyl ketone  
Butyl acetate

## US. Rhode Island RTK

### Chemical Identity

Methyl ethyl ketone  
Butyl acetate

## Other Regulations:

<b>Regulatory VOC (less water and exempt solvent):</b>	642 g/l
<b>VOC Method 310:</b>	46.50 %

## Inventory Status:

Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.

New Zealand Inventory of Chemicals:

All components in this product are listed on or exempt from the Inventory.

Japan ISHL Listing:

One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are not listed on or exempt from the Inventory.

## 16. Other information, including date of preparation or last revision

**Revision Date:** 06/27/2016

**Version #:** 1.0

**Further Information:** No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

