



**ALPHAGUARD C-PRIME 1:1 PART B 5GL PL ALPHAGUARD C-PRIME 1:1 PART B 5GL PL**

Version 2.0

Print Date 07/24/2013

REVISION DATE: 07/08/2012

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : ALPHAGUARD C-PRIME 1:1 PART B 5GL PL ALPHAGUARD C-PRIME 1:1 PART B 5GL PL  
 Product code : 351695B805  
 COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122  
 Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300  
 Product use : Curative

RECEIVED RODS  
13 JUL 29 AM 11:02

**SECTION 2 - HAZARDS IDENTIFICATION**

Emergency Overview

Amber. Liquid. May cause slight irritation to the respiratory system. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.  
 Eyes : Vapors or liquid may cause tearing, blurred vision, severe irritation, and possible chemical burns.  
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting; May cause chemical burns to stomach, mouth, nose, and throat.  
 Skin : May cause itching, reddening, inflammation. May cause severe burns, blistering and skin damage. May cause sensitization resulting in irritation, itching and redness. May cause a rash.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

May cause sensitization by contact. Prolonged skin contact may cause irritation, burns or dermatitis. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. May aggravate persons sensitized to amines. Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. Repeated inhalation of nonyl phenol may cause lung damage. Repeated skin contact with nonyl phenol may cause skin irritation and dermatitis. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
4-Nonylphenol	84852-15-3	30.0 - 60.0



## ALPHAGUARD C-PRIME 1:1 PART B 5GL PL ALPHAGUARD C-PRIME 1:1 PART B 5GL PL

Version 2.0

Print Date 07/24/2013

REVISION DATE: 07/08/2012

Polyamide	NJ TSRN# 51721300-5644P	15.0 - 40.0
Benzyl alcohol	100-51-6	15.0 - 40.0
Mixed Cycloaliphatic amines	NJ TSRN# 51721300-5917P	10.0 - 30.0
Heavy aromatic naphtha	64742-94-5	7.0 - 13.0
Tertiary Amine	NJ TSRN# 51721300-5918P	3.0 - 7.0
Triethylenetetramine	112-24-3	1.0 - 5.0

### SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

### SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	> 200 °F, > 93 °C
Method	:	Setaflash Closed Cup
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Carbon monoxide and carbon dioxide can form. Smoke, fumes. Nitrogen oxides can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Vapor concentrations in enclosed areas may ignite explosively. Empty containers may contain ignitable vapors.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

### SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame



**ALPHAGUARD C-PRIME 1:1 PART B 5GL PL ALPHAGUARD C-PRIME 1:1 PART B 5GL PL**

Version 2.0

Print Date 07/24/2013

REVISION DATE: 07/08/2012

near container. Do not use in confined or poorly ventilated areas. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store under dry warehouse conditions away from heat and all ignition sources.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Wear NIOSH/MSHA approved vapor respirator with appropriate cartridge when the vapor concentration is expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Inspect and replace equipment at regular intervals. Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

No known components with exposure limits.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Liquid
- Color : Amber
- Odor : Amine
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Negligible
- Specific Gravity : 1.2
- % Volatile Weight : 56 %

**SECTION 10 - REACTIVITY / STABILITY**

- Substances to avoid : Oxidizing agents. Epoxies. Isocyanates. Acids.



**ALPHAGUARD C-PRIME 1:1 PART B 5GL PL**  
**ALPHAGUARD C-PRIME 1:1 PART B 5GL PL**

Version 2.0

Print Date 07/24/2013

REVISION DATE: 07/08/2012

Stability : Material is stable under normal storage, handling, and use.  
 Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Benzyl alcohol, CAS-No.: 100-51-6  
 Acute oral toxicity (LD-50 oral) 1,580 mg/kg ( Mouse ) 1,940 mg/kg ( Rabbit ) 3,100 mg/kg ( Rat ) 1,230 - 3,100 mg/kg ( Rat )  
 Acute inhalation toxicity (LC-50) 200 - 300 mg/l for 8 h ( Rat ) 1,000 mg/l for 8 h ( Rat )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**CFR / DOT:**

UN1760, Corrosive liquids, n.o.s. (Alkaline Amine), 8, PG III

**TDG:**

UN1760, CORROSIVE LIQUID, N.O.S. (Alkaline Amine), 8, PG III

**IMDG:**

UN1760, CORROSIVE LIQUID, N.O.S. (Alkaline Amine, Nonylphenol), 8, PG III, MARINE POLLUTANT

**Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

**SECTION 15 - REGULATORY INFORMATION**

**North American inventories:**

All components are listed or exempt from the TSCA inventory.  
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.



**ALPHAGUARD C-PRIME 1:1 PART B 5GL PLALPHAGUARD C-PRIME 1:1 PART B 5GL PL**

Version: 2.0

Print Date 07/24/2013

REVISION DATE: 07/08/2012

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :

OSHA Status: Considered : Irritant  
hazardous based on the : Corrosive  
following criteria:

OSHA Flammability : Not Regulated

When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:  
97 g/l

Regulatory VOC (less water and : 687 g/l  
exempt solvent)

VOC Method 310 : 56 %

**U.S. State Regulations:**

MASS RTK Components : Benzyl alcohol 100-51-6  
Triethylenetetramine 112-24-3

Penn RTK Components : 4-Nonylphenol 84852-15-3  
Polyamide NJ TSRN# 51721300-5644P  
Benzyl alcohol 100-51-6  
Mixed Cycloaliphatic amines NJ TSRN# 51721300-5917P  
Heavy aromatic naphtha 64742-94-5  
Tertiary Amine NJ TSRN# 51721300-5918P  
Triethylenetetramine 112-24-3

NJ RTK Components : 4-Nonylphenol 84852-15-3  
Polyamide NJ TSRN# 51721300-5644P  
Benzyl alcohol 100-51-6  
Mixed Cycloaliphatic amines NJ TSRN# 51721300-5917P  
Heavy aromatic naphtha 64742-94-5  
Triethylenetetramine 112-24-3

Components under California Proposition 65:  
None known.

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	1
Reactivity	0
PPE	

0 = Minimum  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe



**ALPHAGUARD C-PRIME 1:1 PART B 5GL PL ALPHAGUARD C-PRIME 1:1 PART B 5GL PL**

Version 2.0

Print Date 07/24/2013

REVISION DATE: 07/08/2012

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

**Legend**

ACGIH - American Conference of Governmental Hygienists  
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
DOT - Department of Transportation  
DSL - Domestic Substance List  
EPA - Environmental Protection Agency  
HMIS - Hazardous Materials Information System  
IARC - international Agency for Research on Cancer  
MSHA - Mine Safety Health Administration  
NDSL - Non-Domestic Substance List  
NIOSH - National Institute for Occupational Safety and Health  
NTP - National Toxicology Program  
OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
RCRA - Resource Conservation and Recovery Act  
RTK - Right To Know  
SARA - Superfund Amendments and Reauthorization Act  
STEL - Short Term Exposure Limit  
TLV - Threshold Limit Value  
TSCA - Toxic Substances Control Act  
TWA - Time Weighted Average  
V - Volume  
VOC - Volatile Organic Compound  
WHMIS - Workplace Hazardous Materials Information System