

**TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL**

Version 4.0

Print Date 05/09/2014

REVISION DATE: 08/06/2013

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL

Product code : 505410 805

COMPANY : Tremco Incorporated  
3735 Green Road  
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST

Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
After Hours: Chemtrec 1-800-424-9300

Product use : Adhesive

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Amber. Liquid. May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue.

Eyes : Vapor and/or mist may cause eye irritation. Direct contact may cause temporary redness and discomfort.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause moderate irritation.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Prolonged inhalation or ingestion of large amounts of 1-chloro-4-(trifluoromethyl)-benzene may cause liver and kidney damage based on laboratory animal studies. Prolonged or repeated overexposure to acetone may cause liver damage, Central Nervous System depression and narcosis. Prolonged or repeated exposure may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney, and testes damage. Toluene overexposure may cause burns of the skin, respiratory tract damage. May be harmful to the human fetus based on animal tests and limited epidemiology data. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung, Liver, Kidney, Nerve, Reproductive

**TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL**

Version 4.0

Print Date 05/09/2014

REVISION DATE: 08/06/2013

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Acetone	67-64-1	> 60.0
Synthetic Rubber	NJ TSRN# 51721300-5675P	10.0 - 30.0
Hydrocarbon Resin	NJ TSRN# 51721300-5677P	10.0 - 30.0
Methyl ethyl ketone	78-93-3	3.0 - 7.0
Toluene	108-88-3	1.0 - 5.0

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : < 0 °F, < -18 °C
- Method : Not available.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form. Nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water may be used to cool containers to minimize pressure build-up.
- Fire and explosion conditions : Extremely flammable vapors. Vapor concentrations in enclosed areas may ignite explosively. Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors.



**TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL**

Version 4.0

Print Date 05/09/2014

REVISION DATE: 08/06/2013

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container. Store in sealed containers in a cool, dry, ventilated warehouse location.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use. Inspect and replace equipment at regular intervals.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Acetone	67-64-1	ACGIH TWA: ACGIH STEL: OSHA PEL:	500 ppm 750 ppm 2,400 mg/m3	
Methyl ethyl ketone	78-93-3	ACGIH TWA: ACGIH STEL: OSHA PEL:	200 ppm 300 ppm 590 mg/m3	
Toluene	108-88-3	ACGIH TWA: OSHA TWA:	20 ppm 200 ppm	

**TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL**

Version 4.0

Print Date 05/09/2014

REVISION DATE: 08/06/2013

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form	: Liquid
Color	: Amber
Odor	: Aromatic Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: 56 °C, 133 °F
Water solubility	: Negligible
Specific Gravity	: 0.85
% Volatile Weight	: 74 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid	: Oxidizing agents.Strong acids.Strong bases.
Stability	: Stable under normal conditions. Avoid welding arcs, flames or other high temperature sources.
Hazardous polymerization	: Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Acetone, CAS-No.: 67-64-1	
Acute oral toxicity (LD-50 oral)	9,800 mg/kg ( Rat ) 3,000 mg/kg ( Mouse ) 5,340 mg/kg ( Rabbit ) 5.2 g/kg ( Mouse ) 5,800 mg/kg ( Rat )
Acute inhalation toxicity (LC-50)	50.1 mg/l for 8 h ( Rat ) 76 mg/l for 4 h ( Rat )
Acute dermal toxicity (LD-50 dermal)	20,000 mg/kg ( Rabbit ) 20 mg/kg ( Rabbit )
Methyl ethyl ketone, CAS-No.: 78-93-3	
Acute oral toxicity (LD-50 oral)	670 mg/kg ( Mouse ) 2,300 - 3,500 mg/kg ( Rat ) 4,500 - 6,800 mg/kg ( Rat )
Acute inhalation toxicity (LC-50)	11,000 mg/l for 45 min ( Mouse ) 11,700 mg/l for 4 h ( Rat )
Acute dermal toxicity (LD-50 dermal)	8,000 mg/kg ( Rabbit )
Toluene, CAS-No.: 108-88-3	
Acute oral toxicity (LD-50 oral)	2,600 - 7,500 mg/kg ( Rat ) 5,000 mg/kg ( Rat )
Acute inhalation toxicity (LC-50)	26,700 mg/l for 1 h ( Rat ) 400 mg/l for 24 h ( Mouse ) 5,320 mg/l for 8 h ( Mouse )
Acute dermal toxicity (LD-50 dermal)	12,124 mg/kg ( Rabbit )



**TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL**

Version 4.0

Print Date 05/09/2014

REVISION DATE: 08/06/2013

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

RCRA Class : D001: Reportable Quantity = 100 lbs. (Characteristic of ignitability)

This classification applies only to the material as it was originally produced.

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**CFR / DOT:**

UN1133, Adhesives, 3, PG II

**TDG:**

UN1133, ADHESIVES, 3, PG II

**IMDG:**

UN1133, ADHESIVES, 3, PG II

**Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : Toluene 108-88-3

SARA 311/312 Hazards : Acute Health Hazard  
Fire Hazard

**OSHA Hazardous Components :**

Acetone 67-64-1  
Methyl ethyl ketone 78-93-3  
Toluene 108-88-3



**TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL**

Version 4.0

Print Date 05/09/2014

REVISION DATE: 08/06/2013

OSHA Status: Considered : Irritant  
hazardous based on the following criteria:

OSHA Flammability : IB

Regulatory VOC (less water and exempt solvent) : 199 g/l

VOC Method 310 : 5 %

**U.S. State Regulations:**

MASS RTK Components : Acetone 67-64-1  
Methyl ethyl ketone 78-93-3  
Toluene 108-88-3

Penn RTK Components : Acetone 67-64-1  
Synthetic Rubber NJ TSRN# 51721300-5675P  
Hydrocarbon Resin NJ TSRN# 51721300-5677P  
Methyl ethyl ketone 78-93-3  
Toluene 108-88-3

NJ RTK Components : Acetone 67-64-1  
Synthetic Rubber NJ TSRN# 51721300-5675P  
Hydrocarbon Resin NJ TSRN# 51721300-5677P  
Methyl ethyl ketone 78-93-3  
Toluene 108-88-3  
P-chlorobenzotrifluoride 98-56-6

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	3
Reactivity	1
PPE	

0 = Minimum  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
CERCLA - Comprehensive Environmental Response, Compensation, and

PEL - Permissible Exposure Limit  
RCRA - Resource Conservation and Recovery Act



**TPA LV SINGLE PLY BONDING ADHESIVE 5 GAL TPA LV SINGLE PLY  
BONDING ADHESIVE 5 GAL**

Version 4.0

Print Date 05/09/2014

REVISION DATE: 08/06/2013

Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System