



**POLYROOF LV 5 GL. POLYROOF LV 5 GL.**

Version 3.0

Print Date 08/03/2012

REVISION DATE: 07/08/2012

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : POLYROOF LV 5 GL. POLYROOF LV 5 GL.  
 Product code : 361590 805

COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300

RECEIVED KCD A  
 12 AUG 13 PM 2:26

**SECTION 2 - HAZARDS IDENTIFICATION**

Emergency Overview

Black. Paste. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause slight irritation to the respiratory system.  
 Eyes : Direct contact may cause moderate irritation. Direct contact may cause temporary redness and discomfort.  
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.  
 Skin : May cause moderate irritation. May cause itching, reddening, inflammation. May cause a rash. May cause sensitization.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Prolonged or repeated skin contact with asphalt may result in skin sensitivity, such as irritation, rashes, and dermatitis. Prolonged or repeated exposure to polycyclic aromatic hydrocarbons and other volatiles which are contained in trace amounts in asphalt have been shown to cause cancer or respiratory damage in animals. Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. This product contains naphthalene. A National Toxicology Program (NTP) draft report states that lifetime inhalation exposure to naphthalene resulted in increases in tumors of the nose in rats. In a previous NTP study, lifetime inhalation exposure to naphthalene increased lung tumors in female mice. The relevance of the rodent findings to humans is questionable. Prolonged or repeated skin contact with thermally cracked petroleum distillates in these products may result in irritation and dermatitis. Although a direct association between thermally cracked petroleum distillates and cancer or other lung disease has not been established in man, thermally cracked petroleum distillates may contain variable amounts of polynuclear aromatic hydrocarbons (PNA's) and other volatiles which have been shown to cause cancer and respiratory damage in



**POLYROOF LV 5 GL. POLYROOF LV 5 GL.**

Version 3.0

Print Date 08/03/2012

REVISION DATE: 07/08/2012

animals. May produce a phototoxic reaction when contaminated skin is exposed to sunlight. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung, Liver, Kidney, Nerve

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Asphalt	8052-42-4	30.0 - 60.0
Xylene	1330-20-7	15.0 - 40.0
Styrene-butadiene copolymers	NJ TSRN# 51721300-5132P	15.0 - 40.0
Amorphous silica	7631-86-9	5.0 - 10.0
Ethylbenzene	100-41-4	5.0 - 10.0
Petroleum distillates	64741-81-7	5.0 - 10.0
Coal tar	8007-45-2	3.0 - 7.0
Carbon Black	1333-86-4	- <1.0
Naphthalene	91-20-3	- <1.0
Benzo(a)anthracene	56-55-3	- <0.1
Benzo(a)pyrene	50-32-8	- <0.1

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not available.
- Burning rate : Non-flammable solid
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form. Oxides of sulfur can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).



**POLYROOF LV 5 GL. POLYROOF LV 5 GL.**

Version 3.0

Print Date 08/03/2012

REVISION DATE: 07/08/2012

Fire and explosion conditions : Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Vapor concentrations in enclosed areas may ignite explosively. Empty containers may contain ignitable vapors.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame near container. Do not use in confined or poorly ventilated areas. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store under dry warehouse conditions away from heat and all ignition sources.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use. Inspect and replace equipment at regular intervals.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Asphalt	8052-42-4	ACGIH TWA: benzene solubles	0.5 mg/m3	Inhalable fraction.as
Xylene	1330-20-7	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 150 ppm 435 mg/m3	



**POLYROOF LV 5 GL. POLYROOF LV 5 GL.**

Version 3.0

Print Date 08/03/2012

REVISION DATE: 07/08/2012

Chemical Name	CAS Number	Reguiation	Limit	Form
Amorphous silica	7631-86-9	ACGIH TWA: ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA:	3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3 0.8 mg/m3	Respirable particles. Inhalable particles. Total dust. Respirable fraction.
Ethylbenzene	100-41-4	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 125 ppm 435 mg/m3	
Carbon Black	1333-86-4	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	3.5 mg/m3 3.5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.
Napthalene	91-20-3	ACGIH TWA: ACGIH STEL: OSHA PEL:	10 ppm 15 ppm 50 mg/m3	

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form : Paste  
 Color : Black  
 Odor : Aromatic  
 pH : Not available.  
 Vapour pressure : Not available.  
 Vapor density : Heavier than air  
 Melting point/range : Not available.  
 Freezing point : Not available.  
 Boiling point/range : 371 °C, 700 °F  
 Water solubility : Negligible  
 Specific Gravity : 0.98  
 % Volatile Weight : 30 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Oxidizing agents.  
 Stability : Material is stable under normal storage, handling, and use.  
 Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Xylene, CAS-No.: 1330-20-7



**POLYROOF LV 5 GL. POLYROOF LV 5 GL.**

Version 3.0

Print Date 08/03/2012

REVISION DATE: 07/08/2012

Acute oral toxicity (LD-50 oral)	4,300 mg/kg ( Rat ) 1,590 mg/kg ( Mouse ) 6,670 mg/kg ( Rat ) 3,523 - 8,600 mg/kg ( Rat ) 5,627 mg/kg ( Mouse )
Acute inhalation toxicity (LC-50)	6,350 mg/l for 4 h ( Rat ) 3,907 mg/l for 6 h ( Mouse ) 8,000 mg/l for 4 h ( Rat )
Amorphous silica, CAS-No.: 7631-86-9	
Acute oral toxicity (LD-50 oral)	22,500 mg/kg ( Rat ) 15,000 mg/kg ( Mouse )
Ethylbenzene, CAS-No.: 100-41-4	
Acute oral toxicity (LD-50 oral)	5,460 mg/kg ( Rat ) 3,500 mg/kg ( Rat )
Acute dermal toxicity (LD-50 dermal)	17,800 mg/kg ( Rabbit )
Naphthalene, CAS-No.: 91-20-3	
Acute oral toxicity (LD-50 oral)	2,600 mg/kg ( Sprague-Dawley rat ) 2,200 mg/kg ( Sherman rat ) 2,400 mg/kg ( Sherman rat ) 1,200 mg/kg ( Guinea pig ) 490 mg/kg ( Rat )
Acute dermal toxicity (LD-50 dermal)	2,000 mg/kg ( New Zealand white rabbit ) 20,000 mg/kg ( Rat )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**CFR / DOT:**

Not Regulated

**TDG:**

Not Regulated

**IMDG:**

Not Regulated

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.



**POLYROOF LV 5 GL. POLYROOF LV 5 GL.**

Version 3.0

Print Date 08/03/2012

REVISION DATE: 07/08/2012

All components are listed or exempt from the TSCA inventory.

**U.S. Federal Regulations:**

SARA 313 Components : Xylene 1330-20-7  
 Ethylbenzene 100-41-4  
 Naphthalene 91-20-3

SARA 311/312 Hazards : Acute Health Hazard  
 Chronic Health Hazard

**OSHA Hazardous Components :**

Asphalt 8052-42-4  
 Xylene 1330-20-7  
 Amorphous silica 7631-86-9  
 Ethylbenzene 100-41-4  
 Coal tar 8007-45-2  
 Carbon Black 1333-86-4  
 Naphthalene 91-20-3  
 Benzo(a)anthracene 56-55-3

OSHA Status: Considered : Irritant  
 hazardous based on the Carcinogen  
 following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 300 g/l  
 exempt solvent)

VOC Method 310 : 30 %

**Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:**

Coal tar 8007-45-2  
 Carbon Black 1333-86-4  
 Naphthalene 91-20-3

**U.S. State Regulations:**

MASS RTK Components : Asphalt 8052-42-4  
 Xylene 1330-20-7  
 Amorphous silica 7631-86-9  
 Ethylbenzene 100-41-4  
 Coal tar 8007-45-2  
 Benzo(a)anthracene 56-55-3  
 Benzo(a)pyrene 50-32-8

Penn RTK Components : Asphalt 8052-42-4  
 Xylene 1330-20-7  
 Styrene-butadiene copolymers NJ TSRN# 51721300-5132P  
 Amorphous silica 7631-86-9  
 Ethylbenzene 100-41-4  
 Petroleum distillates 64741-81-7  
 Coal tar 8007-45-2

NJ RTK Components : Asphalt 8052-42-4  
 Xylene 1330-20-7



**POLYROOF LV 5 GL. POLYROOF LV 5 GL.**

Version 3.0

Print Date 08/03/2012

REVISION DATE: 07/08/2012

Styrene-butadiene copolymers  
 Amorphous silica  
 Ethylbenzene  
 Coal tar  
 Carbon Black  
 Naphthalene

NJ TSRN# 51721300-5132P  
 7631-86-9  
 100-41-4  
 8007-45-2  
 1333-86-4  
 91-20-3

Components under California Proposition 65:

**WARNING!** Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	2
Reactivity	0
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT - Department of Transportation  
 DSL - Domestic Substance List  
 EPA - Environmental Protection Agency  
 HMIS - Hazardous Materials Information System  
 IARC - International Agency for Research on Cancer  
 MSHA - Mine Safety Health Administration  
 NDSL - Non-Domestic Substance List  
 NIOSH - National Institute for Occupational Safety and Health  
 NTP - National Toxicology Program  
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
 RCRA - Resource Conservation and Recovery Act  
 RTK - Right To Know  
 SARA - Superfund Amendments and Reauthorization Act  
 STEL - Short Term Exposure Limit  
 TLV - Threshold Limit Value  
 TSCA - Toxic Substances Control Act  
 TWA - Time Weighted Average  
 V - Volume  
 VOC - Volatile Organic Compound  
 WHMIS - Workplace Hazardous Materials Information System