

POLYROOF SF 3 GL

Version 1.2

Print Date 08/11/2007

REVISION DATE: 09/01/2006

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : POLYROOF SF 3 GL.
 Product code : 361592 803

COMPANY : Tremco Incorporated
 3735 Green Road
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
 After Hours: Chemtrec 1-800-424-9300

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Black. Liquid. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause slight irritation to the respiratory system.

Eyes : Direct contact may cause moderate irritation. Direct contact may cause temporary redness and discomfort.

Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause moderate irritation. May cause itching, reddening, inflammation. May cause a rash. May cause sensitization.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Prolonged or repeated skin contact with asphalt may result in skin sensitivity, such as irritation, rashes, and dermatitis. Prolonged or repeated exposure to polycyclic aromatic hydrocarbons and other volatiles which are contained in trace amounts in asphalt have been shown to cause cancer or respiratory damage in animals. Prolonged or repeated exposure to butyl benzyl phthalate may cause reduced body weights and adverse effects on the liver, kidney, spleen, pancreas, and reproductive organs. Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. Overexposure to maleic anhydride can cause allergic asthmatic responses and, after long-term exposure, bronchitis. Diphenylmethane diisocyanate (methylene bisphenyl isocyanate) caused an increased incidence of lung tumors in experimental animals following long term inhalation at concentrations in excess of 100 times the exposure limit. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Lung, Liver, Kidney, Nerve

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Asphalt	64741-56-6	30.0 - 60.0

POLYROOF SF 3 GL

Version 1.2

Print Date 08/11/2007

REVISION DATE: 09/01/2006

Polyurethane polymer	NJ TSN# 51721300-5119P	15.0 - 40.0
Butyl benzyl phthalate	85-68-7	15.0 - 40.0
Carbon Black	1333-86-4	5.0 - 10.0
4,4'-Methylene bis(phenylisocyanate)	101-68-8	1.0 - 5.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : 162 °C, 324 °F
- Method : Setafash Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form. Oxides of sulfur can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Vapor concentrations in enclosed areas may ignite explosively. Empty containers may contain ignitable vapors.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame near container. Do not use in confined or poorly ventilated areas. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store under dry warehouse conditions away from heat and all ignition sources.

POLYROOF SF 3 GL

Version 1.2
 REVISION DATE: 09/01/2006

Print Date 08/11/2007

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use. Inspect and replace equipment at regular intervals.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Carbon Black	1333-86-4	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	3.5 mg/m3 3.5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.
4,4'-Methylene bis(phenylisocyanate)	101-68-8	ACGIH TWA:	0.005 ppm	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid
- Color : Black
- Odor : Ester
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Negligible
- Specific Gravity : 1.072
- % Volatile Weight : 6 %

POLYROOF SF 3 GL.

Version 1.2

Print Date 08/11/2007

REVISION DATE: 09/01/2006

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Oxidizing agents.
 Stability : Material is stable under normal storage, handling, and use.
 Hazardous polymerization : Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Butyl benzyl phthalate, CAS-No.: 85-68-7
 Acute oral toxicity (LD-50 oral) 13,500 mg/kg (Rat)
 4,4'-Methylene bis(phenylisocyanate), CAS-No.: 101-68-8
 Acute inhalation toxicity (LC-50) 0.38 mg/l (Rat)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:
 NOT REGULATED

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

This product or its components are listed on, or exempt from the Canadian Domestic Substances List. All components are listed or exempt from the TSCA inventory.

U.S. Federal Regulations:

SARA 313 Components : 4,4'-Methylene bis(phenylisocyanate) 101-68-8

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :

Carbon Black 1333-86-4
 4,4'-Methylene bis(phenylisocyanate) 101-68-8

OSHA Status: Considered : Irritant

POLYROOF SF 3 GL

Version 1.2

Print Date 08/11/2007

REVISION DATE: 09/01/2006

hazardous based on the following criteria: Sensitizer

OSHA Flammability : IIIB

Regulatory VOC (less water and exempt solvent) : 65 g/l

VOC Method 310 : 6 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:
Carbon Black 1333-86-4

U.S. State Regulations:

- MASS RTK Components : Butyl benzyl phthalate 85-68-7
Carbon Black 1333-86-4
4,4'-Methylene bis(phenylisocyanate) 101-68-8
- Penn RTK Components : Asphalt 64741-56-6
Polyurethane polymer NJ TSRN# 51721300-5119P
Butyl benzyl phthalate 85-68-7
Carbon Black 1333-86-4
4,4'-Methylene bis(phenylisocyanate) 101-68-8
- NJ RTK Components : Asphalt 64741-56-6
Polyurethane polymer NJ TSRN# 51721300-5119P
Butyl benzyl phthalate 85-68-7
Carbon Black 1333-86-4
4,4'-Methylene bis(phenylisocyanate) 101-68-8

Chemicals known to the State of California to cause cancer birth defects and/or other reproductive harm:
1333-86-4 Carbon Black
117-81-7 Dioctyl phthalate

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	1
Reactivity	1
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

PEL - Permissible Exposure Limit
RCRA - Resource Conservation and Recovery Act

POLYROOF SF 3 GL

Version 1.2

Print Date 08/11/2007

REVISION DATE: 09/01/2006

DOT - Department of Transportation
DSL - Domestic Substance List
EPA - Environmental Protection Agency
HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

RTK - Right To Know
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume
VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System