



**POWERPLY PLUS HT FR - WHITE GRANULE POWERPLY PLUS HT FR - WHITE GRANULE**

Version 2.0  
 REVISION DATE: 07/08/2012

Print Date 05/31/2015

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : POWERPLY PLUS HT FR - WHITE GRANULE  
 Product code : 036PLHTFR601  
 COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122  
 Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300  
 Product use : Roof Sheeting

RECEIVED  
 15 JUN -8 AM 10:42

**SECTION 2 - HAZARDS IDENTIFICATION**

Emergency Overview

Various colors. Solid ply rolls. Not applicable under normal conditions of use. Generally not required under normal conditions of use.

Acute Potential Health Effects/ Routes of Entry

Inhalation : Not applicable under normal conditions of use.  
 Eyes : Not applicable under normal conditions of use.  
 Ingestion : Not applicable under normal conditions of use.  
 Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

This product contains granular materials which may cause mechanical skin, eye or respiratory irritation. Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation.

Target Organs: Skin, Eye, Lung

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Asphalt	8052-42-4	30.0 - 60.0



**POWERPLY PLUS HT FR - WHITE GRANULE POWERPLY PLUS HT FR - WHITE GRANULE**

Version 2.0

Print Date 05/31/2015

REVISION DATE: 07/08/2012

Rhyolitic argillite/roofing granules	NJ TSRN# 51721300-5488P	15.0 - 40.0
Fire retardant	NJ TSRN# 51721300-5035P	15.0 - 40.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	15.0 - 40.0
Styrene-butadiene copolymers	NJ TSRN# 51721300-5132P	5.0 - 10.0
Fibrous Glass	65997-17-3	1.0 - 5.0
Clay	1332-58-7	1.0 - 5.0
Carbon Black	1333-86-4	- <1.0

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Generally not required under normal conditions of use.
- Eye contact : Generally not required under normal conditions of use.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Not applicable under normal conditions of use.
- Notes to physician : Not applicable.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not available.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Hazardous combustion products : Hydrogen sulfide and hydrocarbon fractions.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Scrape up and transfer to appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

Store under normal warehouse conditions.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Use suitable impervious leather gloves and protective apparel to reduce exposure.



**POWERPLY PLUS HT FR - WHITE GRANULE POWERPLY PLUS HT FR - WHITE GRANULE**

Version 2.0  
 REVISION DATE: 07/08/2012

Print Date 05/31/2015

- Eye protection : Wear appropriate eye protection.
- Skin and body protection : Not required.
- Protective measures : Other equipment not normally required.
- Engineering measures : General ventilation is sufficient.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Asphalt	8052-42-4	ACGIH TWA: benzene solubles	0.5 mg/m3	Inhalable fraction.as
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
Fibrous Glass	65997-17-3	ACGIH TWA:	5 mg/m3	Inhalable fraction.
Clay	1332-58-7	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	2 mg/m3 15 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3 5 mg/m3 15 mg/m3	Respirable fraction. Total dust. Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust.
Carbon Black	1333-86-4	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	3.5 mg/m3 3.5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Solid ply rolls
- Color : Various colors
- Odor : None
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Not available.
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Not available.
- Specific Gravity : 1.3



**POWERPLY PLUS HT FR - WHITE GRANULE**  
**POWERPLY PLUS HT FR -**  
**WHITE GRANULE**

Version 2.0

Print Date 05/31/2015

REVISION DATE: 07/08/2012

% Volatile Weight : 0 %

**SECTION 10 - REACTIVITY / STABILITY**

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Aluminum hydroxide, CAS-No.: 21645-51-2  
Acute oral toxicity (LD-50 oral) 5,000 mg/kg ( Rat )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : As purchased, this product, when discarded, is not a listed or characteristic hazardous waste according to Federal regulations (40 CFR 261). Check local, regional, state or provincial regulations for applicable requirements for disposal. Any processing, using, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the generator's responsibility to determine if a waste is a hazardous waste. Empty containers may retain product residue. Do not reuse.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**CFR / DOT:**

Not Regulated

**TDG:**

Not Regulated

**IMDG:**

Not Regulated

**SECTION 15 - REGULATORY INFORMATION**

North American Inventories:



**POWERPLY PLUS HT FR - WHITE GRANULE POWERPLY PLUS HT FR - WHITE GRANULE**

Version 2.0

Print Date 05/31/2015

REVISION DATE: 07/08/2012

All components are listed or exempt from the TSCA inventory.  
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

- SARA 313 Components : None present or none present in regulated quantities.
- SARA 311/312 Hazards : Acute Health Hazard  
 Chronic Health Hazard

OSHA Hazardous Components :

- Asphalt 8052-42-4
- Crystalline Silica (Quartz)/ Silica Sand 14808-60-7
- Fibrous Glass 65997-17-3
- Clay 1332-58-7
- Carbon Black 1333-86-4

OSHA Status: Considered : Irritant  
 hazardous based on the : Carcinogen  
 following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 0 g/l  
 exempt solvent)

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

- Crystalline Silica (Quartz)/ Silica Sand 14808-60-7
- Carbon Black 1333-86-4

**U.S. State Regulations:**

- MASS RTK Components : Asphalt 8052-42-4  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7  
 Fibrous Glass 65997-17-3  
 Clay 1332-58-7
- Penn RTK Components : Asphalt 8052-42-4  
 Rhyolitic argillite/roofing granules NJ TSRN# 51721300-5488P  
 Fire retardant NJ TSRN# 51721300-5035P  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7  
 Styrene-butadiene copolymers NJ TSRN# 51721300-5132P  
 Fibrous Glass 65997-17-3  
 Clay 1332-58-7
- NJ RTK Components : Asphalt 8052-42-4  
 Rhyolitic argillite/roofing granules NJ TSRN# 51721300-5488P  
 Fire retardant NJ TSRN# 51721300-5035P  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7  
 Styrene-butadiene copolymers NJ TSRN# 51721300-5132P  
 Fibrous Glass 65997-17-3  
 Carbon Black 1333-86-4



**POWERPLY PLUS HT FR - WHITE GRANULE POWERPLY PLUS HT FR - WHITE GRANULE**

Version 2.0

Print Date 05/31/2015

REVISION DATE: 07/08/2012

Components under California Proposition 65:  
**WARNING!** Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT - Department of Transportation  
 DSL - Domestic Substance List  
 EPA - Environmental Protection Agency  
 HMIS - Hazardous Materials Information System  
 IARC - International Agency for Research on Cancer  
 MSHA - Mine Safety Health Administration  
 NDSL - Non-Domestic Substance List  
 NIOSH - National Institute for Occupational Safety and Health  
 NTP - National Toxicology Program  
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
 RCRA - Resource Conservation and Recovery Act  
 RTK - Right To Know  
 SARA - Superfund Amendments and Reauthorization Act  
 STEL - Short Term Exposure Limit  
 TLV - Threshold Limit Value  
 TSCA - Toxic Substances Control Act  
 TWA - Time Weighted Average  
 V - Volume  
 VOC - Volatile Organic Compound  
 WHMIS - Workplace Hazardous Materials Information System