



POWERPLY STANDARD SMOOTH POWERPLY STANDARD SMOOTH

Version 2.0

Print Date 10/23/2012

REVISION DATE: 07/08/2012

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : POWERPLY STANDARD SMOOTH POWERPLY STANDARD SMOOTH
 Product code : 36STSM601

COMPANY : Tremco Incorporated
 3735 Green Road
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
 After Hours: Chemtrec 1-800-424-9300

Product use : Roof Sheeting

RECEIVED KPOA
12 OCT 30 PM 3:20

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Black. Solid ply rolls. Not applicable under normal conditions of use. Generally not required under normal conditions of use.

Acute Potential Health Effects/ Routes of Entry

Inhalation : Not applicable under normal conditions of use.
 Eyes : Not applicable under normal conditions of use.
 Ingestion : Not applicable under normal conditions of use.
 Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

This product contains granular materials which may cause mechanical skin, eye or respiratory irritation. The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Lung

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Calcium Carbonate (Limestone)	1317-65-3	40.0 - 70.0
Asphalt	8052-42-4	15.0 - 40.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	15.0 - 40.0



POWERPLY STANDARD SMOOTH POWERPLY STANDARD SMOOTH

Version 2.0

Print Date 10/23/2012

REVISION DATE: 07/08/2012

Magnesite	546-93-0	5.0 - 10.0
Styrene-butadiene copolymers	NJ TSRN# 51721300-5132P	1.0 - 5.0
Fibrous Glass	65997-17-3	1.0 - 5.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Generally not required under normal conditions of use.
- Eye contact : Generally not required under normal conditions of use.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Not applicable under normal conditions of use.
- Notes to physician : Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : Not available.
- Method : Not available.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Hazardous combustion products : Hydrogen sulfide and hydrocarbon fractions.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Store under normal warehouse conditions.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Use suitable impervious leather gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection.
- Skin and body protection : Not required.
- Protective measures : Other equipment not normally required.



POWERPLY STANDARD SMOOTH POWERPLY STANDARD SMOOTH

Version 2.0

Print Date 10/23/2012

REVISION DATE: 07/08/2012

Engineering measures : General ventilation is sufficient.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Asphalt	8052-42-4	ACGIH TWA:	0.5 mg/m3	Inhalable fraction.as benzene solubles
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.
Magnesite	546-93-0	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Fibrous Glass	65997-17-3	ACGIH TWA:	5 mg/m3	Inhalable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Solid ply rolls
 Color : Black
 Odor : None
 pH : Not available.
 Vapour pressure : Not available.
 Vapor density : Not available.
 Melting point/range : Not available.
 Freezing point : Not available.
 Boiling point/range : Not available.
 Water solubility : Not available.
 Specific Gravity : 1.0
 % Volatile Weight : 0 %

SECTION 10 - REACTIVITY / STABILITY

Stability : Material is stable under normal storage, handling, and use.



POWERPLY STANDARD SMOOTH POWERPLY STANDARD SMOOTH

Version 2.0

Print Date 10/23/2012

REVISION DATE: 07/08/2012

Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : As purchased, this product, when discarded, is not a listed or characteristic hazardous waste according to Federal regulations (40 CFR 261). Check local, regional, state or provincial regulations for applicable requirements for disposal. Any processing, using, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the generator's responsibility to determine if a waste is a hazardous waste. Empty containers may retain product residue. Do not reuse.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :



POWERPLY STANDARD SMOOTH POWERPLY STANDARD SMOOTH

Version 2.0

Print Date 10/23/2012

REVISION DATE: 07/08/2012

Calcium Carbonate (Limestone)	1317-65-3
Asphalt	8052-42-4
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
Magnesite	546-93-0
Fibrous Glass	65997-17-3

OSHA Status: Considered : Irritant
 hazardous based on the
 following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and
 exempt solvent) : 0 g/l

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
Fibrous Glass	65997-17-3

U.S. State Regulations:

MASS RTK Components :	Calcium Carbonate (Limestone)	1317-65-3
	Asphalt	8052-42-4
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
	Magnesite	546-93-0
	Fibrous Glass	65997-17-3

Penn RTK Components :	Calcium Carbonate (Limestone)	1317-65-3
	Asphalt	8052-42-4
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
	Magnesite	546-93-0
	Fibrous Glass	65997-17-3

NJ RTK Components :	Calcium Carbonate (Limestone)	1317-65-3
	Asphalt	8052-42-4
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
	Magnesite	546-93-0
	Styrene-butadiene copolymers	NJ TSRN# 51721300-5132P
Fibrous Glass	65997-17-3	

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe



POWERPLY STANDARD SMOOTH POWERPLY STANDARD SMOOTH

Version 2.0

Print Date 10/23/2012

REVISION DATE: 07/08/2012

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
DOT - Department of Transportation
DSL - Domestic Substance List
EPA - Environmental Protection Agency
HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit
RCRA - Resource Conservation and Recovery Act
RTK - Right To Know
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume
VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System