



SOLARGARD SEAM SEALER 5 GAL

Version 6.0
 REVISION DATE: 07/23/2014

Print Date 10/11/2014

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : SOLARGARD SEAM SEALER 5 GAL
 Product code : 151105P
 COMPANY : Tremco Incorporated
 3735 Green Road
 Cleveland, OH 44122
 Telephone : (216) 292-5000 8:30 - 5:00 EST
 Emergency Phone : (216) 765-6727 8:30 - 5:00 EST
 After Hours: Chemtrec 1-800-424-9300
 Product use : Sealant

RECEIVED KOD
 14 OCT 22 AM 9:17

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

White. Non-sag gunnable paste. May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization.
 Eyes : Direct contact may cause mild irritation.
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
 Skin : May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

Target Organs: Skin, Eye, Ingestion, Lung

SOLARGARD SEAM SEALER 5 GALVersion 6.0
REVISION DATE: 07/23/2014

Print Date 10/11/2014

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Polyurethane Polymer	NJ TSRN# 51721300-5358P	15.0 - 40.0
ASEP	70775-94-9	15.0 - 40.0
Calcium Carbonate (Limestone)	1317-65-3	15.0 - 40.0
Polyvinyl chloride	9002-86-2	15.0 - 40.0
Titanium dioxide	13463-67-7	3.0 - 7.0
Petroleum distillates	64742-47-8	3.0 - 7.0
Calcium oxide	1305-78-8	1.0 - 5.0
Xylene	1330-20-7	1.0 - 5.0
Isophorone Diisocyanate	4098-71-9	0.1 - 1.0
Aluminum oxide	1344-28-1	0.1 - 1.0
Ethylbenzene	100-41-4	0.1 - 1.0
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : > 93 °C, > 199 °F
- Method : Setflash Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Hydrocyanic acid and nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

SOLARGARD SEAM SEALER 5 GAL

Version 6.0
 REVISION DATE: 07/23/2014

Print Date 10/11/2014

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion and contact with skin, eyes and clothing. Preferably use entire contents in one continuous work session. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not store or use near food. Keep container closed when not in use. Since emptied containers retain product residue and vapor, observe precautions even after container is emptied. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Skin and body protection : Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Polyvinyl chloride	9002-86-2	ACGIH TWA:	1 mg/m3	Respirable fraction.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
		OSHA TWA:	15 mg/m3	Total dust.

SOL ARGARD SEAM SEALER 5 GAL

Version 6.0

Print Date 10/11/2014

REVISION DATE: 07/23/2014

Chemical Name	CAS Number	Regulation	Limit	Form
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.
Petroleum distillates	64742-47-8	ACGIH TWA: hydrocarbon vapor ACGIH TWA: hydrocarbon vapor	200 mg/m3 200 mg/m3	Non-aerosol.as total Non-aerosol.as total
Calcium oxide	1305-78-8	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	2 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.
Xylene	1330-20-7	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 150 ppm 435 mg/m3	
Isophorone Diisocyanate	4098-71-9	ACGIH TWA:	0.005 ppm	
Aluminum oxide	1344-28-1	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA: ACGIH TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3 1 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction. Respirable fraction.
Ethylbenzene	100-41-4	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 125 ppm 435 mg/m3	
Hydrotreated heavy naphthenic distillate	64742-52-5	OSHA PEL: OSHA PEL: ACGIH TWA:	2,000 mg/m3 5 mg/m3 5 mg/m3	Mist. Inhalable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Non-sag gunnable paste
Color	: White
Odor	: Petroleum Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.

SOLARGARD SEAM SEALER 5 GAL

Version 6.0
 REVISION DATE: 07/23/2014

Print Date 10/11/2014

Water solubility : Insoluble
 Specific Gravity : 1.3
 % Volatile Weight : 6 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Amines. Water or moisture and oxidizing agents. Alcohols. Strong acids. Strong bases.
 Stability : Material is stable under normal storage, handling, and use.
 Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Titanium dioxide, CAS-No.: 13463-67-7
 Acute oral toxicity (LD-50 oral) 25,000 mg/kg (Rat) 5,000 mg/kg (Rat) 5,000 mg/kg (Rat)
 2,000 mg/kg (Rat) 11,000 mg/kg (Rat)
 Acute inhalation toxicity (LC-50) > 6.82 mg/l for 4 h (Rat) 3.43 mg/l for 4 h (Rat) 5.09 mg/l
 for 4 h (Rat) > 2.28 mg/l for 4 h (Rat) > 3.56 mg/l for 4 h (Rat)

Xylene, CAS-No.: 1330-20-7
 Acute oral toxicity (LD-50 oral) 4,300 mg/kg (Rat) 1,590 mg/kg (Mouse) 6,670 mg/kg (Rat)
 3,523 - 8,600 mg/kg (Rat) 5,627 mg/kg (Mouse)
 Acute inhalation toxicity (LC-50) 6,350 mg/l for 4 h (Rat) 3,907 mg/l for 6 h (Mouse) 8,000
 mg/l for 4 h (Rat)

Isophorone Diisocyanate, CAS-No.: 4098-71-9
 Acute oral toxicity (LD-50 oral) 2,500 mg/kg (Mouse) 1,000 mg/kg (Rat)
 Acute inhalation toxicity (LC-50) 0.033 mg/l for 4 h (Rat) 0.123 mg/l for 4 h (Rat)
 Acute dermal toxicity (LD-50 dermal) 1,060 mg/kg (Rat)

Ethylbenzene, CAS-No.: 100-41-4
 Acute oral toxicity (LD-50 oral) 5,460 mg/kg (Rat) 3,500 mg/kg (Rat)
 Acute dermal toxicity (LD-50 dermal) 17,800 mg/kg (Rabbit)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

SOLARGARD SEAM SEALER 5 GAL

Version 6.0
 REVISION DATE: 07/23/2014

Print Date 10/11/2014

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : Xylene 1330-20-7
 Ethylbenzene 100-41-4

SARA 311/312 Hazards : Acute Health Hazard
 Chronic Health Hazard
 Fire Hazard

OSHA Hazardous Components :

Calcium Carbonate (Limestone)	1317-65-3
Polyvinyl chloride	9002-86-2
Titanium dioxide	13463-67-7
Petroleum distillates	64742-47-8
Calcium oxide	1305-78-8
Xylene	1330-20-7
Isophorone Diisocyanate	4098-71-9
Aluminum oxide	1344-28-1
Ethylbenzene	100-41-4
Hydrotreated heavy naphthenic distillate	64742-52-5

OSHA Status: Considered : Irritant
 hazardous based on the : Carcinogen
 following criteria:

OSHA Flammability : IIIA

Regulatory VOC (less water and : 82 g/l
 exempt solvent)

VOC Method 310 : 6.33 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:
 Hydrotreated heavy naphthenic distillate 64742-52-5

SOLARGARD SEAM SEALER 5 GAL

Version 6.0
 REVISION DATE: 07/23/2014

Print Date 10/11/2014

U.S. State Regulations:

<p>MASS RTK Components :</p>	<p>Calcium Carbonate (Limestone) 1317-65-3 Titanium dioxide 13463-67-7 Petroleum distillates 64742-47-8 Calcium oxide 1305-78-8 Xylene 1330-20-7 Isophorone Diisocyanate 4098-71-9</p>
<p>Penn RTK Components :</p>	<p>Polyurethane Polymer NJ TSNR# 51721300-5358P ASEP 70775-94-9 Calcium Carbonate (Limestone) 1317-65-3 Polyvinyl chloride 9002-86-2 Titanium dioxide 13463-67-7 Petroleum distillates 64742-47-8 Calcium oxide 1305-78-8 Xylene 1330-20-7</p>
<p>NJ RTK Components :</p>	<p>Polyurethane Polymer NJ TSNR# 51721300-5358P ASEP 70775-94-9 Calcium Carbonate (Limestone) 1317-65-3 Polyvinyl chloride 9002-86-2 Titanium dioxide 13463-67-7 Petroleum distillates 64742-47-8 Calcium oxide 1305-78-8 Xylene 1330-20-7 Hydrotreated heavy naphthenic distillate 64742-52-5</p>

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	2
Reactivity	0
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

PEL - Permissible Exposure Limit
 RCRA - Resource Conservation and Recovery Act

SOLARGARD SEAM SEALER 5 GAL

Version 6.0

Print Date 10/11/2014

REVISION DATE: 07/23/2014

DOT - Department of Transportation
DSL - Domestic Substance List
EPA - Environmental Protection Agency
HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

RTK - Right To Know
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume
VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System