

**TREMLASTIC S 55 GL TREMLASTIC S 55 GL**

Version 1.3

Print Date 06/13/2008

REVISION DATE: 09/01/2006

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : TREMLASTIC S 55 GL TREMLASTIC S 55 GL  
 Product code : 344620L855

COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Black. Liquid. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause slight irritation to the respiratory system.  
 Eyes : Direct contact may cause mild irritation.  
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.  
 Skin : May cause mild irritation. May cause sensitization resulting in irritation, itching and redness. May cause a rash.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Prolonged or repeated skin contact with asphalt may result in skin sensitivity, such as irritation, rashes, and dermatitis. Prolonged or repeated exposure to polycyclic aromatic hydrocarbons and other volatiles which are contained in trace amounts in asphalt have been shown to cause cancer or respiratory damage in animals. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Long term overexposure to propylene glycol caused liver abnormalities, kidney damage in laboratory animals. Repeated excessive ingestion may cause central nervous system effects. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	40.0 - 70.0
Asphalt	8052-42-4	40.0 - 70.0
Neoprene latex	NJ TSN# 51721300-5016P	5.0 - 10.0
Propylene glycol	57-55-6	1.0 - 5.0
Bentonite	1302-78-9	1.0 - 5.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	<1.0



**TREMLASTIC S 55 GL TREMLASTIC S 55 GL**

Version 1.3  
 REVISION DATE: 09/01/2006

Print Date 06/13/2008

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not available.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Oxides of sulfur can form.
- Protective equipment for firefighters : Not applicable. Product is not expected to burn.
- Fire and explosion conditions : Not applicable, not expected to burn.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.

**TREMLASTIC S 55 GL TREMLASTIC S 55 GL**

Print Date 06/13/2008

Version 1.3

REVISION DATE: 09/01/2006

- Eye protection : Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use. Other equipment not normally required.
- Engineering measures : General ventilation is sufficient. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Asphalt	8052-42-4	ACGIH TWA: benzene solubles	0.5 mg/m3	Inhalable fraction.as
Bentonite	1302-78-9	ACGIH TWA: ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3	Respirable particles. Inhalable particles. Total dust. Respirable fraction. Total dust. Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	ACGIH TWA: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	0.05 mg/m3 0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Respirable. Total dust. Total dust. Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Liquid
- Color : Black
- Odor : Asphalt
- pH : 10 - 12
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : 212 °F, 100 °C
- Water solubility : Dispersible
- Specific Gravity : 1.0108
- % Volatile Weight : 48 %

**SECTION 10 - REACTIVITY / STABILITY**

- Substances to avoid : Oxidizing agents.
- Stability : Material is stable under normal storage, handling, and use.

**TREMLASTIC S 55 GL TREMLASTIC S 55 GL**

Version 1.3

Print Date 06/13/2008

REVISION DATE: 09/01/2006

Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Propylene glycol, CAS-No.: 57-55-6  
 Acute oral toxicity (LD-50 oral) 30,000 mg/kg ( Rat )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
 NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard  
 Chronic Health Hazard

**OSHA Hazardous Components :**

Asphalt	8052-42-4
Bentonite	1302-78-9
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

OSHA Status: Considered : Irritant  
 hazardous based on the : Carcinogen  
 following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 25 g/l  
 exempt solvent)

VOC Method 310 : 1 %

**TREMLASTIC S 55 GL TREMLASTIC S 55 GL**

Print Date 06/13/2008

Version 1.3

REVISION DATE: 09/01/2006

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

**U.S. State Regulations:**

- MASS RTK Components : Asphalt 8052-42-4
- Penn RTK Components : Water 7732-18-5  
 Asphalt 8052-42-4  
 Neoprene latex NJ TSRN# 51721300-5016P  
 Propylene glycol 57-55-6
- NJ RTK Components : Water 7732-18-5  
 Asphalt 8052-42-4  
 Neoprene latex NJ TSRN# 51721300-5016P  
 Propylene glycol 57-55-6  
 Bentonite 1302-78-9  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Chemicals known to the State of California to cause cancer birth defects and/or other reproductive harm:  
 8052-42-4 Asphalt  
 14808-60-7 Crystalline Silica (Quartz)/ Silica Sand

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	0
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

- ACGIH - American Conference of Governmental Hygienists
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration

- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- RTK - Right To Know
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System



**TREMLASTIC S 55 GL TREMLASTIC S 55 GL**

Version 1.3

Print Date 06/13/2008

REVISION DATE: 09/01/2006