

**TREMSEAL D LIMESTONE, 30CTGS/CS LVTREMSEAL D LIMESTONE,
30CTGS/CS LV**

Version 3.0

Print Date 07/26/2012

REVISION DATE: 07/08/2012

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : TREMSEAL D LIMESTONE, 30CTGS/CS LVTREMSEAL D LIMESTONE,
30CTGS/CS LV

Product code : 876153 309

COMPANY : Tremco Incorporated
3735 Green Road
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST

Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Limestone. Non-sag gunnable paste. May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization.

Eyes : Direct contact may cause mild irritation.

Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

Target Organs: Skin, Eye, Ingestion, Lung

**TREMSEAL D LIMESTONE, 30CTGS/CS LVTREMSEAL D LIMESTONE,
30CTGS/CS LV**

Version 3.0

Print Date 07/26/2012

REVISION DATE: 07/08/2012

SECTION 3 - PRODUCT COMPOSITION

| Chemical Name | CAS-No. | Weight % |
|--|-------------------------|-------------|
| Aromatic Polyisocyanate Resin | NJ TSRN# 51721300-5270P | 30.0 - 60.0 |
| Diisodecyl phthalate | 26761-40-0 | 15.0 - 40.0 |
| Calcium Carbonate (Limestone) | 1317-65-3 | 10.0 - 30.0 |
| Tackifier | NJ TSRN# 51721300-5272P | 5.0 - 10.0 |
| Thickener | NJ TSRN# 51721300-5300P | 3.0 - 7.0 |
| Titanium dioxide | 13463-67-7 | 3.0 - 7.0 |
| Petroleum distillates | 64742-47-8 | 1.0 - 5.0 |
| Butyl benzyl phthalate | 85-68-7 | - <1.0 |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 | - <1.0 |
| Toluene-2,6-Diisocyanate | 91-08-7 | - <0.1 |
| 2,4-Toluene diisocyanate | 584-84-9 | - <0.1 |
| o-Cresol | 95-48-7 | - <0.1 |

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : 150 °F, 66 °C
- Method : Tag Closed Cup
- Lower explosion limit : 0.60 %(V) Solvent
- Upper explosion limit : 7 %(V) Solvent
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Hydrocyanic acid and nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).



TREMSEAL D LIMESTONE, 30CTGS/CS LVTREMSEAL D LIMESTONE, 30CTGS/CS LV

Version 3.0

Print Date 07/26/2012

REVISION DATE: 07/08/2012

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion and contact with skin, eyes and clothing. Preferably use entire contents in one continuous work session. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not store or use near food. Keep container closed when not in use. Since emptied containers retain product residue and vapor, observe precautions even after container is emptied. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Skin and body protection : Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

Exposure Limits

| Chemical Name | CAS Number | Regulation | Limit | Form |
|----------------------------------|------------|------------|----------|-----------------------|
| Calcium Carbonate (Limestone) | 1317-65-3 | OSHA PEL: | 5 mg/m3 | Respirable fraction. |
| | | OSHA PEL: | 15 mg/m3 | Total dust. |
| | | ACGIH TWA: | 3 mg/m3 | Respirable particles. |
| | | ACGIH TWA: | 10 mg/m3 | Inhalable particles. |
| | | OSHA TWA: | 15 mg/m3 | Total dust. |
| | | OSHA TWA: | 5 mg/m3 | Respirable fraction. |
| Titanium dioxide | 13463-67-7 | ACGIH TWA: | 10 mg/m3 | |
| | | OSHA PEL: | 15 mg/m3 | Total dust. |
| | | OSHA TWA: | 15 mg/m3 | Total dust. |
| | | OSHA TWA: | 5 mg/m3 | Respirable fraction. |

**TREMSEAL D LIMESTONE, 30CTGS/CS LVTREMSEAL D LIMESTONE,
30CTGS/CS LV**

Version 3.0

Print Date 07/26/2012

REVISION DATE: 07/08/2012

| Chemical Name | CAS Number | Regulation | Limit | Form |
|---|------------|--|--|---|
| Petroleum distillates | 64742-47-8 | ACGIH TWA: hydrocarbon vapor | 200 mg/m3 | Non-aerosol.as total |
| | | ACGIH TWA: hydrocarbon vapor | 200 mg/m3 | Non-aerosol.as total |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 | OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA: | 0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3 | Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction. |
| Toluene-2,6-Diisocyanate | 91-08-7 | ACGIH TWA: ACGIH STEL: | 0.005 ppm 0.02 ppm | |
| 2,4-Toluene diisocyanate | 584-84-9 | ACGIH TWA: ACGIH STEL: | 0.005 ppm 0.02 ppm | |
| o-Cresol | 95-48-7 | OSHA PEL: ACGIH TWA: | 22 mg/m3 20 mg/m3 | inhalable fraction and vapor. |

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---------------------|--------------------------|
| Form | : Non-sag gunnable paste |
| Color | : Limestone |
| Odor | : Petroleum Solvent |
| pH | : Not available. |
| Vapour pressure | : Not available. |
| Vapor density | : Heavier than air |
| Melting point/range | : Not available. |
| Freezing point | : Not available. |
| Boiling point/range | : 280 °F, 138 °C |
| Water solubility | : Insoluble |
| Specific Gravity | : 1.1344 |
| % Volatile Weight | : 6 % |

SECTION 10 - REACTIVITY / STABILITY

| | |
|--------------------------|---|
| Substances to avoid | : Amines.Water or moisture and oxidizing agents.Alcohols.Strong acids.Strong bases. |
| Stability | : Material is stable under normal storage, handling, and use. |
| Hazardous polymerization | : Will not occur. |

TREMSEAL D LIMESTONE, 30CTGS/CS LV
TREMSEAL D LIMESTONE, 30CTGS/CS LV

Version 3.0

Print Date 07/26/2012

REVISION DATE: 07/08/2012

SECTION 11 - TOXICOLOGICAL INFORMATION

Butyl benzyl phthalate, CAS-No.: 85-68-7

Acute oral toxicity (LD-50 oral) 13,500 mg/kg (Rat)

2,4-Toluene diisocyanate, CAS-No.: 584-84-9

Acute oral toxicity (LD-50 oral) 5,800 mg/kg (Rat)

Acute inhalation toxicity (LC-50) 14 mg/l for 4 h (Rat) 10 mg/l for 4 h (Mouse) 13 mg/l for 4 h (Guinea pig) 11 mg/l for 4 h (Rabbit)

o-Cresol, CAS-No.: 95-48-7

Acute oral toxicity (LD-50 oral) 940 mg/kg (Rabbit) 1,800 mg/kg (Rabbit) 121 mg/kg (Rat) 344 mg/kg (Mouse) 1,350 mg/kg (Rat)

Acute inhalation toxicity (LC-50) 0.179 mg/l for 2 h (Mouse)

Acute dermal toxicity (LD-50 dermal) 620 mg/kg (Rat) 890 mg/kg (Rabbit) 620 mg/kg (Mouse)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA**CFR / DOT:**

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.



TREMSEAL D LIMESTONE, 30CTGS/CS LVTREMSEAL D LIMESTONE, 30CTGS/CS LV

Version 3.0

Print Date 07/26/2012

REVISION DATE: 07/08/2012

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard
Fire Hazard

OSHA Hazardous Components :

| | |
|--|------------|
| Diisodecyl phthalate | 26761-40-0 |
| Calcium Carbonate (Limestone) | 1317-65-3 |
| Titanium dioxide | 13463-67-7 |
| Petroleum distillates | 64742-47-8 |
| Butyl benzyl phthalate | 85-68-7 |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 |
| Toluene-2,6-Diisocyanate | 91-08-7 |
| 2,4-Toluene diisocyanate | 584-84-9 |
| o-Cresol | 95-48-7 |

OSHA Status: Considered : Irritant
hazardous based on the Sensitizer
following criteria: Carcinogen

OSHA Flammability : IIIA

Regulatory VOC (less water and : 79 g/l
exempt solvent)

VOC Method 310 : 2 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

| | |
|--|------------|
| Butyl benzyl phthalate | 85-68-7 |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 |

U.S. State Regulations:

| | | |
|-----------------------|--|------------|
| MASS RTK Components : | Calcium Carbonate (Limestone) | 1317-65-3 |
| | Titanium dioxide | 13463-67-7 |
| | Petroleum distillates | 64742-47-8 |
| | Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 |
| | Toluene-2,6-Diisocyanate | 91-08-7 |
| | 2,4-Toluene diisocyanate | 584-84-9 |
| | o-Cresol | 95-48-7 |

| | | |
|-----------------------|-------------------------------|-------------------------|
| Penn RTK Components : | Aromatic Polyisocyanate Resin | NJ TSRN# 51721300-5270P |
| | Diisodecyl phthalate | 26761-40-0 |
| | Calcium Carbonate (Limestone) | 1317-65-3 |
| | Tackifier | NJ TSRN# 51721300-5272P |
| | Thickener | NJ TSRN# 51721300-5300P |
| | Titanium dioxide | 13463-67-7 |
| | Petroleum distillates | 64742-47-8 |
| | 2,4-Toluene diisocyanate | 584-84-9 |

| | | |
|---------------------|-------------------------------|-------------------------|
| NJ RTK Components : | Aromatic Polyisocyanate Resin | NJ TSRN# 51721300-5270P |
| | Diisodecyl phthalate | 26761-40-0 |



TREMSEAL D LIMESTONE, 30CTGS/CS LV
TREMSEAL D LIMESTONE, 30CTGS/CS LV

Version 3.0

Print Date 07/26/2012

REVISION DATE: 07/08/2012

| | |
|--|-------------------------|
| Calcium Carbonate (Limestone) | 1317-65-3 |
| Tackifier | NJ TSRN# 51721300-5272P |
| Thickener | NJ TSRN# 51721300-5300P |
| Titanium dioxide | 13463-67-7 |
| Petroleum distillates | 64742-47-8 |
| Butyl benzyl phthalate | 85-68-7 |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 |

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

| | |
|--------------|---|
| Health | 2 |
| Flammability | 2 |
| Reactivity | 0 |
| PPE | |

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

- ACGIH - American Conference of Governmental Hygienists
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration

- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- RTK - Right To Know
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System