

TREMSEAL HP PRETINT LIMESTONE 1.5 Gal
TREMSEAL HP PRETINT LIMESTONE 1.5 Gal

Version 5.0

Print Date 06/06/2013

REVISION DATE: 11/15/2012

SECTION 1 - PRODUCT IDENTIFICATION

Trade name	:	TREMSEAL HP PRETINT LIMESTONE 1.5 Gal
	:	TREMSEAL HP PRETINT LIMESTONE 1.5 Gal
Product code	:	876040 802
COMPANY	:	Tremco Incorporated
	:	3735 Green Road
	:	Cleveland, OH 44122
Telephone	:	(216) 292-5000 8:30 - 5:00 EST
Emergency Phone:	:	(216) 765-6727 8:30 - 5:00 EST
	:	After Hours: Chemtrec 1-800-424-9300
Product use	:	Sealant

RECEIVED
13 JUN 12 AM 9:09
KCDV**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Limestone. Non-sag gunnable paste. May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization.

Eyes : Direct contact may cause mild irritation.

Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Prolonged or repeated exposure to butyl benzyl phthalate may cause reduced body weights and adverse effects on the liver, kidney, spleen, pancreas, and reproductive organs. The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Ingestion, Lung

TREMSEAL HP PRETINT LIMESTONE 1.5 Gal
TREMSEAL HP PRETINT LIMESTONE 1.5 Gal

Version 5.0

Print Date 06/06/2013

REVISION DATE: 11/15/2012

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Calcium carbonate	471-34-1	40.0 - 70.0
Polyol	NJ TSRN# 517213--6317P	30.0 - 60.0
Fibrous Glass	65997-17-3	7.0 - 13.0
Titanium dioxide	13463-67-7	3.0 - 7.0
Butyl benzyl phthalate	85-68-7	3.0 - 7.0
Calcium oxide	1305-78-8	1.0 - 5.0
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1.0
Aluminum oxide	1344-28-1	0.1 - 1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : Not available.
- Method : Not available.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Hydrocyanic acid and nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.



TREMSEAL HP PRETINT LIMESTONE 1.5 Gal
LIMESTONE 1.5 Gal

Version 5.0

Print Date 06/06/2013

REVISION DATE: 11/15/2012

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion and contact with skin, eyes and clothing. Preferably use entire contents in one continuous work session. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not store or use near food. Keep container closed when not in use. Since emptied containers retain product residue and vapor, observe precautions even after container is emptied. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Skin and body protection : Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

Exposure Limits

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Fibrous Glass	65997-17-3	ACGIH TWA:	5 mg/m3	Inhalable fraction.
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.
Calcium oxide	1305-78-8	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	2 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.
Hydrotreated heavy naphthenic distillate	64742-52-5	OSHA PEL: OSHA PEL: ACGIH TWA:	2,000 mg/m3 5 mg/m3 5 mg/m3	Mist. Inhalable fraction.

TREMSEAL HP PRETINT LIMESTONE 1.5 Gal
LIMESTONE 1.5 Gal

Version 5.0

Print Date 06/06/2013

REVISION DATE: 11/15/2012

Chemical Name	CAS Number	Regulation	Limit	Form
Aluminum oxide	1344-28-1	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	1 mg/m3	Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Non-sag gunnable paste
Color	: Limestone
Odor	: Petroleum Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Insoluble
Specific Gravity	: 1.02
% Volatile Weight	: 0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Amines. Water or moisture and oxidizing agents. Alcohols. Strong acids. Strong bases.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Calcium carbonate, CAS-No.: 471-34-1	
Acute oral toxicity (LD-50 oral)	6,450 mg/kg (Rat)
Butyl benzyl phthalate, CAS-No.: 85-68-7	
Acute oral toxicity (LD-50 oral)	13,500 mg/kg (Rat)



TREMSEAL HP PRETINT LIMESTONE 1.5 Gal
TREMSEAL HP PRETINT LIMESTONE 1.5 Gal

Version 5.0

Print Date 06/06/2013

REVISION DATE: 11/15/2012

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components :

Fibrous Glass	65997-17-3
Titanium dioxide	13463-67-7
Butyl benzyl phthalate	85-68-7
Calcium oxide	1305-78-8
Hydrotreated heavy naphthenic distillate	64742-52-5



TREMSEAL HP PRETINT LIMESTONE 1.5 Gal
TREMSEAL HP PRETINT LIMESTONE 1.5 Gal

Version 5.0

Print Date 06/06/2013

REVISION DATE: 11/15/2012

Aluminum oxide 1344-28-1

OSHA Status: Considered : Irritant
 hazardous based on the : Carcinogen
 following criteria:

OSHA Flammability : Not Regulated

When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:
 5 g/l

Regulatory VOC (less water and : 1 g/l
 exempt solvent)

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:
 Hydrotreated heavy naphthenic distillate 64742-52-5

U.S. State Regulations:

- | | | | |
|---------------------|---|--|------------------------|
| MASS RTK Components | : | Calcium carbonate | 471-34-1 |
| | | Fibrous Glass | 65997-17-3 |
| | | Titanium dioxide | 13463-67-7 |
| | | Butyl benzyl phthalate | 85-68-7 |
| | | Calcium oxide | 1305-78-8 |
| | | Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 |
| | | Benzene | 71-43-2 |
| Penn RTK Components | : | Calcium carbonate | 471-34-1 |
| | | Polyol | NJ TSRN# 517213--6317P |
| | | Fibrous Glass | 65997-17-3 |
| | | Titanium dioxide | 13463-67-7 |
| | | Butyl benzyl phthalate | 85-68-7 |
| | | Calcium oxide | 1305-78-8 |
| NJ RTK Components | : | Calcium carbonate | 471-34-1 |
| | | Polyol | NJ TSRN# 517213--6317P |
| | | Fibrous Glass | 65997-17-3 |
| | | Titanium dioxide | 13463-67-7 |
| | | Butyl benzyl phthalate | 85-68-7 |
| | | Calcium oxide | 1305-78-8 |
| | | Hydrotreated heavy naphthenic distillate | 64742-52-5 |

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm



TREMSEAL HP PRETINT LIMESTONE 1.5 Gal
TREMSEAL HP PRETINT LIMESTONE 1.5 Gal

Version 5.0
 REVISION DATE: 11/15/2012

Print Date 06/06/2013

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
 DOT - Department of Transportation
 DSL - Domestic Substance List
 EPA - Environmental Protection Agency
 HMIS - Hazardous Materials information System
 IARC - International Agency for Research on Cancer
 MSHA - Mine Safety Health Administration
 NDSL - Non-Domestic Substance List
 NIOSH - National Institute for Occupational Safety and Health
 NTP - National Toxicology Program
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit
 RCRA - Resource Conservation and Recovery Act
 RTK - Right To Know
 SARA - Superfund Amendments and Reauthorization Act
 STEL - Short Term Exposure Limit
 TLV - Threshold Limit Value
 TSCA - Toxic Substances Control Act
 TWA - Time Weighted Average
 V - Volume
 VOC - Volatile Organic Compound
 WHMIS - Workplace Hazardous Materials Information System