

DATE OF PREPARATION
FEB 21 1989

FOR COATINGS, RESINS AND RELATED MATERIALS
(Approved by US Department of Labor "Essentially Similar" to Form OSHA-20)

NFPA 1-12

Section 1

American Art Clay Co., Inc.
Reward Ceramic Color Mfrs., Co.
4717 W. Sixteenth Street
Indianapolis, IN 46222

EMERGENCY TELEPHONE NO.:
(317) 244-6871, (800) 428-3239, (800) 358-8252,
or contact your local poison control center.
TELEX 272145 AMACO IND

pg. 1

PRODUCT CLASS: Modeling Material

TRADE NAME: Friendly Plastic

MANUFACTURERS CODE IDENTIFICATION: # 23825 -
23833

5719-00 5763-00
~~5723-00~~ 5764-00
5725-04 5765-00
1528

BOX 1207
REWARD CLAY CO.

Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV		LEL	VAPOR PRESSURE
		PPM	mg.M3		
"NON TOXIC" Bears the AP Seal Conforms to ASTM D-4236 See Section V					

SPECIAL LABELING INSTRUCTIONS

American Art Clay Co., Inc./Reward Ceramic Color Mfrs., Co. is a member of the Art and Craft Material Institute, 715 Boylston St., Boston MA 02116. Our art and craft materials are certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 (American Society for Testing and Materials). This product is appropriately labeled with one of the following nontoxic seals:



"Products bearing the Certified Products Seal or the AP Approved Product Seal of The Art Craft Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the Institute's Toxicological Advisory Board to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems.

In addition, products bearing the CP Seal meet specific requirements of materials, workmanship, working qualities and color described in the appropriate Product Standard issued by The Art and Craft Materials Institute, Inc. or other recognized standards organization."

23825-23833

Section III - PHYSICAL DATA

Melting Point - 140 - 144°F

DENSITY: NOT APPLICABLE, HEAVIER, LIGHTER, THAN AIR

EVAPORATION RATE: NOT APPLICABLE,
 FASTER, SLOWER, THAN ETHER

PERCENT VOLATILE
BY VOLUME: None

SPECIFIC GRAVITY:
1.15

Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: None

Auto-ignition - 38°C +/- 5°C

EXTINGUISHING MEDIA: NOT APPLICABLE - no fire or explosion hazard

Use water spray, carbon dioxide, dry

chemical, alcohol-type or universal-type foams.

UNUSUAL FIRE AND EXPLOSION HAZARDS NONE

Not Available

SPECIAL FIRE FIGHTING PROCEDURES: NONE

Use self-contained breathing apparatus and protective clothing.

Section V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: TLV - not established
Non-Toxic - Bears AP Seal - Conforms to ASTM D-4236

23825

pg. 2

EFFECTS OF OVEREXPOSURE:

None currently known

EMERGENCY AND FIRST AID PROCEDURES: Skin: wash with soap and water.
Eyes: Flush with water.

Section VI - REACTIVITY DATA

STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: None
INCOMPATIBILITY (materials to avoid): None

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may form carbon monoxide and/or carbon dioxide under certain conditions.

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR CONDITIONS TO AVOID: None

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Collect for disposal

WASTE DISPOSAL METHOD: Dispose in accordance with federal, state, and local regulations.

Section VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION
None

VENTILATION: General (mechanical) room ventilation is expected to be satisfactory.

PROTECTIVE GLOVES: None
EYE PROTECTION: None
OTHER PROTECTIVE EQUIPMENT: None

Section IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: None

OTHER PRECAUTIONS:
None