



Material Safety Data Sheet

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: DURACELL PROCELL PROFESSIONAL ALKALINE BATTERIES

Product Identification: Alkaline Manganese Dioxide Cells –

Duracell Designations: PC1300; PC1400; PC1500; PC1604; PC2400; PC9100; PC7K67; PC903
PC908

Product Use: Energy Source

MSDS Date of Preparation: July 1, 2008

Company Identification

US Office

Duracell, a division of P&G
Berkshire Industrial Park
14 Research Drive
Bethel, CT USA 06401
(203) 796-4000

Canadian Office

Duracell, a division of P&G
4711 Yonge Street
Toronto, Ontario
Canada M2N 6K8
(416) 730-4711

Emergency Phone Number: INFOTRAC Emergency Response Hotline 1-800-535-5053 (US & Canada)

SECTION 2: HAZARDS IDENTIFICATION

Physical Appearance: Cylindrical battery

EMERGENCY OVERVIEW

CAUTION: May explode or leak, and cause burn injury, if recharged, disposed of in fire, mixed with a different battery type, inserted backwards or disassembled. Replace all used batteries at the same time. Do not carry batteries loose in your pocket or purse. Do not remove the battery label.

Potential Health Effects:

The chemicals and metals in this product are contained in a sealed can. Exposure to the contents will not occur unless the battery leaks, is exposed to high temperatures or is mechanically, physically, or electrically abused. Damaged battery will release concentrated potassium hydroxide, which is caustic. Anticipated potential leakage of potassium hydroxide is 2 to 20 mL, depending on battery size. A similar amount of zinc may also leak.

Eye Contact: Contact with battery contents may cause severe irritation and burns. Eye damage is possible.

Skin Contact: Contact with battery contents may cause severe irritation and burns.

Inhalation: Inhalation of vapors or fumes released due to heat or a large number of leaking batteries may cause respiratory and eye irritation.

Ingestion: Swallowing is not anticipated due to battery size. Choking may occur if smaller AAA batteries are swallowed. Ingestion of battery contents (from a leaking battery) may cause mouth, throat and intestinal burns and damage.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS Number | Amount |
|---------------------------------|----------------------|--------|
| Manganese Dioxide | 1313-13-9 | 35-40% |
| Zinc | 7440-66-6 | 10-25% |
| Potassium Hydroxide (35%) | 1310-58-3 | 5-10% |
| Graphite (natural or synthetic) | 7782-42-5, 7440-44-0 | 1-5% |

SECTION 4: FIRST AID MEASURES

Eye Contact: If battery is leaking and material contacts the eye, flush thoroughly with copious amounts of running water for 30 minutes. Seek immediate medical attention.

Skin Contact: If battery is leaking and material contacts the skin, remove any contaminated clothing and flush exposed skin with copious amounts of running water for at least 15 minutes. If irritation, injury or pain persists, seek medical attention.

Inhaled: If battery is leaking, contents may be irritating to respiratory passages. Move to fresh air. If irritation persists, seek medical attention.

Swallowed: If battery contents are swallowed, do not induce vomiting. If the victim is alert, have them rinse their mouth and the surrounding skin with water for at least 15 minutes. Seek immediate medical attention.

Note: This MSDS does not include or address the small button cell batteries which can be ingested.

SECTION 5: FIRE FIGHTING MEASURES

Fire and Explosion Hazards: Batteries may burst and release hazardous decomposition products when exposed to a fire situation.

Extinguishing Media: Use any extinguishing media that is appropriate for the surrounding fire.

Special Fire Fighting Procedures: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Fight fire from a distance or protected area. Cool fire exposed batteries to prevent rupture. Use caution when handling fire-exposed containers (containers may rocket or explode in heat of fire).

Hazardous Combustion Products: Thermal degradation may produce hazardous fumes of zinc and manganese; hydrogen gas, caustic vapors of potassium hydroxide and other toxic by-products.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Notify safety personnel of large spills. Caustic potassium hydroxide may be released from leaking or ruptured batteries. Clean-up personnel should wear appropriate protective clothing to avoid eye and skin

contact and inhalation of vapors or fumes. Increase ventilation. Carefully collect batteries and place in an appropriate container for disposal.

SECTION 7: HANDLING AND STORAGE

Avoid mechanical or electrical abuse. DO NOT short circuit or install incorrectly. Batteries may explode, pyrolyze or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions. Do not mix battery systems, such as alkaline and zinc carbon, in the same equipment. Replace all batteries in equipment at the same time. Do not carry batteries loose in a pocket or bag. Do not remove battery label.

Storage: Store batteries in a dry place at normal room temperature. Do not refrigerate – this will not make them last longer.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

The following occupational exposure limits are provided for informational purposes. No exposure to the battery components should occur during normal consumer use.

| Chemical Name | Exposure Limits |
|----------------------------------|--|
| Manganese Dioxide | 5 mg/m ³ Ceiling OSHA PEL 0.2 mg/m ³ TWA ACGIH TLV |
| Zinc | None established for zinc metal |
| Potassium Hydroxide | 2 mg/m ³ Ceiling ACGIH TLV |
| Graphite (natural-non-fibrous) | 15 mppcf TWA OSHA PEL 2 mg/m ³ TWA (respirable dust) ACGIH TLV |
| Graphite (synthetic non-fibrous) | 5 mg/m ³ TWA (respirable dust), 15 mg/m ³ TWA (total dust) OSHA PEL 2 mg/m ³ TWA (respirable dust) ACGIH TLV |

Ventilation: No special ventilation is needed for normal use.

Respiratory Protection: None required for normal use.

Skin Protection: None required for normal use. Use neoprene, rubber or latex gloves when handling leaking batteries.

Eye Protection: None required for normal use. Wear safety goggles when handling leaking batteries.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Cylindrical battery.

Specific Gravity: Not applicable

Water Solubility: Insoluble

Vapor Pressure: Not applicable

Vapor Density: Not applicable

Boiling Point: Not applicable

Melting Point: Not applicable

Flash Point: Not applicable

Autoignition Point: Not applicable

SECTION 10: STABILITY AND REACTIVITY

Stability: This product is stable.

Incompatibility/Conditions to Avoid: Contents are incompatible with strong oxidizing agents. Do not heat, crush, disassemble, short circuit or recharge.

Hazardous Decomposition Products: Thermal decomposition may produce hazardous fumes of zinc and manganese; caustic vapors of potassium hydroxide and other toxic by-products.

Hazardous Polymerization: Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity Data:

Manganese Dioxide: LD50 oral rat >3478 mg/kg

Potassium Hydroxide: LD50 oral rat 273 mg/kg

Chronic Effects: The chemicals in this product are contained in a sealed can and exposure does not occur during normal handling and use. No chronic effects would be expected from handling a leaking battery.

Target Organs: Skin, eyes and respiratory system.

Carcinogenicity: None of the components of this product are listed as carcinogens by ACGIH, IARC, NTP or OSHA.

SECTION 12: ECOLOGICAL INFORMATION

No ecotoxicity data is available. This product is not expected to present an environmental hazard.

SECTION 13: DISPOSAL INFORMATION

Disposal should be in accordance with Federal, state/provincial and local regulations. Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous waste according to Federal RCRA regulations (40 CFR 261).

Alkaline batteries can be safely disposed of with normal household waste. Due to concerns about mercury in the municipal solid waste stream, Duracell has voluntarily eliminated all of the added mercury from its alkaline batteries since 1993. Individual consumers may dispose of spent (used) batteries with household trash. Duracell does not recommend that spent batteries be accumulated and disposed of in large quantities. Do not incinerate for disposal except for in a controlled incinerator.

Some communities offer recycling or collection of alkaline batteries – contact your local government for disposal practices in your area.

SECTION 14: TRANSPORT INFORMATION

Products covered by this MSDS, in their original form, are considered “dry cell” batteries and are not regulated as “DANGEROUS GOODS” for transportation.

For finished packaged product transported by ground (US DOT): – not regulated

For finished packaged product transported by sea (IMDG) – not regulated

For finished packaged product transported by air (IATA): – not regulated

SECTION 15: REGULATORY INFORMATION

United States

OSHA Status: While the finished product(s) is considered an article and not covered by the OSHA Hazard Communication Standard, 29 CFR 1910.1200, this MSDS contains valuable information critical to the safe handling and proper use of the product".

EPA TSCA Status: All intentionally-added components of this product are listed on the US TSCA Inventory.

SARA 313/302/304/311/312 chemicals: Manganese compounds 35-40%, Zinc 10-25%

California: This product has been evaluated and does not require warning labeling under California Proposition 65.

State Right-to-Know and CERCLA:

The following ingredients present in the finished product are listed on state right-to-know lists or state worker exposure lists

| Ingredient | CAS # | Level | CERCLA RQ | State | | | | |
|---------------------|------------------------|--------|--------------|-------|----|----|----|----|
| | | | | IL | MA | NJ | PA | RI |
| Manganese Dioxide | 1313-13-9 | 35-40% | None | Y | Y | N | Y | Y |
| Zinc | 7440-66-6 | 10-25% | 1000 lb | Y | Y | Y | Y | N |
| Potassium Hydroxide | 1310-58-3 | 5-10% | 1000 lb | Y | Y | Y | Y | Y |
| Graphite | 7782-42-5 7440-44-0 | 1-5% | None | Y | Y | N | Y | Y |

Canada All intentionally-added components of this product are listed on the Canadian DSL. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and this MSDS contains all information required by the Controlled Products Regulations.

SECTION 16: OTHER INFORMATION

P&G Hazard Rating: Health: 0 Fire: 0 Reactivity: 0

=====
Data supplied is for use only in connection with occupational safety and health.

DISCLAIMER: This MSDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by Procter & Gamble to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. Procter & Gamble assumed no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.