

31302+31310

U.S. DEPARTMENT OF LABOR  
Occupational Safety and Health Administration

Form Approved  
OMB No. 44-R1387

# MATERIAL SAFETY DATA SHEET

PG

Required under USDL Safety and Health Regulations for Ship Repairing,  
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I	
MANUFACTURER'S NAME <b>Kimberly-Clark Corporation</b>	EMERGENCY TELEPHONE NO. <b>(404) 441-8000</b>
ADDRESS (Number, Street, City, State, and ZIP Code) <b>1400 Holcomb Bridge Rd. Roswell, GA. 30076</b>	
CHEMICAL NAME AND SYNONYMS <b>Scrim Reinforced Cellulose Wiper</b>	TRADE NAME AND SYNONYMS <b>Numerous</b>
CHEMICAL FAMILY <b>Cellulose</b>	FORMULA <b>Not Applicable</b>

SECTION II - HAZARDOUS INGREDIENTS					
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
NOT HAZARDOUS-Consists of Cellulosic Wood Fiber				92.6	
Nylon Yarn				1.4	
Adhesive (polyvinyl chloride and/or latex based resin)				6.0	
Dyes				Less than 0.1	

31302, 31310

SECTION III - PHYSICAL DATA			
BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H <sub>2</sub> O=1)	N/A
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ =1)	N/A
SOLUBILITY IN WATER	N/A		
APPEARANCE AND ODOR <b>White or dyed as advertised essentially odor free</b>			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA			
FLASH POINT (Method used) <b>N/A</b>	FLAMMABLE LIMITS <b>N/A</b>	Lel	Uel
EXTINGUISHING MEDIA <b>Water</b>			
SPECIAL FIRE FIGHTING PROCEDURES <b>None required</b>			
UNUSUAL FIRE AND EXPLOSION HAZARDS <b>None</b>			

SECTION V - HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE	N/A
EFFECTS OF OVEREXPOSURE	N/A
EMERGENCY AND FIRST AID PROCEDURES	N/A

SECTION VI - REACTIVITY DATA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY <i>(Materials to avoid)</i> Oxidizing agents			
HAZARDOUS DECOMPOSITION PRODUCTS Comparable to all paper products			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID Ignition sources and temperature
	WILL NOT OCCUR	X	Over 400° F

SECTION VII - SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED None	
WASTE DISPOSAL METHOD Normal incineration or land fills	

SECTION VIII - SPECIAL PROTECTION INFORMATION			
RESPIRATORY PROTECTION <i>(Specify type)</i>			
VENTILATION None	LOCAL EXHAUST		SPECIAL
	MECHANICAL <i>(General)</i>		OTHER
PROTECTIVE GLOVES	N/A	EYE PROTECTION	N/A
OTHER PROTECTIVE EQUIPMENT N/A			

SECTION IX - SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Keep Dry	
OTHER PRECAUTIONS Routine Plant Sanitation	