

#31778 & 31779



ENVIRO CARE

Tech 4 Wood Floor Seal/Finish

Product Safety Information Sheet (MSDS)

This Product Safety Information Sheet is principally directed to managerial, safety, hygiene and medical personnel. The description of physical, chemical and toxicological properties and handling advice is based on experimental results and anticipated exposure.

This Product Safety Information Sheet meets the material safety data sheet (MSDS) requirements of the federal OSHA Hazard Communication Standard (29 CFR 1910.1200).

<u>NFPA 704 Rating</u>	
Health	1
Flammability	0
Reactivity	0

<u>Key</u>
0 = Minimal
1 = Slight
2 = Moderate
3 = High
4 = Extreme

31778

I. INGREDIENTS

N-Methyl pyrrolidone	5-10%
CAS Reg. No. 872-50-4	TLV 100 ppm
Methyl ethyl ketone	1-5%
CAS Reg. No. 78-93-3	TLV 200 ppm
Triethylamine	1-5%
CAS Reg. No. 121-44-8	TLV 10 ppm
Ethylene glycol	1-5%
CAS Reg. No. 107-21-1	TLV 50 ppm

II. PHYSICAL PROPERTIES

Appearance: Enviro Care Tech 4 Wood Floor Seal/Finish is a free-flowing, white opaque liquid with a mild odor.

Boiling Point: 175° F.

Specific Gravity: 1.045 (8.7 lbs/gallon)

pH: 9.0

Percent Volatile: 75

Solubility in Water: Complete

Corporate Headquarters
 1015 North 14th Street
 Omaha, Nebraska 68102
 (402) 342-4248
 (800) 877-7200
 FAX 1-402-342-3706

III. FIRE HAZARD

Enviro Care Tech 4 Wood Floor Seal/Finish is not considered a fire hazard, nor will it support combustion.

Use standard firefighting techniques to extinguish fires involving this material (water spray, dry chemicals or foam).

IV. REACTIVITY DATA

Enviro Care Tech 4 Wood Floor Seal/Finish is stable and non-reactive.

V. HEALTH HAZARD DATA

The principal route of exposure to Enviro Care Tech 4 Wood Floor Seal/Finish is skin contact. Skin or eye contact may cause irritation. Inhalation of mist or vapor may irritate upper respiratory tract. May be harmful if swallowed.

Enviro Care Tech 4 Wood Floor Seal/Finish is not listed as a carcinogen by NTP, IARC or OSHA.

VI. FIRST AID

For eye contact, flush with clear water for 15 minutes. For skin contact, wash with soap and water. For respiratory irritation, remove to fresh air. If swallowed, or if any irritation persists, consult a physician.

VII. PRECAUTIONS FOR SAFE HANDLING AND USE

Keep out of reach of children. Avoid eye and prolonged skin contact. Use with adequate ventilation.

VIII. SPILL HANDLING

If Enviro Care Tech 4 Wood Floor Seal/Finish is spilled, recover liquid with wet mop or wet/dry vacuum. Flush residue to sewer with water. Use care, as floor may become slippery.

IX. SPECIAL PROTECTION INFORMATION

Protective equipment is not normally required. If desired, rubber, neoprene or vinyl gloves may be used to minimize skin contact. Splashproof chemical safety goggles may be used to eliminate the possibility of eye contact.

New Issue: 2/90