

MATERIAL SAFETY DATA SHEET
(Complies with OSHA Communication Standard 29CFR 1910.1200 Dept. of Labor.)

Item # 34348 page 1

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

TM4099 Gum Remover

Revision Date: 9/8/99

MANUFACTURER/SUPPLIER'S/NAME:

Hi-Port Aerosol, 9150 Valley View Road, Macedonia, OH 44056 - (330) 467-4195

COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT CAS REG NO. UNITS	COMPOSITION/ WGT. %	ACGIH TLV		OSHA PEL	
		TWA	STEL	TWA	STEL
Isobutane 75-28-5	90-100	na	na	na	na
n-Hexane 110-54-3	1-10	50	na	500	na ppm

Additional Component Information:
NA

HAZARDS IDENTIFICATION

HEALTH HAZARD DATA (ACUTE AND CHRONIC)

May cause dizziness or narcosis in high vapor concentrations. Will cause defatting of skin. Effects are reversible. Long term exposure (years) to high concentrations of vapor may cause lung, liver or kidney damage. The solvents listed have been reported to affect the central nervous system. Aspiration hazard if swallowed. Eye and skin irritant. May irritate respiratory tract. Deliberately concentrating and inhaling the vapor of the contents may be harmful or fatal.

OTHER:

May cause cardiac abnormalities. Liquid contact may cause frostbite. n-Hexane may damage peripheral nerve tissue.

CARCINOGENICITY:

NA

FIRST AID

Give oxygen. Do not induce vomiting. Wash eyes and skin with water for 15 minutes. Get medical help. Never administer adrenalin following overexposure. Treat for frostbite.

ROUTES OF ENTRY

Ingestion Inhalation Skin

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Inhalation - Difficulty in breathing. Skin - redness. Ingestion - vomiting.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Heart Disease. Respiratory conditions.

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	-11.7F to 159F
Vapor Pressure at 70F	52
VAPOR DENSITY (AIR=1)	4.0
EVAP. RATE(BUTYL ACETATE=1)	>1
SPECIFIC GRAVITY (WATER=1)	0.5
Solubility	Nil
Appearance	Clear
Odor	Solvent

34348

PH: Not Applicable

STABILITY AND REACTIVITY

STABILITY: STABLE
INCOMPATIBILITY:- Strong oxidizers
HAZARDOUS THERMAL DECOMPOSITION/COMBUSTION PRODUCTS:- Carbon dioxide.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65:

NONE

Ozone Depleting Substances:

None

HMIS:

FLAMMABILITY 4, REACTIVITY 0, HEALTH 2

NFPA:

FLAMMABILITY 4, REACTIVITY 0, HEALTH 1

SARA 313 TITLE III - TOXIC CHEMICALS LIST:

n-Hexane (CAS 110-54-3)

DOT Shipping Name:

Consumer Commodity, ORM-D

CONTROL MEASURES

Respiratory Protection Equipment

Use NIOSH approved respirator if TLV limit is exceeded.

VENTILATION:

Local exhaust - yes

PROTECTIVE GLOVES:

None required if spraying.

EYE AND FACE PROTECTION:

Safety glasses.

OTHER PROTECTIVE EQUIPMENT:

Long pants Long sleeves

SAFE HANDLING

Do not smoke while using. Wash hands after use.

PRECAUTIONS FOR SAFE HANDLING AND USE

Flash Point -160F T C C

LOWER EXPLOSION LIMIT : 1.9

UPPER EXPLOSION LIMIT : 8.5

EXTINGUISHING MEDIA:- Water fog, carbon dioxide, foam, dry chemical

UNUSUAL FIRE AND EXPLOSION HAZARDS:- Heated cans may burst.

SPECIAL FIRE FIGHTING PROCEDURES Keep containers cool. Use equipment or shielding required to protect against bursting or venting containers.

SPILL PROCEDURES: Use absorbent sweeping compound to soak up material. Put into container. Dispose as hazardous waste.

WASTE DISPOSAL METHODS: Dispose as hazardous waste in accordance with EPA RCRA.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep away from heat, sparks, or open flame. Store at temperatures below 120F.

OTHER INFORMATION: When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.

NFPA 30B Level:

3