

Pg 1

MATERIAL SAFETY DATA SHEET

DAP INC.  
P.O. BOX 277  
DAYTON, OH 45401-0277

#35580; 35582

MSDS NO: DAP / 10401  
INTERNAL ID: 10401  
DAP '33' GLAZING  
REVISION: 3  
DATE: FEBRUARY 3, 1992

NATIONAL PAINT  
AND COATINGS  
ASSOCIATION  
  
HAZARDOUS MATERIAL  
IDENTIFICATION  
SYSTEM

HEALTH HAZARD	0 - MINIMAL
FLAMMABILITY HAZARD	0 - MINIMAL
REACTIVITY HAZARD	0 - MINIMAL
PERSONAL PROTECTION	B - GLASSES, GLOVES

SECTION I. MATERIAL IDENTIFICATION

TRADE/MATERIAL NAME: DAP '33' GLAZING  
DESCRIPTION: GLAZING COMPOUND  
FORM: MIXTURE  
PREVIOUS MSDS REVISION DATE: FEBRUARY 28, 1991

SHIPPING NAME (49 CFR 172.101): NA  
DOT HAZARD CLASS (49 CFR 172.101): NA  
DOT ID NO. (49 CFR 172.101): NA  
DOT LABEL REQUIRED (49 CFR 172.101): NA  
HAZARD CLASS - IF DISCARDED (40 CFR 261): NA

MANUFACTURER: DAP INC.  
P.O. BOX 277  
DAYTON, OH 45401

PHONE: 1-800-543-3840  
IN OHIO:  
1-513-667-4461

35580, 35582

SECTION II. INGREDIENTS AND HAZARDS

INGREDIENT NAME: PERCENT: EXPOSURE LIMITS:  
ALL INGREDIENTS ARE NOT REGULATED BY OSHA AND ARE CONSIDERED TRADE SECRETS.

SECTION III. PHYSICAL DATA

APPEARANCE & ODOR: COLORED PASTE WITH A MILD ODOR.

BOILING POINT: NA  
VAPOR PRESSURE: < 1MM HG @ 20C  
WATER SOLUBILITY (%): NEGLIGIBLE  
VAPOR DENSITY (AIR=1): > 1

EVAPORATION RATE: (N-BUTYL  
ACETATE=1): <1  
SPECIFIC GRAVITY (H2O=1): 2.2  
% VOLATILE BY VOLUME: < 1

OC LESS WATER LESS EXEMPT SOLVENT: 10 G/LITER  
OC MATERIAL: 10 G/LITER

35580

Pg 2

MATERIAL SAFETY DATA SHEET

DAP INC.  
P.O. BOX 277  
DAYTON, OH 45401-0277

MSDS NO: DAP / 10401  
INTERNAL ID: 10401  
DAP '33' GLAZING  
REVISION: 3  
DATE: FEBRUARY 3, 1992

-----  
SECTION IV. FIRE AND EXPLOSION DATA  
-----

FLASH POINT (METHOD): >200F (SETA)      LIMITS: LEL %: NE      UEL %: NE  
EXTINGUISHING MEDIA: FOAM, WATER, DRY CHEMICALS  
UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE KNOWN  
SPECIAL FIRE-FIGHTING PROCEDURES: USE WATER SPRAY TO COOL EXPOSED SURFACES.

-----  
SECTION V. REACTIVITY DATA  
-----

MATERIAL IS STABLE. HAZARDOUS POLYMERIZATION WILL NOT OCCUR.  
CHEMICAL INCOMPATIBILITIES: STRONG OXIDIZERS AND CAUSTICS.  
CONDITIONS TO AVOID: EXCESSIVE HEAT AND FREEZING.  
HAZARDOUS DECOMPOSITION PRODUCTS: NORMAL COMBUSTION PRODUCTS, I.E. COX, NOX.

-----  
SECTION VI. HEALTH HAZARD INFORMATION  
-----

THIS PRODUCT IS NOT CONSIDERED A CARCINOGEN BY THE NTP, IARC, OR OSHA.  
SPECIAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: NONE KNOWN  
PRIMARY ENTRY ROUTE(S): SKIN CONTACT  
ACUTE EFFECTS: NONE KNOWN  
CHRONIC EFFECT(S): NONE KNOWN  
FIRST AID:  
EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES.  
CONTACT A PHYSICIAN.  
SKIN CONTACT: WASH WITH SOAP AND WATER.  
INHALATION: REMOVE TO FRESH AIR. CONTACT A PHYSICIAN IMMEDIATELY.  
INGESTION: DO NOT INDUCE VOMITING. CONTACT A PHYSICIAN OR  
REGIONAL POISON CONTROL CENTER IMMEDIATELY.

