



#35620-35626

1

GE Plastics-Structured Product

### MATERIAL SAFETY DATA SHEET

PRODUCT 9034

01/01/94 PAGE 01/04

## 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

\*\* THIS MSDS IS APPLICABLE FOR ALL COLORS AND PID NUMBERS OF THIS PRODUCT \*\*

#### MANUFACTURER / SUPPLIER

General Electric Company  
One Plastics Avenue  
Pittsfield, MA 01201

GE Plastics Canada, Ltd.  
2300 Meadowvale Blvd.  
Mississauga, ONT L5N 5P9

#### EMERGENCY TELEPHONE

(800) 447-4545 (24 hour)  
(812) 831-7444 (24 hour)

Medical  
Other

(800) 447-4545 (24 hour)  
(812) 831-7444 (24 hour)

#### NON-EMERGENCY TELEPHONE

(800) 451-3147 or (800) 323-3783

#### PRODUCT IDENTIFIER:

LEXAN sheet or film.

#### PRODUCT DESCRIPTION:

Poly(bisphenol-A carbonate) (CAS#111211-39-3).

#### PRODUCT USE:

May be used as received, processed to produce other articles, or as a component of other industrial products.

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

This product consists primarily of high molecular weight polymers which are not expected to be hazardous.

This product is not subject to the OSHA Hazard Communication Standard (29CFR1910.1200). Information on this form is being provided as a service to our customers.

## 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW:

Plastic film or sheet. Can burn in a fire creating dense, toxic smoke. Molten plastic can cause severe burns. Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Secondary operations, such as grinding, sanding or sawing can produce dust which may present an explosion hazard.

#### POTENTIAL HEALTH EFFECTS

##### EYE:

Dust and small particles may cause irritation due to mechanical action.

##### SKIN:

Dust and small particles may cause irritation due to mechanical action.

##### INGESTION:

Not acutely toxic.

##### INHALATION:

Inhalation of product is unlikely due to physical form.

#### CHRONIC/CARCINOGENICITY

##### NTP:

Not Tested

##### OSHA:

Not Regulated

##### IARC:

Not Listed

#### THERMAL PROCESSING HAZARDS:

Hot or molten plastic can cause severe burns.

Processing fumes may cause irritation to the eyes, skin and respiratory tract, and in cases of severe over-exposure, nausea and headache.

Grease-like processing fume condensates on ventilation duct work, molds and other surfaces can cause irritation and injury to skin.

#### MEDICAL RESTRICTIONS:

There are no known human health effects aggravated by exposure to this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing fumes.

#### NOTE:

Additives containing certain heavy metal

35620-35626

compounds may be present. These ingredients are essentially bound in the plastic matrix and are unlikely to contribute to workplace exposure under normal conditions of use.

#### 4. FIRST AID MEASURES

**EYES:** Remove contact lenses at once. Immediately flush eyes well with copious quantities of water or normal saline for at least 20-30 minutes. Seek medical attention.

**SKIN:** Wash skin thoroughly with soap and water. Seek medical attention if rash or burn occurs.

**INGESTION:** Not probable. If a large amount is swallowed, seek medical attention.

**INHALATION:** Not likely to be inhaled due to physical form.

**THERMAL PROCESSING:** For molten plastic skin contact, cool rapidly with water and immediately seek medical attention. Do not attempt removal of plastic without medical assistance. Do not use solvent for removal.

For processing fume inhalation irritation, leave contaminated area and breathe fresh air. If coughing, difficult breathing or any other symptoms develop seek medical attention at once, even if symptoms develop at a later time.

For skin contact with fume condensate, immediately wash thoroughly with soap and water. If irritation develops seek medical attention.

#### 5. FIRE FIGHTING MEASURES

**FIRE FIGHTING:** Approved pressure demand breathing apparatus and protective clothing should be used for all fires. Water spray is the preferred extinguishing medium. This product will melt but will not be carried on the surface of water.

**EXTINGUISHING MEDIA:** Water spray and foam. Water is the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition.

**HAZARDOUS COMBUSTION PRODUCTS:** Hazardous combustion products may include intense heat, dense black smoke, carbon monoxide, carbon dioxide and hydrocarbon fragments.

**FLASH POINT:** Not Applicable

**LOWER FLAMMABLE LIMIT:** Not Established

**UPPER FLAMMABLE LIMIT:** Not Established

**AUTOIGNITION:** 630 C (1166 F), estimated

**CONDITIONS OF FLAMMABILITY:** Requires a continuous flame source to ignite.

**EXPLOSION DATA**

**IMPACT SENSITIVITY:** Not sensitive to mechanical impact.

**STATIC DISCHARGE:** Not sensitive to static discharge.  
(See HANDLING AND STORAGE)

#### 6. ACCIDENTAL RELEASE MEASURES

**GENERAL:** Sweep or gather up material and place in proper container for disposal or recovery. (See DISPOSAL INFORMATION)

#### 7. HANDLING AND STORAGE

**HANDLING:** Use good industrial hygiene practices. Provide adequate ventilation. Secondary operations such as grinding, sanding or sawing may produce a dust explosion hazard. Use aggressive housekeeping activities to prevent dust accumulation; employ bonding, grounding, venting and explosion relief provisions in accordance with accepted engineering practices.

**STORAGE:** Store in a dry place away from moisture, excessive heat and sources of ignition.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** When thermally processing this product, a continuous supply of fresh air to the workplace, together with the removal of processing fumes through exhaust systems is recommended. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, ductwork, and other surfaces using appropriate personal protection. For powders and residual dusts, refer to HANDLING AND STORAGE section.

Ventilation requirements must be locally determined to limit exposure to processing fumes in the workplace. Design techniques and guidelines may be found in publications such as:

P3

Industrial Ventilation; available from the American Conference of Governmental Industrial Hygienists, Committee on Industrial Ventilation, P.O. Box 16153, Lansing, MI 48901.

**PERSONAL PROTECTION**

**EYE/FACE:**

Wear safety glasses with side shields or chemical goggles. In addition, use full face shield when cleaning processing fume condensates from hoods, ducts and other surfaces.

**SKIN:**

When thermally processing product, wear long pants, long sleeves, well insulated gloves and face shield when applicable. Use appropriate protective clothing, including chemical resistant gloves, to prevent any contact with processing fume condensates.

**RESPIRATORY:**

When processing fumes are not adequately controlled, use respirator approved for protection from organic vapors and acid gases. When dust or powder from secondary operations, such as grinding sanding or sawing, are not adequately controlled use respirator approved for protection from dust.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>PHYSICAL STATE:</b>	Solid
<b>ODOR AND APPEARANCE:</b>	Plastic sheet or film with slight or no odor.
<b>BOILING POINT:</b>	Not Applicable
<b>MELTING POINT:</b>	See COMMENT below.
<b>VAPOR PRESSURE (mmHg):</b>	Not Applicable
<b>VAPOR DENSITY (air=1):</b>	Not Applicable
<b>SPECIFIC GRAVITY (water=1):</b>	>1
<b>WATER SOLUBILITY:</b>	Insoluble
<b>% VOLATILES:</b>	Negligible
<b>pH:</b>	Not Applicable
<b>ODOR THRESHOLD:</b>	Not Established
<b>EVAPORATION RATE:</b>	Not Applicable
<b>COEFFICIENT WATER/OIL DISTR:</b>	Not Established
<b>COMMENT:</b>	This product does not exhibit a sharp melting point, but softens gradually over a wide temperature range.

**10. STABILITY AND REACTIVITY**

<b>STABILITY:</b>	Stable under recommended conditions of storage and handling.
<b>REACTIVITY:</b>	Not reactive under recommended conditions of handling, storage, processing and use.
<b>CONDITIONS TO AVOID:</b>	Do not exceed melt temperature recommendations in product literature. See EXPOSURE CONTROLS/PERSONAL PROTECTION section for respiratory protection advice.
<b>HAZARDOUS DECOMPOSITION:</b>	Processing fumes evolved at recommended processing conditions may include trace levels of phenol, alkylphenols, and diarylcarbonates.

**11. TOXICOLOGICAL INFORMATION**

**PRODUCT:**

**EYE:** Product not considered primary eye irritant. When similar products, in finely divided form, were placed into the eyes of rabbits, slight transient redness or discharge occurred - consistent with the expected slightly abrasive nature of the resin particles.

**SKIN:** Product not considered primary skin irritant. Draize Skin Primary Irritation Score (rabbit) for similar products, in finely divided form, for a 24-hour exposure is 0. Not expected to be a skin sensitizer based on results of Modified Buehler Guinea Pig Sensitization Test from similar products. Dermal LD50 (rabbit) > 2g/kg, estimated.

**ACUTE ORAL:** Oral LD50 (Rat) >5 g/kg, estimated.

**ACUTE INHALATION:** Processing fumes from similar products are not considered toxic. In acute inhalation tests, laboratory rats were exposed to processing fumes at concentrations exaggerating those that would likely occur in workplace situations. No deaths or signs of toxicity, except transient irritancy in some cases, were noted during the 6 hour fume exposure tests. There were no distinct or consistent treatment related tissue or organ changes noted in gross necropsies.

12. ECOLOGICAL INFORMATION p.4.**GENERAL:**

Not expected to present any significant ecological problems.

## 13. DISPOSAL INFORMATION

**RCRA HAZARDOUS WASTE:**

Product is not a RCRA hazardous waste.

**WASTE DISPOSAL:**

Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification.

## 14. TRANSPORTATION INFORMATION

**DOT HAZARD CLASS:**

Not Regulated

**PROPER SHIPPING NAME:**

Not Regulated

**IDENTIFICATION NUMBER:**

Not Listed

**TDGA:**

Not Listed

## 15. REGULATORY INFORMATION

The products covered by this MSDS are articles as defined by 29CFR Part 1910.1200 (c) and Section 313, Title III of SARA (Emergency Planning and Community Right-to-Know Act), and therefore are exempt from notification requirements.

**TSCA STATUS:**

This product complies with the Chemical Substance Inventory requirements of the US EPA Toxic Substances Control Act (TSCA).

**WHMIS CLASSIFICATION:**

Not a controlled product.

## 16. OTHER

**PREPARED BY:**

Product Compliance

The above information and recommendations are believed accurate and reliable. Because it is not possible to anticipate all conditions of use additional safety precautions may be required. GENERAL ELECTRIC COMPANY makes no warranty, either express or implied, including merchantability and fitness. **USER RESPONSIBILITY:** Each user should read and understand this information and incorporate it into individual site safety programs in accordance with applicable hazard communication standards and regulations.

LEXAN is a registered trademark of the GENERAL ELECTRIC COMPANY or its affiliates.

REVISIONS IN THIS MSDS SINCE YOUR LAST ORDER ARE IN THE FOLLOWING SECTION(S):

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION
16. OTHER