

#82573-82619

MATERIAL SAFETY DATA SHEET

Pg. 1
NPCA 1

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

DATE OF PREP 5/6/86

Section I

MANUFACTURER'S NAME Hunt Manufacturing Company

STREET ADDRESS Speedball Road CITY, STATE, AND ZIP CODE Statesville, NC 28677

EMERGENCY TELEPHONE NO 704-872-9511

PRODUCT CLASS Watercolor MANUFACTURERS CODE IDENTIFICATION 5700 to 5740

TRADE NAME SPEEDBALL Professional Watercolours

82573, 82575, 82577, 82579, 82581, 82584, 82585, 82619

Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV		LEL	VAPOR PRESS
		PPM	mg/m ³		
As per ASIM D4236 and as per the Art and Craft Materials Institute, Inc. (ACMI), all of the SPEEDBALL Professional Watercolours have been certified non-toxic.					
Under current OSHA criteria this material is considered to be non-hazardous.					

Section III - PHYSICAL DATA

BOILING RANGE 212-554°F. VAPOR DENSITY HEAVIER. LIGHTER THAN AIR

EVAPORATION RATE FASTER SLOWER THAN ETHER PERCENT VOLATILE BY VOLUME 49 - 57% WEIGHT PER GALLON 10.0 - 15.7#

Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY Not restricted FLASH POINT 375°F./191°C LEL/N/A

EXTINGUISHING MEDIA Alcohol foam, water fog, carbon dioxide or dry chemical

UNUSUAL FIRE AND EXPLOSION HAZARDS Material may spatter if temperature exceeds boiling point. Decomposition may form toxic materials; i.e., carbon dioxide, carbon monoxide, various hydrocarbons, acrolein, etc.

SPECIAL FIRE FIGHTING PROCEDURES Wear self-contained breathing apparatus.

Section V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE N/A
EFFECTS OF OVEREXPOSURE None expected.

EMERGENCY AND FIRST AID PROCEDURES Eye & Skin: Flush with water.

Section VI - REACTIVITY DATA

STABILITY UNSTABLE STABLE CONDITIONS TO AVOID N/A
INCOMPATIBILITY (Materials to avoid) Avoid contact with strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS See Section IV

HAZARDOUS POLYMERIZATION MAY OCCUR WILL NOT OCCUR
CONDITIONS TO AVOID N/A

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Mop up or absorb on inert material and place into containers. May be slippery; will leave a film on drying.

WASTE DISPOSAL METHOD Landfill according to Federal, State and local regulations.

Section VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION Not required under normal conditions of use.

VENTILATION Adequate ventilation recommended.

PROTECTIVE GLOVES Impermeable gloves suggested.

EYE PROTECTION NA

OTHER PROTECTIVE EQUIPMENT NA

Section IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Keep from freezing - product may coagulate.

OTHER PRECAUTIONS N/A