

Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
Consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

Identity (As used on Label and List) Orton Pyrometric Cones / Bars / TempCheks / Cone Plaques labeled P9000 S-4 50, P9000 L-3 50, P9000 L-4 50 Cone boxes are labeled as SSB, LRB, SRB, PCB or BRB followed by the identification number	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
---	---

Section 1 – Product Identification

Manufacturer's Name The Edward Orton Jr. Ceramic Foundation	Emergency Telephone Number (614) 895-2663
Address (Number, Street, City, State, & Zip Code) 6991 Old 3C Highway, P.O. Box 2760, Westerville OH 43086 – 2760	Telephone Number for Information (614) 895-2663
Date Prepared 8/8/22	Signature of Preparer (Optional)

Section 2 – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	(%) (Optional)
Cone Plaques, Tempchek, Pyrometric Cone and Bar Numbers				
022, 021, 020, 019, 018, 017, 016, 015, 014, 013,				
012, 011, 010, 09, 08, 07, 06, 05½, 05, 04, 03, 02,				
01, 1, 2, 3, 4, 5, 5½, 6, 7, 8, 9, 10, 11, 12, 12½, 13,				
13½, 14, 14½, 15, 15½, 16, 17, 18, 19, 20, 21, 23,				
26, 27, 28, 29, 30, 31, 31½, 32, 32½, 33, 34, 35, 36				
37, 38, 39, 40, 41 (Contain 2-65% Silica)				
Silica as dust	10 mg/m ³	0.025mg/m ³ TWA (respirable dust)		



DANGER

May cause cancer by inhalation.

Causes Damage to lungs through prolonged or repeated exposure by inhalation.

Response:

If exposed or concerned: get medical advice

Disposal:

Dispose of contents/containers in accordance with local regulation

Prevention

Do not eat, drink, or smoke when using this product

Do not breath dust

Section 3 – Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H₂O = 1)	1.8 – 2.0
Vapor Pressure (mmHg)	N/A	Melting Point	N/A
Vapor Density (Air = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water			
Nil			
Appearance and Color			
Solid-Shape of pyramid or rectangular shape – some products contain organic colors for aid in identification			

Section 4 – Fire And Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
N/A	N/A	N/A	N/A
Extinguishing Media			
N/A			
Special Fire Fighting Procedures			
All products except those labeled PCB contain 4-6% organic material that will combust above 300°F			
Unusual Fire and Explosion Hazards			
N/A			

Section 5 – Reactivity Data

Stability	Unstable		Conditions to Avoid -None
	Stable	X	
Incompatibility (Materials to Avoid)			
N/A			
Hazardous Decomposition or Byproducts			
N/A			
Hazardous Polymerization	May Occur		Conditions to Avoid - none
	Will not Occur	X	

Section 6 – Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	N/A	None Anticipated	None Anticipated
Health Hazards (Acute and Chronic)			
Product is non-hazardous when used as intended. Product should not be ground into dust or ingested.			
Product may contain crystalline silica, which may cause cancer, when inhaled, based on animal testing.			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No
Signs and Symptoms of Exposure			
N/A			
Medical Conditions Generally Aggravated by Exposure			
N/A			
Emergency and First Aid Procedures			
If swallowed, get professional medical help			

Section 7 – Precautions for Safe Handling and Use

Steps to be taken in Case Material is Released or Spilled

No specific precautions

Waste Disposal Method

Disposal must meet existing federal, state, and local environmental control for low soluble glass frit - titanium dioxide – silica

Precautions to Be Taken in Handling and Storing

Keep out of reach of children. Wash hands after handling.

Other Precautions

Organic components may produce harmful gases during firing, if not fully oxidized. Also other gases may be produced during firing, therefore, provide adequate ventilation to kiln or kiln area.

Section 8 – Control Measures

Respiratory Protection (Specify Type)

N/A

Ventilation	Local Exhaust N/A	Special N/A
	Mechanical (General) N/A	Other N/A
Protective Gloves N/A	Eye Protection N/A	
Other Protective Clothing or Equipment No special requirements		
Work/Hygienic Practices Wash hands after handling		

Section 9 - Physical and Chemical Properties

Appearance: Pyrometric Cones are three sided elongated pyramids 1” to 2” long. Cone plaques are rectangular clay forms ranging in Length, width, and height between 3”-4”x1”x1/2” . TempChek are ceramic disks 1 1/8” in diameter by 1/4” thick.

Odor: none

Vapor Pressure: none

PH: neutral

Melting point: above 1000°F

Freezing point: none

Flammability: none

Section 10 – Stability and Reactivity

Reactivity: None

Chemical Stability: Stable

Section 11 – Toxicological Information

Not toxic

Section 12 – Ecological Information

None available

Section 13 – Disposal Considerations

No precautions known

Section 14 – Transport Information

Non-hazardous

Section 15 – Regulatory Information



California Proposition 65: Crystalline silica (airborne particles of respirable size) is classified as a substance known to the state of California to be a carcinogen

Section 16 – Other Information

Rev 8/8/22

Product resources found at www.ortonceramic.com