

82876-87764

Pg 1

MATERIAL SAFETY DATA SHEET



IDENTITY <i>Sand Paper</i> COATED ABRASIVES "ALUMINUM OXIDE"	TRADE NAME G-88
--	--------------------

SECTION I (MATERIAL IDENTIFICATION)

MANUFACTURER'S NAME Fábrica Nacional de Lija, S.A de C.V.	EMERGENCY TELEPHONE NUMBER 011 525 6251403
ADDRESS (Street, Number, City, State, ZIP Code) Av. Presidente Juárez # 225 San Jerónimo Tepetlacalco Tlalnepantla 54000 Estado de México MEXICO	TELEPHONE & FAX NUMBER FOR INFORMATION 011 525 625 1400 fax 011 525 625 1499
	REVISION DATE April 1997
	PREPARED BY (Technical contact) Alfredo Bañuelos or José Jiménez

SECTION II (MATERIAL DESCRIPTION & HAZARD RATING)

TECHNICAL DESCRIPTION: Aluminum Oxide coated on a fibre backing and resin binder.	HAZARD RATING: 1, 0, 0	NFPA CODE
CHEMICAL FAMILY NA		0: Minimum
CHEMICAL NAME/FORMULA NA		1: Slight
SYNONYMOUS NA		2: Moderate
		3: Serious
		4: Extreme

SECTION III (HAZARDOUS INGREDIENTS/IDENTITY INFORMATION)

HAZARDOUS COMPONENTS					
Chemical name	CAS No.	Common name (s)	Percent	OSHA - PEL (mg/m3)	ACGIH-TLV (mg/m3)
Aluminum Oxide (Al2O3)	1344 - 28 - 1	Alpha Alumina	15 - 45	15.0 (total dust)	10.0 (total dust)
Phenol-Formaldehyde resin "cured"	NONE	Phenolic Resin	12 - 30	-----	-----
Calcium Fluoride (CaF2)	14542 - 23 - 5	Fluorspar	1 - 5	5.3 (total dust)	5.3 (total dust)
Vulcanized Fibre	NONE	Fibre Backing	30 - 70	-----	-----

REMARKS
 The above materials are not carcinogen.
 Materials are regulated by OSHA 29 CFR 1910.1200, Hazard Communication and/or The Massachusetts General Law, Chapter III, Right to know Regulations

SECTION IV (PHYSICAL & CHEMICAL CHARACTERISTICS)

BOILING POINT NA	SOLUBILITY IN WATER NA	SPECIFIC GRAVITY (H2O=1) NA
VAPOR PRESSURE NA	SOLUBILITY IN ALCOHOL NA	MELTING POINT NA
VAPOR DENSITY (Air = 1) NA	SOLUBILITY IN OTHER SOLVENT NA	% VOLATILE BY VOLUME NA
APPEARANCE & ODOR Cloth coated with abrasive particles which are bonedd with resin binder.		EVAPORATION RATE NA

SECTION V (FIRE & EXPLOSION HAZARD DATA)

FLASH POINT (Method used) NA	FLAMMABLE LIMITS	LEL NA	UEL NA
EXTINGUISHED MEDIA Water, carbon dioxide, Dry chemical, Foam			
SPECIAL FIRE FIGHTING PROCEDURES Backings and cured resin will burn or decompose. Use respiratory protection.			
UNUSUAL FIRE & EXPLOSION HAZARDS NA			

82876-87764

SECTION VI (REACTIVITY DATA)

STABILITY	UNSTABLE		CONDITIONS TO AVOID	NA
	STABLE	X		
INCOMPATIBILITY (Materials to Avoid) In use organic fumes may be liberated.				
HAZARDOUS DECOMPOSITION OR BY PRODUCTS				
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID	NA
	WILL NOT OCCUR	X		

SECTION VII (HEALTH HAZARD DATA)

ROUTE (s) OF ENTRY During use	INHALATION? Airborne dusts or fumes.	SKIN? Airborne dusts or fumes.	INGESTION? Airborne dusts or fumes.
HEALTH HAZARDS (Acute & chronic) Innertal bleeding or tissue damage. CHRONIC: exposure to organic fumes (fluoride) has been reported to cause osteoclorosis, mottling of tooth enamel and damage to skin, eye and mucous membranes.			
CARCINOGENICITY	NTP? NA	IARC MONOGRAPHS? NA	OSHA REGULATED? NA
SIGNS & SYMPTOMS OF EXPOSURE Deposits or material on skin, in eyes and nasal passages. Coughing and/or breathing difficulties may be present.			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Pulmonary disorders, skin or eye disorders.			
EMERGENCY & FIRST AID PROCEDURES Remove to dust free area. Irrigate eyes and/or skin with copious amounts of water. SEEK MEDICAL ATTENTION.			

SECTION VIII (PRECAUTIONS FOR SAFE HANDLING & USE)

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Ordinary precautions for dust and particulates.	
WASTE DISPOSAL METHOD In compliance with Federal, State and local regulations for landfill.	
PRECAUTIONS TO BE TAKEN IN HANDLING & STORING Not applicable	
OTHER PRECAUTIONS Not applicable	

SECTION IX (CONTROL MEASURES)

RESPIRATORY PROTECCION (Specify type)		If limits are exceeded during sanding or grinding, an approved NIOSH respirator must be used. OSHA 29 CFR 1910 - 134	
VENTILATION	LOCAL EXHAUST	SPECIAL	NA
	MECHANICAL (General) Hoods connected to exhaust ducts and appropriate dust collector.		
PROTECTIVE GLOVES abrasion and/or skin irritation.	Wear gloves to prevent	EYE PROTECTION	Wear safety glasses while sanding or grinding. OSHA 29 CFR 1910 . 133
OTHER PROTECTIVE CLOTHING OR EQUIPMENT Hearing protection OSHA 29 CFR 1910 . 215			
WORK/HYGIENIC PRATICES Ordinary washing and cleanliness practices.			

ABREVIATIONS: NA = NOT APPLICABLE

"THE INFORMATION IS PROVIDED IN GOOD FAITH AND IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER, FABRICA NACIONAL DE LJA, SA de C.V. MAKES NO WARRANTY WITH RESPECT OF THE ACCURACY OF THE INFORMATION AND DISCLAIMS RESPONSIBILITY FOR DAMAGES OF ANY KIND RESULTING FROM THE USE OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEROF. CUSTOMERS ARE ENCOURAGED TO MAKE THEIR OWN DETERMINATION AS TO THE SUITABILITY OF THIS PRODUCT FOR THEIR PURPOSE PRIOR TO USE".