

88560-88565

Darworth Company

3 MILL POND LANE, P.O. BOX 639 • SIMSBURY, CT 06070-0639 • 203-843-1200

MATERIAL SAFETY DATA SHEET

Product Name: **Fl:X® Wood Patch** *all colors*
 Issued Date: **JANUARY 3, 1994** *1985*

<u>Manufacturer:</u>	Darworth Company Division Of Ensign-Bickford Industries, Inc. P.O. Box 639 3 Mill Pond Lane Simsbury, CT 06070	<u>HMIS</u>	Health 1 Flammability 3 Reactivity 0 Personal Protection 0
----------------------	--	-------------	---

Contact For Further Information And Emergency : (203) 843-1200 or (800) 624-7767

SECTION ONE: PRODUCT IDENTIFICATION

Product/Trade Name: **Fl:X® Wood Patch**
 Generic Name: **Wood Putty**
 Chemical Family: **Wood Filler**

SECTION TWO: HAZARDOUS COMPONENTS

COMPONENTS:

Acetone			
C.A.S. Number:	67-64-1	Percentage:	16.8%
T.L.V.:	750 ppm 1780 mg/m ³ 8 hour TWA	P.E.L.:	750 ppm 1800 mg/m ³ 8 hour TWA
	1000 ppm 2380 mg/m ³ 15 min STEL		1000 ppm 2400 mg/m ³ 15 min STEL
Butyl Acetate			
C.A.S. Number:	123-86-4	Percentage:	6.3%
T.L.V.:	150 ppm 713 mg/m ³ 8 hour TWA	P.E.L.:	150 ppm 710 mg/m ³ 8 hour TWA
	200 ppm 950 mg/m ³ 15 min STEL		200 ppm 950 mg/m ³ 15 min STEL
Methyl Ethyl Ketone			
C.A.S. Number:	78-93-3	Percentage:	5.6%
T.L.V.:	200 ppm 590 mg/m ³ 8 hour TWA	P.E.L.:	200 ppm 590 mg/m ³ 8 hour TWA
	300 ppm 885 mg/m ³ 15 min STEL		300 ppm 885 mg/m ³ 15 min STEL
Lactol Spirits			
C.A.S. Number:	64741-55-5	Percentage:	11.83%
T.L.V.:	200 ppm	P.E.L.:	200 ppm
Nitrocellulose **			
C.A.S. Number:	9004-70-0	Percentage:	3.9%
T.L.V.:	Not Established	P.E.L.:	Not Established

88560-88565

88560-88565

MATERIAL SAFETY DATA SHEET

Product Name: **FI:X@ Wood Patch**
Issued Date: **JANUARY 3, 1994**
Page 2

Page 5

Isopropanol

C.A.S. Number:	67-63-0	Percentage:	1.7%
T.L.V.:	400 ppm 985 mg/m ³ 8 hour TWA	P.E.L.:	400 ppm 980 mg/m ³ 8 hour TWA
	500 ppm 1230 mg/m ³ 15 min STEL		500 ppm 1225 mg/m ³ 15 min STEL

** The supplier of nitrocellulose interprets the U.S. Occupational Safety and Health Act and Regulations, including the Hazard Communication Standard 29CFR 1910.1200 Dated November 25, 1993. This ingredient should not be considered a health hazard.

This Product Does Not Contain Ingredients Listed By IARC, NTP, Or OSHA As Carcinogens Or Potential Carcinogens. See Section Nine.

SECTION THREE: PHYSICAL DATA FOR CAULK

Boiling Point:	N/A
Vapor Pressure:	184 mm Hg @ 20°C
Solubility In Water:	Partial
Evaporation Rate:	Less Than Ether
Appearance And Odor:	Light Brown Paste With Acetone Odor

Specific Gravity:	1.28
Percent Volatile:	41.64
Melting Point:	N/A

* Acetone in Product

SECTION FOUR: FIRE AND EXPLOSION HAZARD DATA

Flash Point: -4°F -1+ TOC* **Flammable Limits:** LEL: 2.5% UEL: 13.0%

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide and/or Oxides of Nitrogen.

Extinguishing Media: Fog, Alcohol Foam, CO₂, Dry Chemical

Special Firefighting Procedures: Full protective equipment including self-contained breathing apparatus are recommended. Fog nozzles are preferable to water spray. Water may be used to cool closed containers to prevent auto ignition and explosion.

Unusual Fire And Explosion Hazards: Dry wood patch contains a small percentage of nitrocellulose which is readily ignitable and burns with intense heat. Burning wet wood patch generates toxic fumes (oxides of nitrogen, carbon monoxide, carbon dioxide). People breathing the fumes should promptly seek ventilation and medical care.

Auto Ignition: 869°F *

* Acetone in Product

88560-88565

MATERIAL SAFETY DATA SHEET

Product Name: FI:XO Wood Patch
Issued Date: JANUARY 3, 1994
Page 3

Page 3

SECTION FIVE: HEALTH HAZARD DATA

Permissible Exposure Limit: Refer to Section Two

Threshold Limit Value: Refer to Section Two

Effects Of Acute Overexposure:

Eye Contact:

Acetone - May cause irritation and temporary corneal damage.

Butyl Acetate - May cause redness, or pain.

Isopropanol - May cause irritation.

Lactol Spirits - May cause eye irritation.

Methyl Ethyl Ketone - May cause eye irritation.

Skin Contact:

Acetone - May cause skin irritation.

Butyl Acetate - May cause slight irritation.

Isopropanol - May cause slight irritation.

Lactol Spirits - May cause irritation.

Methyl Ethyl Ketone - May cause irritation.

Inhalation:

Acetone - May cause irritation of nose and throat, headache, nausea, vomiting, dizziness, narcosis, respiratory failure, low blood pressure, central nervous system depression..

Butyl Acetate - Exposure may cause headache, dizziness, eye, nose or throat irritation.

Isopropanol - May cause mild irritation to the nose and throat.

Lactol Spirits - Exposure to vapors or mists may cause irritation of the nose and throat. Signs of nervous system depression (e.g. drowsiness, dizziness).

Methyl Ethyl Ketone - May cause irritation to the nose and throat.

Ingestion:

Acetone - May cause headache, nausea, vomiting, dizziness, gastrointestinal irritation, central nervous system depression.

Butyl Acetate - May irritate the mouth, throat or digestive tract or cause abdominal pain or nausea.

Isopropanol - May cause abdominal pain, hematemesis, nausea, vomiting, and hemorrhage. Central nervous system depression may occur, with headache, dizziness, flushing, incoordination, stupor, confusion, hypotension, and flexia, and refractory narcosis. Oliguria followed by diuresis and coma may also occur.

88560-88575

MATERIAL SAFETY DATA SHEET

Product Name: Fl:X® Wood Patch
Issued Date: JANUARY 3, 1994
Page 4

4085

Lactol Spirits - Ingestion may cause irritation of the digestive tract and signs of nervous system depression.

Methyl Ethyl Ketone - May cause irritation of the digestive tract.

Effects of Chronic Overexposure:

Acetone - No adverse effects reported in available information.

Butyl Acetate Eye - May cause conjunctivitis.

Skin - May cause slight irritation.

Isopropanol - Eye - May cause conjunctivitis.

Skin - Repeated or prolonged may cause dermatitis due to defatting action on the skin.

Lactol Spirits - Deliberate misuse of this product has shown to cause liver, kidney, and brain damage.

Methyl Ethyl Ketone - No adverse effects repeated in available information.

EMERGENCY AND FIRST AID PROCEDURES

Eye Contact: Immediately flush with large quantities of water for at least 15 minutes. Seek immediate medical attention.

Skin Contact: Wash affected areas with soap and large quantities of water. Remove contaminated clothing. Consult physician if irritation from contact persists.

Inhalation: If victim appears to be exhibiting respiratory stress due to high concentrations, remove the victim from the contaminated area. If breathing stops, initiate artificial respiration and seek medical attention.

Ingestion: Do not induce vomiting. Obtain medical attention immediately.

Primary Route Of Entry: (Refer To Section Two) Inhalation, Skin Contact

Medical Conditions Aggravated By Exposure:

Skin- People with pre-existing skin disorders may be more susceptible to the effects of this product.

Inhalation- People with pre-existing respiratory disorders such as asthma, may be aggravated by exposure to this material.

SECTION SIX: REACTIVITY DATA

Hazardous Polymerization: Will not occur.

Stability: This product is stable in most conditions. Use this product only as recommended by manufacturer.

Incompatibility: Oxidizing agents, alkaline materials and strong acids.

Conditions To Avoid: N/A

88560-88565

MATERIAL SAFETY DATA SHEET

Product Name: FI:X® Wood Patch
Issued Date: JANUARY 3, 1994
Page 5

5085

SECTION SEVEN: SPILL OR LEAK PROCEDURES

Procedure: Keep all sources of ignition and hot metal surfaces isolated from spill. Avoid breathing vapors. Provide adequate ventilation. Pick up (wear protective clothing) with a scoop or small shovel. Place an appropriate container for storage prior to disposal. Dispose of product in accordance with applicable local, county, state and federal regulations.

SECTION EIGHT: PROTECTIVE EQUIPMENT TO BE USED

Ventilation

Respiratory Protection: If vapor concentration exceeds the TLV use a National Institute of Occupational Safety and Health approved organic vapor respirator.

Local Exhaust: May be necessary in certain areas with poor general ventilation in order to maintain exposures below the PEL's and TLV's.

Special: N/A

Mechanical: General mechanical ventilation is recommended when product is used in areas without adequate ventilation.

Outdoors: Mechanical ventilation or respiratory protection not required.

Protective Clothing

Protective Gloves: Use impermeable gloves such as neoprene.

Eye Protective: Safety glasses, chemical goggles, and/or face shields are recommended to safeguard against potential eye contact.

Other Equipment: The availability of eye washes and safety showers in work areas is recommended. Impermeable aprons are advised to prevent skin contact.

SECTION NINE: SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing: Keep product containers cool, dry and away from sources of ignition. Keep from freezing. Use and store product with adequate ventilation. Keep product containers closed when not in use.

Other Precautions: Keep out of reach of children. Use with adequate ventilation.

Label Precautions: Keep out of reach of children. Do not take internally.

The information contained in this document is based upon available data and believed to be accurate. However, because the information has been obtained from various sources over which Ensign-Bickford Industries, Inc. (EBI) has no control, including the manufacturer and independent laboratories, it is provided without warranty or representation that it is complete, accurate or can be relied upon. Because EBI cannot anticipate or control the many situations in which this product may be used, EBI makes no warranty that the health and safety precautions set out in this document will be proper under all conditions. It is the sole responsibility of each user of this product to determine what is appropriate for your use and to comply with the requirements of all applicable laws. This information is provided solely for health and safety purposes. Any other use of this information is expressly prohibited.