

#88873

Pg 1

MATERIAL SAFETY DATA SHEET

CHRISTENSON OIL COMPANY, INC.
3747 N. SUTTLE RD.
PORTLAND, ORE. 97217
(503) 286-1673

CHRISTENSON OIL MSDS #AER2/3/4

PAGE 1 OF 6

PRODUCT CODE NO.: NONE

MANUFACTURER: CHRISTENSON OIL COMPANY, INC. 3747 N. SUTTLE RD. P.O. BOX 17339 PORTLAND, ORE. 97217 CONTACT FOR FURTHER INFORMATION: CALL (503) 286-1673	TRANSPORTATION EMERGENCIES: CALL CHEMTREC (800) 424-9300 CONTINENTAL U.S.																		
PRODUCT IDENTIFICATION																			
<table> <tr> <td>PRODUCT NAME</td> <td>:</td> <td>AERO NON-DET MOTOR OIL SAE 20W, 30W, 40W</td> </tr> <tr> <td>SYNONYMS</td> <td>:</td> <td>AERO NON-DET 20, 30, 40</td> </tr> <tr> <td>GENERIC NAME</td> <td>:</td> <td>CRANKCASE OIL</td> </tr> <tr> <td>CHEMICAL FAMILY:</td> <td></td> <td>PETROLEUM HYDROCARBON</td> </tr> <tr> <td>DOT PROPER SHIPPING NAME</td> <td>:</td> <td>NOT APPLICABLE; NOT HAZARDOUS BY DOT REGULATIONS</td> </tr> <tr> <td>ID NUMBER</td> <td>:</td> <td>NONE</td> </tr> </table>		PRODUCT NAME	:	AERO NON-DET MOTOR OIL SAE 20W, 30W, 40W	SYNONYMS	:	AERO NON-DET 20, 30, 40	GENERIC NAME	:	CRANKCASE OIL	CHEMICAL FAMILY:		PETROLEUM HYDROCARBON	DOT PROPER SHIPPING NAME	:	NOT APPLICABLE; NOT HAZARDOUS BY DOT REGULATIONS	ID NUMBER	:	NONE
PRODUCT NAME	:	AERO NON-DET MOTOR OIL SAE 20W, 30W, 40W																	
SYNONYMS	:	AERO NON-DET 20, 30, 40																	
GENERIC NAME	:	CRANKCASE OIL																	
CHEMICAL FAMILY:		PETROLEUM HYDROCARBON																	
DOT PROPER SHIPPING NAME	:	NOT APPLICABLE; NOT HAZARDOUS BY DOT REGULATIONS																	
ID NUMBER	:	NONE																	

88873

SECTION I - INGREDIENTS

	TLV	UNITS	AGENCY	TYPE	TERM	TWA
OIL MIST, IF GENERATED	5.00	MG/M3	OSHA	FULL		

THE IDENTITIES OF INGREDIENTS THAT ARE TRADE SECRETS ARE EXCLUDED FROM THIS LIST.

SECTION II - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT:
FOR DIRECT CONTACT, FLUSH THE AFFECTED EYE(S) WITH CLEAN WATER, IF IRRITATION OR REDNESS DEVELOPS, SEEK MEDICAL ATTENTION.

88873

Pg 2

MATERIAL SAFETY DATA SHEET

CHRISTENSON OIL MSDS #AER2/3/4

PAGE 2 OF 6

SKIN CONTACT:

DO NOT USE GASOLINES, THINNERS OR SOLVENTS TO REMOVE PRODUCT FROM SKIN. WIPE MATERIAL FROM SKIN AND REMOVE CONTAMINATED CLOTHING. CLEANSE AFFECTED AREA(S) THOROUGHLY BY WASHING WITH SOAP AND WATER AND, IF NECESSARY, A WATERLESS SKIN CLEANSER. IF IRRITATION OR REDNESS DEVELOPS AND PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION (BREATHING):

OF IRRITATION OF NOSE AND THROAT DEVELOPS, MOVE AWAY FROM SOURCE OF EXPOSURE AND INTO FRESH AIR. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. IF VICTIM IS NOT BREATHING OR IF BREATHING OR IF BREATHING DIFFICULTIES DEVELOP, ARTIFICIAL RESPIRATION OR OXYGEN SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. SEEK IMMEDIATE MEDICAL ATTENTION.

INGESTION (SWALLOWING):

IF VICTIM IS CONSCIOUS AND ALERT, GIVE 2 TO 3 CUPS OF MILK OR WATER TO DRINK. SEEK MEDICAL ATTENTION. TO PHYSICIAN: EMESIS OR LAVAGE IS NOT RECOMMENDED FOR INGESTIONS OF MINUTE QUANTITIES OR TASTES OF MOST HYDROCARBONS. MEDICAL OPINION IS DIVIDED FOR LARGER INGESTIONS. EMESIS OR LAVAGE HAS BEEN RECOMMENDED FOR THOSE PETROLEUM PRODUCTS WHICH HAVE A HIGH ORAL TOXICITY. GASTRIC LAVAGE WITH A CUFFED ENDOTRACHEAL TUBE IS RECOMMENDED BY SOME PHYSICIANS TO PREVENT ASPIRATION.

SECTION III - POTENTIAL ADVERSE HEALTH EFFECTS**EYE CONTACT:**

THIS MATERIAL MAY CAUSE EYE IRRITATION. DIRECT CONTACTS MAY CAUSE BURNING, TEARING AND REDNESS.

SKIN CONTACT:

THIS MATERIAL MAY CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS, BURNING AND DERMATITIS.

INHALATION (BREATHING):

EXPOSURE TO MISTS, OR PROLONGED OR REPEATED EXPOSURE TO FUMES OR VAPORS THAT MAY BE GENERATED WHEN THIS MATERIAL IS HEATED, MAY CAUSE IRRITATION OF NOSE AND THROAT.

INGESTION (SWALLOWING):

ACCIDENTAL INGESTION OF THIS MATERIAL MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT.

88873

Pg 3

MATERIAL SAFETY DATA SHEET

CHRISTENSON OIL MSDS #AER2/3/4

PAGE 3 OF 6

COMMENTS:

USED MOTOR OIL: FOLLOWING REPEATED SKIN APPLICATIONS, ANIMAL STUDIES HAVE SHOWN THAT USED MOTOR/CRANKCASE OILS HAVE CAUSED AN INCREASED INCIDENCE OF SKIN CANCER IN MICE. IT IS THEREFORE RECOMMENDED THAT PROLONGED OR REPEATED CONTACT WITH MOTOR/CRANKCASE OILS BE AVOIDED.

SECTION IV - SPECIAL PROTECTION INFORMATION**VENTILATION:**

IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE IN MAINTAINING AIRBORNE CONCENTRATIONS BELOW THE ESTABLISHED EXPOSURE LIMITS (SEE SECTION I), ADDITIONAL VENTILATION OR EXHAUST SYSTEMS MAY BE REQUIRED.

RESPIRATORY PROTECTION:

IF AIRBORNE CONCENTRATIONS EXCEED RECOMMENDED LIMITS, A SUITABLE FILTER TYPE RESPIRATOR SHOULD BE WORN. (SEE SECTION I)

PROTECTIVE GLOVES:

THE USE OF GLOVES IMPERMEABLE TO THE SPECIFIC MATERIAL HANDLED IS ADVISED TO PREVENT SKIN CONTACT AND POSSIBLE IRRITATION.

EYE PROTECTION:

APPROVED EYE PROTECTION TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OF INJURY IS RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT:

IT IS SUGGESTED THAT A SOURCE OF CLEAN WATER BE AVAILABLE IN WORK AREA FOR FLUSHING EYES AND SKIN. BARRIER CREAMS THAT ARE SPECIFIC FOR OILBASED MATERIALS ARE RECOMMENDED WHEN GLOVES ARE IMPRACTICAL.

SECTION V - REACTIVITY DATA**STABILITY:**

STABLE

CONDITIONS TO AVOID (STABILITY):

AVOID CONTACT WITH ANY SOURCE OF HEAT OR FLAME.

INCOMPATIBILITY (MATERIALS TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS SUCH AS CHLORINE, PERMANGANATES AND DICHROMATES.

88873

Page 4

MATERIAL SAFETY DATA SHEET

CHRISTENSON OIL MSDS #AER2/3/4

PAGE 4 OF 6

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY FIELD MAJOR AMOUNTS OF OXIDES OF CARBON AND MINOR AMOUNTS OF OXIDES OF SULFUR AND NITROGEN.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

SECTION VI - SPILL OR LEAK PROCEDURES
HIGHWAY OR RAILWAY SPILLS
CALL CHEMTREC 800-424-9300 CONT. U.S.

PRECAUTIONS IN CASE OF RELEASE OR SPILL:

COLLECT LEAKING LIQUID IN SEALABLE CONTAINERS. ABSORB SPILLED LIQUID IN SAND OR INERT ABSORBENT. CONTACT FIRE AUTHORITIES AND APPROPRIATE STATE/LOCAL AGENCIES. IF SPILL OF ANY AMOUNT IS MADE INTO OR UPON U.S. NAVIGABLE WATERS, THE CONTIGUOUS, OR ADJOINING SHORELINES, NOTIFY COST GUARD NATIONAL RESPONSE CENTER (PHONE NUMBER 800-424-8802).

WASTE DISPOSAL METHOD:

DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS:

STORE IN A COOL, DRY LOCATION. KEEP AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION V). AVOID GENERATING OIL MISTS WHILE HANDLING. AVOID PROLONGED OR REPEATED SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. FOR USED MOTOR OIL: LAUNDRER SATURATED CLOTHING BEFORE WEARING AND DISCARD-OIL SOAKED SHOES AND UNWASHABLE CLOTHING.

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

HAZARD RANKING

NFPA	HEALTH HAZARD: 0	0 = LEAST	DOT FLAMMABILITY	FLASH POINT
HAZARD	FLAMMABILITY: 1	1 = SLIGHT	CLASSIFICATION	
CLASS	REACTIVITY: 0	2 = MODERATE		
	OTHER: 0	3 = HIGH	NOT REGULATED	440F (COC)
		4 = EXTREME		

88873 Pg 5

MATERIAL SAFETY DATA SHEET

CHRISTENSON OIL MSDS #AER2/3/4

PAGE 6 OF 6

EXTINGUISHING MEDIA:

EXTINGUISH WITH DRY CHEMICAL, CO₂, WATER SPRAY, FOAM, SAND OR EARTH.
WATER AND FOAM MAY CAUSE PROTHING.

FIRE & EXPLOSION HAZARDS:

THIS MATERIAL WILL BURN, BUT WILL NOT IGNITE READILY.

FIRE FIGHTING PROCEDURES:

WATER SPRAY MAY BE USEFUL IN MINIMIZING VAPORS AND COOLING CONTAINERS EXPOSED TO HEAT AND FLAME. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. MOVE UNDAMAGED CONTAINERS FROM FIRE AREA IF YOU CAN DO SO WITHOUT RISK.

SECTION IX - PHYSICAL DATA

APPROX BOILING POINT	VAPOR DENSITY	EVAPORATION RATE	% VOLATILE
+600F (316C)	HEAVIER THAN AIR	SLOWER THAN ETHER	NEGLIGIBLE
% SOLUBILITY IN WATER	SPECIFIC GRAVITY	APPEARANCE	ODOR
NEGLIGIBLE	N/A	CLEAR, AMBER LIQUID	CHARACTERISTIC

SECTION X - PRECAUTIONARY LEVEL

CAUTION! USED MOTOR OIL IS A POSSIBLE SKIN CANCER HAZARD BASED ON TESTS WITH LABORATORY ANIMALS. AVOID PROLONGED OR REPEATED SKIN CONTACT. AVOID MAKING OR BREATHING OIL MIST. USE ADEQUATE VENTILATION. WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING.

SECTION XI - DOCUMENTARY INFORMATION

ISSUE DATE	:	01/01/94	PRODUCT CODE NO.	:	NONE
MSDS NO.	:	AER2/3/4	PREV. PROD. CODE NO.:	:	NONE
			PREV. MSDS NO.	:	NONE

88873

Pg 6

MATERIAL SAFETY DATA SHEET

CHRISTENSON OIL MSDS #DND3

PAGE 6 OF 6

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OF COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product and on the condition that he assume the risk of his use thereof.