

# MATERIAL SAFETY DATA SHEET

## Radiator Specialty Company

1900 WILKINSON BLVD. CHARLOTTE, NC 28208 (704) 377-6555

POISON INFORMATION & EMERGENCY: 303-623-5716

# 88875

182

### MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

### US DEPARTMENT OF LABOR

Occupational Safety and Health Administration. (Non-Mandatory Form) Form Approved OMB No. 1218-0072

### SECTION I GENERAL INFORMATION

**PRODUCT NAME** PENETRANT LUBRICANT  
**PART NUMBER** BUN3 -12/6

NOTE: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

### SECTION II HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

COMPONENT	WT%	C.A.S. NO.	TLV (ACGIH--XX--OSHA-----)
Perchloroethylene*	65-80	127-18-4	50 ppm
Naphthenic petroleum oil mixture	20-30	64742-53-6/ 64742-52-5	5 mg/M <sup>3</sup> (Mist)
Carbon Dioxide	1-3	124-38-9	5000 ppm (air)

\*Indicates toxic chemical subject to the reporting requirements of section 313 of Title III and 40CFR 372. Warning: This product contains a chemical known to the State of California to cause cancer.  
 \*Carcinogen by International Agency for Research on Cancer (IARC)

NFPA AEROSOL LEVEL 1

**Comments:**

Components not identified are non-hazardous according to 29 CFR 1910.1200

### SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Specific Gravity (H <sub>2</sub> O=1)	1.34	pH	does not apply
Solubility in Water	insoluble	Solubility in Solvent	hydrocarbons
Flash Point (Method) - F°	does not flash (COC)	% Volatiles By Wt.	approx 60%
Melting Point - F°	does not apply	Boiling Point - F°	248°
Vapor Pressure (mmHg)	not available	Vapor Density (Air=1)	5.83
Evaporation Rate (Butyl Acetate=1)	.95		
Appearance and Odor	Clear, heavy liquid with sweet odor.		

### SECTION IV FIRE AND EXPLOSION HAZARD DATA

<b>EXTINGUISHING MEDIA:</b>	non flammable		
Water Fog	Foam	CO <sub>2</sub>	Dry Chemical

**SPECIAL FIRE FIGHTING PROCEDURES.** Wear self-contained, positive pressure breathing apparatus and protective clothes. see Hazardous Decomposition Products below

**UNUSUAL FIRE AND EXPLOSION HAZARDS** Fire may cause aerosol cans to burst, even violently. Cool containers by water spray.

88875

BUN3-12/8

**SECTION V REACTIVITY DATA**

88875

*Page 2*

Stable	XX	Unstable		Corrosive		NO	Hazardous Polymerization?	Yes	No	XX
Incompatibilities		None								
Hazardous Decomposition or Byproducts		Hydrogen Chloride and possible traces of phosgene								

**SECTION VI HEALTH HAZARD INFORMATION**

Recommended TLV of Product		5 mg/m <sup>3</sup> (Mist)	
EYE CONTACT		Mildly irritating	
SKIN CONTACT		Prolonged contact may cause irritation, dermatitis.	
INHALATION		Moderately toxic, nausea, dizziness, headache, CNS damage	
INGESTION		Slightly toxic, irritation of mouth and GI tract	
OTHER Prolonged exposure to high levels may bring on or aggravate existing Liver, Kidney damage/ diseases. Minimize human exposure.			

**SECTION VII EMERGENCY AND FIRST AID PROCEDURES**

EYE CONTACT		Flush eyes with water for 15 minutes	
SKIN CONTACT		Wash with soap and water. Remove contaminated clothing/shoes. Clean contaminated items before reuse or discard.	
INHALATION		Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.	
INGESTION		NEVER ADMINISTER ADRENALINE FOLLOWING PERCHLOROETHYLENE OVEREXPOSURE!!! If conscious drink large quantities of water. Do not induce vomiting. Take immediately to a hospital or physician.	

**SECTION VIII SPECIAL PROTECTION INFORMATION**

	CONSUMER	BULK HANDLING (Prolonged Exposure)
RESPIRATORY PROTECTION	NONE	If TLV is exceeded wear NIOSH approved respirator
VENTILATION	Use with adequate ventilation	General
EYE PROTECTION	NONE	Fully protective goggles or face shield
PROTECTIVE CLOTHING	NONE	Butyl rubber gloves and apron

**SECTION IX PRECAUTIONS FOR SAFE HANDLING AND USE**

SPILL OR LEAK PROCEDURE	Ventilate area, recover with adsorbents, dispose of through a permitted hazardous waste management facility.
WASTE DISPOSAL METHOD	Dispose of in accordance with all applicable government laws and regulations.
STORAGE AND HANDLING PRECAUTIONS	Store in a cool, dry place away from heat sources
OTHER PRECAUTIONS Wearing contact lens during use is inadvisable. <b>KEEP AWAY FROM CHILDREN AND ANIMALS. DO NOT PUNCTURE OR INCINERATE CANS.</b>	

**HAZARD INFORMATION LABEL DATA**

HAZARD CODE	FLAMMABILITY	REACTIVITY
4- Extreme	0	1
3- High	2	
2- Moderate		
1- Slight		
0- Negligible		
*pr=pressure		

HEALTH SPECIAL

Supersedes NEW 1996

OSHA Revised DEC 1996

Title HORST ABRAMOWSKI

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification.