

94602

04/13/92

105

Section I. General Information

MSDS Identifier Code

Supplier ID: Ricoh Product Code: 886007

Identity: 800/870/880 Landa Toner Pak

Manufacturer's Name and Address:

Ricoh Corporation  
5 Dedrick Place

W. Caldwell, NJ 07006

Distributor's Name and Address:

Savin Corporation  
P.O. Box 10270  
Stamford, CT 06904

Emergency Telephone Number: (800) 336-6737

Telephone Number for Information: (201) 882-2000, (800) 336-6737

Synonyms & Common Names: 800/870/880 Landa Toner Pak

Hazard Classes: Combustible Liquid N.O.S.

Chemical Formula: Mixture

Registry numbers

CAS Number: 0-00-0

RTECS Number: N/App

Date Prepared: 04/10/92 Filed/Prepared By: Kristina Sage

Section II. Hazardous Ingredients/Identity Information

Composition

Component	%	CAS #	OSHA Pel	ACGIH TLV
Hydrotreated heavy naphtha (ISOPAR)	89.00	64742-48-9	N/App	300ppm**
*Carbon black	02.00	1333-86-4	3.5mg/m3	3/5mg/m3
Acrylic Polymer	03.00	25068-63-7	N/App	N/App
*Wax	06.00	9002-88-4	N/App	N/App

\*Carbon Black is listed on the Massachusetts Substance List and the IARC Monograph.

The IARC has evaluated the evidence for the \*Wax is listed on the IARC Monograph.

The IARC has evaluated the evidence for the carcinogenicity of Carbon Black and Wax as inadequate to determine a carcinogenic risk for humans.

\*\*Recommended by Exxon

94602

941002

Page 5

Exposure Limits (TLV/PEL)  
OSHA: See data above  
NIOSH: Not applicable  
ACGIH: See data above  
State: Not applicable  
Other: None

---

### Section III. Physical/Chemical Characteristics

---

Boiling Point: 161-199C                      Specific Gravity: 0.78@15.6C  
Vapor Pressure: <10mmHg at 25C            % Volatile by Volume: Not applicable  
Melting Point: Not applicable              Vapor Density (Air=1): Greater than 5  
Evaporation Rate (n-BuAc=1): Approx. 0.3

Solubility in Water: Negligible: Less than 0.1%

Appearance and Odor: Black liquid, faint petroleum hydrocarbon odor

---

### Section IV. Fire and Explosion Hazard Data

---

Flash Point and Method: 41C T.C.C.

Explosive Limits: LEL 0.7 UEL 6.5  
Comments: Not applicable

Extinguishing Media: Foam, dry chemicals, or carbon dioxide.

Special Fire-Fighting Procedures: If a leak or spill has ignited, use standard fire-fighting procedures for petroleum based liquids. Minimize breathing gases, vapor, fumes or decomposition products. Fire-fighters should use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

Unusual Fire and Explosion Hazards: Not applicable

---

### Section V. Reactivity Data

---

Stability: Stable  
Conditions to Avoid: Not applicable

Incompatibility (Materials to Avoid): Avoid contact with strong oxidizers such as liquid Cl<sub>2</sub>, or conc. O<sub>2</sub>.

Hazardous Decomposition or Byproducts: Will not occur.

Hazardous Polymerization: Will not Occur  
Conditions to Avoid: Not applicable

94602

04/13/92

3085

RICOH CORPORATION  
MATERIAL SAFETY DATA SHEET

Page #3

-----  
Section VI. Health and Hazard Data  
-----

Routes of Entry: Skin, inhalation, ingestion

Health Hazards of Short-Term exposure (Acute)

Eyes: Slight conjunctival irritation.

Skin: Mild irritation under conditions of excessive exposure.

Inhalation: No untoward effects.

LD50 (rat): Greater than 12,400 mg/m3 (approximately 2000 ppm)

Ingestion: Acute oral toxicity: Greater 5g/kg bodyweight.

Health Hazards of Long-Term exposure (Chronic): Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which may vary from person to person. As a precaution, exposure to liquid, vapor, mist or fumes should be minimized.

Carcinogenicity: See Section II

NTP? No IARC Monographs? Yes OSHA Regulated? No

Signs and Symptoms of Exposure: High vapor concentrations (greater than approximately 1000 ppm) are irritative to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic, and may have other central nervous system effects.

Medical Conditions Generally Aggravated by Exposure: Not applicable

Emergency and First Aid Procedures

First Aid

Eyes: If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides.

Skin: In the case of skin contact, remove any contaminated clothing and cleanse skin thoroughly with waterless hand cleaner followed by washing with soap and water.

Inhalation: If overcome by vapors, remove from exposure and call a physician immediately.

Ingestion: If ingested, do not induce vomiting; call a physician immediately.

Additional Information: Ames test result: Negative

94602

4 of 5

-----  
Section VII. Precautions for Safe Handling and Use  
-----

Steps to be Taken in Case Material is Released or Spilled: Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or mounding. Advise authority if product has entered or may enter sewers, watercourses, or extensive land areas. Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

Waste Disposal Method: Waste liquid should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Precautions to Be Taken in Handling and Storing:

CAUTION - COMBUSTIBLE LIQUID

Keep away from heat, open flame and sparks. Keep out of reach of children.

Other Precautions: Empty containers retain residue (liquid and/or vapor) and can be dangerous. In order to avoid the risks of explosion, do not pressure, cut or expose such containers to heat, sparks or other sources of ignition.

-----  
Section VIII. Control Measures  
-----

Respiratory Protection: None needed under normal conditions of use.

Ventilation

Local Exhaust: None needed under normal conditions of use.

Special: None

Mechanical (general): Adequate ventilation

Other: None

Protective Gloves: None needed under normal conditions.

Eye Protection: None needed under normal conditions of use.

Other Protective Clothing or Equipment: None needed under normal conditions of use.

Work and Hygienic Practices: Minimize breathing vapor or mist. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Remove contaminated shoes and thoroughly clean and dry before reuse. Cleanse skin thoroughly after contact, before breaks and meals

RICOH CORPORATION  
MATERIAL SAFETY DATA SHEET

94602

04/13/92

585

at the end of work periods. Product is readily removed from skin by  
waterless hand cleaners followed by washing with soap and water.