

94636, 94637

1004

MATERIAL SAFETY DATA SHEET

NASHUA CORPORATION
44 Franklin Street
Nashua, NH 03061

Facility Emergency Tel.No. 1(603)880-5555
Facility Information Tel.No. 1(800)258-1370

SECTION I - IDENTIFICATION

PRODUCT NAME: 7300 Series Liquid Toner
MSDS: 200
DATE: 4/91
FORMULA: Liquid Organic Mixture
DIVISION: OPD
CHEMICAL FAMILY: Petroleum Organic Solvent
MEDICAL EMERGENCY TELEPHONE (Poison Center): (303) 623-5716
TRANSPORTATION EMERGENCY TELEPHONE (Chemtrec): (800) 424-9300

SECTION II - HAZARDOUS COMPONENTS (Typical Values)

<u>INGREDIENTS</u>	<u>CAS NO.</u>	<u>WT %</u>	<u>ACGIH(TLV)</u>	<u>OSHA(PEL)</u>
Isopar H/ (Isoparaffinic Hydrocarbon)	64742-48-9	>85%	1900 mg/m ³	*NE
Carbon Black	1333-86-4	<5.0%	3.5 mg/m ³	3.5 mg/m ³
Mixture of Acrylic/ Polymers & Resins	*NE	<10.0%	*NE	*NE

* None Established

SECTION III - PHYSICAL DATA

Boiling Point: For Isopar H 335-380°F or (169-193°C)
Melting Point: Not Applicable
Vapor Pressure: (mmHg.) <10 @ 25°C for Isopar H
Vapor Density (AIR=1): >5.0 for Isopar H
Evaporation Rate: (Butyl Acetate = 1) 0.3 for Isopar H
Volatile Fraction by Weight: Not Estimated
Solubility in Water (By Weight %): Immiscible
Specific Gravity (H₂O=1): <1.0
pH: Not Applicable
Appearance: Black Mobile Liquid
Odor: Petroleum Solvent Odor

94636, 94637

94636, 94637

Jay

SECTION IV--FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 111°F or 43.9°C Tag Closed Cup

EXTINGUISHING MEDIA: Foam, Dry Chemical, CO₂.
Water may be ineffective but should be used to keep fire exposed containers cool.

SPECIAL FIRE FIGHTING PROCEDURES: Wear full protective clothing and a self-contained breathing apparatus to avoid breathing toxic fumes.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Emits toxic fumes upon thermal decomposition. Vapors are heavier than air and can flow to a source of ignition.

SECTION V--HEALTH HAZARD DATA

A. SARA--Title III Hazard Categories

Immediate: See Section V (Acute Exposure Effects)

B. ACUTE EXPOSURE EFFECTS (NOTE: Pertains to Finished Product)

Eye Contact: May cause irritation.

Skin Contact: May cause irritation.

Inhalation: Normally no problem, but inhalation of mist could cause respiratory irritation.

Ingestion: May cause irritation of the mucous membranes or digestive tract and minute amounts aspirated into the lungs may cause mild to severe pulmonary injury and possible death.

C. FIRST AID (Applies to Finished Product)

Eyes: Immediately flush with plenty of running water for at least 15 minutes. Obtain medical attention.

Skin: Flush affected areas promptly with water for 15 minutes. Remove contaminated clothing. In case of continued irritation consult physician.

Inhalation: For over-exposure, remove to fresh air.

Ingestion: Obtain immediate medical attention. Do not induce vomiting.

D. CHRONIC HALTH EFFECTS (NOTE: Pertains to each ingredient listed in Section 2 per 29 CFR Sect. 1910-1200)

Carbon Black has been tested for mutagenicity on Species S. typhimurium with negative result.

All Other Ingredients in Section II - A computerized literature search of national databases did not yield any chronic effects associated with these materials.

CARCINOGENICITY LISTING NTP no IARC no OSHA no

94636, 94637

Zaj

SECTION VI--REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Excessive heat or flame.

INCOMPATIBILITY: Avoid strong oxidizers such as chlorates, bromates, and nitrates.

HAZARDOUS DECOMPOSITION PRODUCTS: CO₂, Carbon Monoxide and aldehydes.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII--DISPOSAL INFORMATIONSpill, Leak, or Release

NOTE: Review Section IV and Section VIII before proceeding with clean up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean up. Dike spill. Prevent liquid from entering sewers, water ways or low areas. Soak up with sawdust, sand, oil dry or other absorbent material.

Waste Disposal

Recover nonusable free liquid, contaminated water, and nonusable solid material and dispose of in an approved and permitted incineration treatment system.

SECTION VIII--SPECIAL PROTECTION INFORMATION

- A. Respiratory Protection: None needed with working mixtures and normal room ventilation. Wear MSHA/NIOSH approved respirator whenever prolonged exposure to vapor is likely.
- B. Ventilation: Room ventilation is sufficient. Avoid use of product in unventilated areas.
- C. Skin & Eye Protection: Simple protection is suggested, e.g., eye glasses with side shields. Chemical gloves and aprons are recommended.

SECTION IX--STORAGE CONDITIONS

Store in well ventilated area. Keep container tightly closed. Do not store with incompatible materials (see Section VI). Do not store or consume food, drink or tobacco in area where they may become contaminated with this material.

94636, 94637
MSDS # 200

Hoy

SECTION X--HAZARDOUS REGULATIONS**A. DOMESTIC: Non Regulated**

IMO: Petroleum Distillates (Containing Isoparaffinic Hydrocarbons)
Class 3.3, UN 1268

IATA/ICAO: Naphtha Distillate (Isoparaffinic Hydrocarbon) UN 1268

B. OSHA Regulations for Labeling

Carbon Black is listed in OSHA 29 CFR 1910-1000 Table Z-1, and therefore must be listed on any container in the workplace which contains this substance in quantities of one percent or greater.

SECTION XI--HAZARD COMMUNICATION

4 = Extreme

3 = High

2 = Moderate

1 = Slight

0 = Insignificant

HEALTH 1FLAMMABILITY 2REACTIVITY 0SPECIAL**SECTION XII-TSCA INFORMATION**

TSCA LISTING: All ingredients in this finished product are listed on the EPA TSCA Inventory (see Section II).

SECTION XIII--FEDERAL--SARA TITLE III NOTIFICATION

Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313).

Components present in this product at a level which could require reporting under the statute are:

NONE

While this material is furnished in good faith, NO WARRANTY EXPRESS OR IMPLIED, OF MERCHANTABILITY FITNESS OR OTHERWISE IS MADE as to the product described above. This material is offered only for your consideration and Nashua Corporation including its divisions, affiliates and subsidiaries, shall not in any event be liable for special, incidental or consequential damages in connection with its publication. Likewise, no statement made herein shall be construed as a permission or recommendation for the use of any product in a manner that might infringe existing patents.

TECHNICAL CONTACT

Technical Manager, Officer Products Division
Nashua Corporation
44 Franklin Street
Nashua, NH 03061
Telephone No. 1(603)880-2323